

TECHNOLUBE PRODUCTS CO -- A9952, LUBE OIL -- 9150-00-273-2389

===== Product Identification =====

Product ID:A9952, LUBE OIL

MSDS Date:05/26/1988

FSC:9150

NIIN:00-273-2389

MSDS Number: BSCVC

=== Responsible Party ===

Company Name:TECHNOLUBE PRODUCTS CO

Address:5814 E 61ST ST

City:LOS ANGELES

State:CA

ZIP:90040-3412

Country:US

Info Phone Num:213-727-7792

Emergency Phone Num:213-727-7792

Preparer's

Name:RICHARD J. EBERHARDT

CAGE:8Y842

=== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

Box:City:LOS ANGELES

State:CA

ZIP:90058

Country:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

===== Composition/Information on Ingredients =====

Ingred Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE

CAS:64742-46-7

RTECS #:JN9379645

Fraction by Wt: 212F,>100C

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extingu

ishing Media:WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, FOAM
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:SLIGHTLY COMBUSTIBLE WHEN HEATED ABOVE
FLASH POINT. WILL RELEASE FLAMMABLE VAPORS WHICH CAN BURN OR
EXPLODE IN CONFINED AREA WITH IGNITION SOURCE.

===== Accidental Release Measures =====
=====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. EVACUATE AREA.
WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT. CONTAIN SPILL. STOP LEAK
IF CAN DO SO WITHOUT RISK. ABSORB LIQUID WITH SUITABLE ABSORBENT
MATERIAL. COLLECT FOR DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH
ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND
HIGH
TEMPERATURES. EXCESSIVE MISTING MAY CAUSE SLIPPERY FLOORS.
Other Precautions:AVOID SKIN CONTACT. LAUNDRY CONTAMINATED CLOTHING
BEFORE REUSE. WEAR PROPER SHOES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. MAY USE APPROVED SOHA
RESPIRATOR AND CARTRIDGE FOR OIL MIST.
Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION TO
MAINTAIN EXPOSURE LEVELS.
Protective Gloves:NITRILE GLOVES
Eye Protection:SA
FETY GLASSES OR GOGGLES
Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO AVOID
SKIN CONTACT. AN EMERGENCY EYE WASH STATION AND SHOWER SHOULD BE
AVAILABLE.
Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT
AND BEFORE EATING DRINKING OR SMOKING.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>482F,>250C
Melt/Freeze Pt:M.P/F.P Text:NOT GIV

EN
Vapor Pres:< 0.1
Vapor Density:> 1
Spec Gravity:0.878
Evaporation Rate & Reference:< 1 (ETHER = 1)
Solubility in Water:SLIGHT
Appearance and Odor:BROWN OILY LIQUID WITH A PETROLEUM ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:DO NOT HEAT ABOVE FLASH POINT
Hazardous Decomposition Products:CARBON MONOXIDE AND ASPHYXIANTS.

===== Disposal Consideration

S =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.