View NSN Online: https://aerobasegroup.com/nsn/6850-01-028-4642

EMERSON & CUMING,INC., DIV OF W.R.GRACE AND CO. -- ECCOSLIP 122S PINK

6850-01-028-4642

============= Product Identification =================

Product ID:ECCOSLIP 122S PINK

MSDS Date:07/19/1988

FSC:6850

NIIN:01-028-4642

MSDS Number: BSDRY === Responsible Party ===

Company Name: EMERSON & CUMING, INC., DIV OF W.R. GRACE AND CO.

Address:61 HOLTON STREET

City:WOBURN

State:MA ZIP:01180 Country:US

Info Phone Num:800-225-1

936

Emergency Phone Num:800-225-1936

CAGE:0JMR7

=== Contractor Identification ===

Company Name: EMERSON & CUMING, INC., DIV OF W.R.GRACE AND CO.

Address:61 HOLTON STREET

Box:City:WOBURN

State:MA ZIP:01180 Country:US

Phone:800-225-1936

CAGE:0JMR7

Company Name: GRACE W R & CO EMERSON & CUMING DEWEY & ALMY CHEM

Address:869 WASHINGTON ST

City:CANTON State:MA

ZIP:02021-2513 Country:US

Phone:617-935-4850

CAGE:04552

======= Composition/Information on Ingredients ========

Ingred Name: SILICON

E RESIN (POLYDIMETHYL SILOXANE) Other REC Limits: NONE SPECIFIED Ingred Name:PIGMENTS Other REC Limits: NONE SPECIFIED Ingred Name:DICHLORODIFLUOROMETHANE (SARA III) (PROPELLANT) CAS:75-71-8 RTECS #:PA8200000 Other REC Limits: NONE SPECIFIED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM: 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinoge

nicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: NO KNOWN HEALTH EFFECTS EXCEPT FOT SLIGHT IRRITATION TO EYES ON CONTACT. CHRONIC: NONE GIVEN. Explanation of Carcinogenicity: NONE OF THE COMPOUNDS IN THIS CHEMICAL IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure: EYES: REDNESS, DISCOMFORT.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: EYES:

FLUSH EYES WITH LOTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERISTS. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERISTS FROM ANY OTHER ROUTE OF EXPOSURE.

Flash Point Method:TOC Flash Point:480F,249C

Extinguishing Media: CARBON DIOXIDE, ALCOHOL FOAM, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: EVACUATE AREA. WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND SCBA. COOL FIRE EXPOSED CONT

AINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:TOXIC FUMES MAY BE EVOLVED UPON EXPOSURE TO HEAT OR OPEN FLAME.
======== Accidental Release Measures =========
Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL AND PUT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE SLIPPING HAZARD. WEAR PROPER PROTECTIVE EQUIPMENT AS SPECIFIE D IN THE PROTECTIVE EQUIPMENT SECTION. VENTILATE. Neutralizing Ag ent:NONE RECOMMENDED.
=========== Handling and Storage ============
Handling and Storage Precautions:AVOID CONTACT WITH SKIN AND EYES. USE ONLY IN WELL VENTILATED AREA. KEEP CONTAINERS AWAY FROM EXCESSIVE HEAT. Other Precautions:NONE
====== Exposure Controls/Personal Protection =======
Respiratory Protection:SELECT NIOSH/MSHA APPROVED RESPIRATOR BASED UPON CONTAMINATION LEVELS FOUND IN THE WORK PLACE. Ventilation:LOCAL AND MECHANICAL (GENERAL) VENTILATION AS REQUIRED TO
CONTAMINATION LEVELS FOUND IN THE WORK PLACE. Ventilation:LOCAL AND MECHANICAL (GENERAL) VENTILATION AS REQUIRED TO MAINTAIN VAPOR AND MIST CONCENTRATIONS BELOW PELS EST. BY OSHA Protective Gloves:RUBBER IF REQUIRED. Eye Protection:SAFETY GLASSES OR SAFETY GOGGLES.
CONTAMINATION LEVELS FOUND IN THE WORK PLACE. Ventilation:LOCAL AND MECHANICAL (GENERAL) VENTILATION AS REQUIRED TO MAINTAIN VAPOR AND MIST CONCENTRATIONS BELOW PELS EST. BY OSHA Protective Gloves:RUBBER IF REQUIRED.
CONTAMINATION LEVELS FOUND IN THE WORK PLACE. Ventilation:LOCAL AND MECHANICAL (GENERAL) VENTILATION AS REQUIRED TO MAINTAIN VAPOR AND MIST CONCENTRATIONS BELOW PELS EST. BY OSHA Protective Gloves:RUBBER IF REQUIRED. Eye Protection:SAFETY GLASSES OR SAFETY GOGGLES. Other Protective Equipment:EYE WASH STATION. Work Hygienic Practices:WASH THOROUGHLY AFTER USE AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

0.98

Evaporation Rate & Reference: N/K (BUTYL ACETATE=1)

Solubility in Water: NEGLIGIBLE

Appearance and Odor:TRANSLUCENT PINK GREASE CONTAINED IN 6 OZ AEROSOL CAN.

Percent Volatiles by Volume: NONE

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS AND ACIDS.

Stability Condition to Avoid:STORAGE IN OPEN CONTAINER, EXPOSURE TO HEAT AND/OR OPEN FLAME, EXPOSURE TO ACIDS AND/OR STRONG OXIDIZERS.

Hazardous Decompo

sition Products:DURING COMBUSTION, CARBON MONOXIDE, CARBON DIOXIDE, HYDROCARBONS, AND SILICON DIOXIDE FUMES AND/OR

VAPORS.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. DO NOT INCINERATE AEROSOL CANS. MANUFACTURER STATES MATERIAL IS NOT A HAZARDOUS WASTE AS DEFINED IN 40 CFR SEC 261.3.

Disclaimer (provided with this information by the compiling age ncies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.