

XEROX CORPORATION -- 4405-16,ECP-PROCESS BLACK TYPE H,TYPE V80 TONER --
6850-01-198-7958

=====
Product Identification
=====

Product ID:4405-16,ECP-PROCESS BLACK TYPE H,TYPE V80 TONER

MSDS Date:01/09/1992

FSC:6850

NIIN:01-198-7958

MSDS Number: BSDTC

=== Responsible Party ===

Company Name:XEROX CORPORATION

Address:100 CLINTON AVE SOUTH, XROX SQ

City:ROCHESTER

State:NY

ZIP:14644-1877

Country:US

Info

Phone Num:800-828-6571/FAX 716-422-6449

Emergency Phone Num:716-422-2177/1230

CAGE:26921

=== Contractor Identification ===

Company Name:VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

Address:2710 WALSH AVE.

Box:City:SANTA CLARA

State:CA

ZIP:95051-0905

Country:US

Phone:716-422-2177 (XEROX CORP, NY)

CAGE:50804

Company Name:XEROX CORPORATION

Address:100 CLINTON AVE SOUTH

Box:City:ROCHESTER

State:NY

ZIP:14644-1877

Country:US

Phone:800-828-6571/716-422-2177

CAGE:26921

=====
Composition/
=====

Information on Ingredients =====

Ingred Name:HYDROTREATED HEAVY NAPHTHA
CAS:64742-48-9
Fraction by Wt: 80-90%
Other REC Limits:NONE SPECIFIED

Ingred Name:POLYMER - CLAIMED AS TRADE SECRET.
Other REC Limits:NONE SPECIFIED

Ingred Name:PIGMENTS -CLAIMED AS TRADE SECRET.
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS >10 G/KG
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carci
nogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:NONE PRESENT
Effects of Overexposure:PROLONGED CONTACT WITH SKIN MAY CAUSE
IRRITATION AND DERMATITIS. INHALATION: RESPIRATORY ARREST AND CNS
DEPRESSION.
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED.
EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN
CONTA
CT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS
PERSIS T. INGESTION:DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF
WATER. GET MEDICAL HELP IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:102F,39C
Lower Limits:0.8
Upper Limits:7.0
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:USE AIR-SUPPLIED BREATHING EQUIPMENT FOR
ENCLOSED AREAS.COOL CONTAINERS WIT

H WATER SPRAY.AVOID BREATHING
VAPOR OR FUMES.

Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDANTS
LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. RECOVER FREE LIQUID
USING AN ABSORBANT MATERIAL (VERMICULITE,FIRE
RETARDANT,SAWDUST,ETC.).

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. STORE AWAY FROM
OPEN FLAMES,STRONG OXIDANTS.

Other Precautions:AVOID BREATHING VAPORS. AVOID REPEATED OR PROLONGED
SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. USE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED OR WHEN
SPRAYING OR USING IN CONFINED SPACES.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS
NORMALLY ADEQUATE.

Protective Gloves:NEOPRENE, NITRILE

Eye Protection:NONE NORMALLY REQUIRED.

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:320F,160C

Vapor Pres:1

Vapor Density:5.0

Spec Gravity:0.77

Evapora

tion Rate & Reference:0.3 (N-BUTYL ACETATE=1)

Solubility in Water:IMMISCIBLE

Appearance and Odor:BLACK LIQUID/SLIGHT ODOR

Percent Volatiles by Volume:80-100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN,SODIUM OR CALCIUM HYPOCHLORITE.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:FUMES,SMOKE AND

CARBON MONOXIDE IN THE

CASE OF INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:THE WASTE TONER MAY BE CLASSIFIED AS AN

IGNITABLE HAZARDOUS WASTE UNDER FEDERAL AND/OR STATE REGULATIONS

AND SHOULD BE DISPOSED AT AN APPROVED DISPOSAL SITE OR FACILITY IN

ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for u

se by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.