

VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC. -- CAM 2 80 W 90 GO -- 9150-01-313-2191

=====
Product Identification
=====

Product ID:CAM 2 80 W 90 GO

MSDS Date:04/24/1990

FSC:9150

NIIN:01-313-2191

MSDS Number: BSDTS

=== Responsible Party ===

Company Name:VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC.

Address:200 E MAIN ST

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Info Phone Num:606

-264-7000

Emergency Phone Num:800-ASHLAND/800-274-5263

CAGE:72527

=== Contractor Identification ===

Company Name:BUDGET OIL CO

CAGE:8P476

Company Name:VALVOLINE OIL CO

Address:3499 BLAZER PKY

Box:14000

City:LEXINGTON

State:KY

ZIP:40512

Country:US

Phone:606-357-7206 / 800-274-5263

CAGE:72527

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM OIL

Fraction by Wt: 85- 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL M

IST)

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS UNKNOWN.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE AND CHRONIC- TOXICOLOGICAL
TESTING INDICATES THAT SIMILAR PRODUCTS ARE NOT HAZARDOUS AS
DEFINED BY OSHA (29 CFR 1910.1200).
Effects of Overexposure:MAY CAUSE EYE, SKIN, RESPIRATORY TRACT
IRRITATION.
Medical Cond Aggravate
d by Exposure:NONE KNOWN.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALATION:REMOVE TO
FRESH AIR. PROVIDE CPR IF NEEDED. EYES:FLUSH WITH WATER FOR 15
MINUTES, HOLDING EYELIDS OPEN. SKIN:REMOVE EXCESS. WASH SKIN WITH
SOAP & WATER . INGESTION:DO NOT INDUCE VOMITING. KEEP PERSON WARM &
QUIET. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:>300F,>1
49C
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
WATER/FOAM MAY CAUSE FROTHING. COOL FIRE EXPOSED CONTAINERS WITH
WATER SPRAY.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. DO NOT SPRAY WATER
INTO CONTAINERS OF HOT, BURNING LIQUID.
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE DUE TO PRESSURE
BUILD UP.

=====
===== Accidental Release Measures =====

Spill Rel
ease Procedures:ABSORB SPILLS WITH NON-FLAMMABLE ABSORBENT
MATERIAL SUCH AS EARTH, SAND OR VERMICULITE. SWEEP UP AND TRANSFER
TO A CONTAINER FOR PROPER DISPOSAL. CLEAN AREA WITH APPROPRIATE
CLEANER.
Neutralizing Agent:NOT RELEVANT

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY PLACE AWAY FROM STRONG
OXIDANTS. DO NOT USE CUTTING OR WELDING TORCH ON THIS CONTAINER
(EVEN EMPTY).
Other Precautions:DO NOT GET IN

EYES, ON SKIN OR ON CLOTHING. WASH
THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.
Ventilation:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE.
Protective Gloves:NOT NORMALLY REQUIRED.
Eye Protection:NOT NORMALLY REQUIRED.
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS AND LEGS.
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROC
EDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
NRC/State Lic Num:NOT RELEVANT
Vapor Density:>1
Spec Gravity:0.902
Evaporation Rate & Reference: