

BEL-RAY CO INC. -- 2765 MOLYLUBE 503 -- 9150-00-141-4481

=====
===== Product Identification =====

Product ID:2765 MOLYLUBE 503
MSDS Date:11/05/1993
FSC:9150
NIIN:00-141-4481
MSDS Number: BSFHW
=== Responsible Party ===
Company Name:BEL-RAY CO INC.
Address:111-BOWMAN AVE
Box:526
City:FARMINGDALE
State:NJ
ZIP:07727
Country:US
Info Phone Num:201-938-2421
Emergency Phone Num:201-938-2421
CAGE:KO218

=== Con
tractor Identification ===
Company Name:BEL-RAY CO INC.
Address:111-BOWMAN AVE
Box:526
City:FARMINGDALE
State:NJ
ZIP:07727
Country:US
Phone:201-938-2421
CAGE:KO218
Company Name:BEL-RAY COMPANY INC.
Address:1201 BOWMAN AVE
Box:526
City:FARMINGDALE
State:NJ
ZIP:07727
Country:US
Phone:732-938-2421
CAGE:12474

=====
===== Composition/Information on Ingredients =====

Ingred Name:PROPRIETARY INGREDIENT # 6017
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/M3 (STEL)

ingred Name:PROPRIETARY INGREDIENT # 6037
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (TOTAL DUST)
ACGIH TLV:5 MG/M3 (TOTAL DUST)

Ingred Name:PROPRIETARY INGREDIENT # 6061
Other REC Limits:0.5 MG/M3 (MFR)
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CONTACT MAY CAUSE SOME EYE
|
RRITATION. CHRONIC: PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN
OR EYE IRRITATION.
Explanation of Carcinogenicity:MANUFACTURER STATED NO CARCINOGENS
PRESENT.
Effects of Overexposure:SKIN: REDNESS, DISCOMFORT. EYES: REDNESS,
DISCOMFORT.
Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LOTS OF WATER; CALL A PHYSICIAN IF NEEDED.
SKIN: REMOVE CONTAMINATED CLOTHES. WASH THOROUGHLY
WITH SOAP &
WATER. INGESTION: DO NOT INDUCE VOMITING, SEEK MEDICAL HELP.
INHALATION: REMO VE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMTOMS
DEVELOP.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>660F,>349C
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fire/Explosion Hazard:NONE NOTED.

===

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN AND RECOVER. ABSORB REMAINDER WITH INERT MATERIAL AND PLACE IN A CONTAINER FOR LATER DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AND WELL-VENTILATED AREA. KEEP AWAY FROM HEAT, OPEN FLAMES & SPARKS, OXIDIZING MATERIALS.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE. DO NOT WELD OR EXPOSE TO HEAT OR FLAMES AS THEY MAY EXPLODE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE TLV/PEL FOR OIL MIST.

Ventilation:GENERAL/LOCAL TO MAINTAIN TLV/PEL FOR OIL MIST.

Protective Gloves:NITRILE

Eye Protection:GOGGLES WITH SIDE SHIELDS

Other Protective Equipment:NONE

Work Hygienic Practices:

AVOID CONTACT WITH EYES & SKIN. WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Vapor Pres:10(AIR=1)

Spec Gravity:0.92 (WATER=1)

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK GREASE, SLIGHT OIL ODOR.

Percent Volatiles by Volume: