Product ID:E-50 EMULSIFIER/REMOVER MSDS Date:01/20/1992 FSC:6850 NIIN:01-266-4553 Kit Part:Y MSDS Number: BSFLR === Responsible Party === Company Name: MET-L-CHEK COMPANY Address:1639 EUCLID ST **City:SANTA MONICA** State:CA ZIP:90404-3770 Country:US Info Phone Num:213-450-1111 Emergency Phone Num:213-450-1111 CAGE:98733 === Contractor Identification === **Company Nam** e:MET-L-CHEK COMPANY Address:1639 EUCLID ST Box:00000 **City:SANTA MONICA** State:CA ZIP:90404 Country:US Phone:310-450-1111/FAX 310452-4046 CAGE:98733

Ingred Name:NAPHTHA, MEDIUM ALIPHATIC CAS:64742-88-7 Other REC Limits:TLV 100 PPM (MFR)

Ingred Name:2-BUTOXYETHANOL CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: < 5% Other REC Limits:NONE RECOMMENDED OSHA PEL:S, 50 PPM ACGIH TLV:S, 25 PPM; 9293

====== Hazards I

dentification =======================

LD50 LC50 Mixture:TLV = 100PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

- Health Hazards Acute and Chronic:LIQUID IS MINIMALLY IRRITATING TO THE EYES AND SLIGHTLY IRRITATING TO THE SKIN. VAPORS MAY BE IRRITATING TO NOSE, THROAT AND RESPIRATORY TRACT AND CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.
- Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIO
- NS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.
- Effects of Overexposure: IRRITATION OF EYES, SKIN, NOSE, THROAT OR RESPIRATORY TRACT. GIDDINESS OR HEADACHE. POSSIBLE VOMITING IF INGESTED.
- Medical Cond Aggravated by Exposure:PRE-EXISTING EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:FLUSH EYES AND SKIN WITH PLENTY OF WATER. REMOVE VICTIM TO

FRESH AIR. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF REQUIRED. DO NOT INDUCE VOMITING.

Flash Point Method:TCC Flash Point:140F,60C Lower Limits:1 % Upper Limits:6 % Extinguishing Media:WATER FOG, DRY CHEMICAL, CARBON DIOXIDE Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. DO NOT USE A DIRECT STREAM OF W ATER. Unusual Fire/Explosion Hazard:CONTAINERS EXPOSED TO INTENSE HEAT OF FIRE SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILD-UP

WHICH COULD RUPTURE CONTAINER.

Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. WEAR APPROPRIATE PROTECTIVE CLOTHING. SOAK UP WITH CLAY, SAND OR OTHER ABSORBENT. PLACE IN NON-LEAKING CONTAINERRS AND SEAL FOR PROPER DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY

MANUFACTURER.

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, AND FLAME, KEEP CONTAINERS CLOSED WHEN NOT IN USE, USE WITH ADEQUATE VENTILATION. Other Precautions: NONE SPECIFIED BY MANUFACTURER. Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR SELECTION. Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION TO MAINTAIN EXPOSURE LEVELS. Protective Gloves: CHEMICAL RESISTANT Eye Protection: SAFETY GLASSES OR GOGGLES Other Protective Equipment: CLOTHING AS REQUIRED TO MINIMIZE SKIN CONTACT. Work Hygienic Practices: WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING. Supplemental Safety and Health AVOID PROLONGED BRE ATHING OF VAPORS.

HCC:F4 Boiling Pt:B.P. Text:355F,179C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:< 5 Vapor Density:5.4 Spec Gravity:0.770 Evaporation Rate & amp; Reference: