

PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV -- ENAMEL ALKYD, GLOSS, LO VOC CT GREEN 14110, ID 774422 -- 8010-00-286-7748

=====  
Product Identification  
=====

Product ID:ENAMEL ALKYD, GLOSS, LO VOC CT GREEN 14110, ID 774422

MSDS Date:03/10/1993

FSC:8010

NIIN:00-286-7748

MSDS Number: BSFNT

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

S

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C)  
(LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100

000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/STEL 150 PPM

ACGIH TLV:100 PPM/STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ACETATE (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)  
(LFL 1.7; UFL 7.6)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM/STEL 200 PPM

ACGIH TLV:150 PPM/STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (SOLVENT) (SARA III) (VAPOR P

RESSURE 70

MM HG @ 20C) (LFL 2.0; UFL 10.0)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/STEL 300 PPM

ACGIH TLV:200 PPM/STEL 300 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOAMYL KETONE (SOLVENT)

CAS:110-12-3

RTECS #:MP3850000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:50 PPM, 240 MG/M3

ACGIH TLV:50 PPM, 240 MG/M3

Ingred Name:MINERAL SPIRITS (SOLVENT) (VAPOR PRESSURE 2 MM HG @ 20C)

(LFL: 1.0 UF

L: 7.0)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 115F) AND SOURCES  
OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY  
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON  
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND  
LOCAL REGULATIONS. THE PROPER RCRA CLASSIFICATION WOULD BE D001.

Disclaimer (provided with this information by t  
he compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.