

HY-KLAS PAINTS, INC -- L-XXX-7342 LATEX FLAT WALL -- 8010-00-579-9533

=====
Product Identification
=====

Product ID:L-XXX-7342 LATEX FLAT WALL

MSDS Date:07/02/1990

FSC:8010

NIIN:00-579-9533

MSDS Number: BSFPL

=== Responsible Party ===

Company Name:HY-KLAS PAINTS, INC

Box:3607

City:LOUISVILLE

State:KY

ZIP:40201-3607

Country:US

Info Phone Num:502-634-9406

Emergency Phone Num:502-634-9406/502-589-82

22

CAGE:KO343

=== Contractor Identification ===

Company Name:HY-KLAS PAINTS INC

Box:3607

City:LOUISVILLE

State:KY

ZIP:40201-3607

Country:US

Phone:502-634-9406

CAGE:0HN95

Company Name:HY-KLAS PAINTS, INC

Box:10205

City:LOUISVILLE

State:KY

ZIP:40210

Phone:(502) 634-9406

CAGE:KO343

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL (SARA III) (VAPOR PRESSURE 0.1 MM HG)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 2.6%

Other REC Limits:NONE SPECIFIE

D
ACGIH TLV:50 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:ACUTE; INHALATION: VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA AND IRRITATION OF NOSE, THROAT & LUNGS. EYE: SLIGHTLY IRRITATING TO EYES. OVEREXPOSURE TO ETHYLENE GLYCOL HAS BEEN SUGGESTED AS A CAUSE OF L IVER ABNORMALITIES, KIDNEY DAMAGE AND CENTRAL NERVOUS SYSTEM DAMAGE.
Effects of Overexposure:CHRONIC; SKIN: IRRITATING TO SKIN UPON REPEATED OR PROLONGED CONTACT.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYE AND SKIN CONTACT: FLUSH WITH WATER. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN.

=====
Fire Fighting Measures
=====

Fire Fighting Procedures:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

=====
Accidental Release
Measures
=====

Spill Release Procedures:DIKE AND CONTAIN SPILL WITH INERT MATERIAL (E.G., SAND, EARTH). TRANFER LIQUID TO CONTAINERS FOR RECOVERY OR DISPOSAL AND SOLID DIKING MATERIALS TO SEPARATE CONTAINERS FOR DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP FROM FREEZING.
Other Precautions:DO NOT TAKE INTERNALLY.

=====
Exposure Controls/Personal Protection
=====

Ventilation:MECH

ANICAL LOCAL EXHAUST.
Protective Gloves:IMPERVIOUS
Eye Protection:SPLASH GOGGLES
Work Hygienic Practices:WASH HANDS BEFORE EATING.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:212F,100C
Vapor Density:> AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:69+/-3

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

=====

===== Disposal Considerations =====

Waste Disposal Methods:ACCORDING TO FEDERAL, STATE AND LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should s
seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.