

WELLBORN PAINT MFG CO -- TT-P-1952B WHITE, P/C 184602 -- 8010-01-017-1512

=====
Product Identification
=====

Product ID:TT-P-1952B WHITE, P/C 184602
MSDS Date:12/11/1985
FSC:8010
NIIN:01-017-1512
MSDS Number: BSGGC
=== Responsible Party ===
Company Name:WELLBORN PAINT MFG CO
Address:215 ROSSMOOR RD
City:ALBUQUERQUE
State:NM
ZIP:87012
Country:US
Info Phone Num:505-877-5050
Emergency Phone Num:505-
877-5050/505-843-2551
CAGE:WELLB

=== Contractor Identification ===
Company Name:WELLBORN PAINT MFG CO
Address:215 ROSSMOOR RD
City:ALBUQUERQUE
State:NM
ZIP:87012
Country:US
Phone:505-877-5050
CAGE:WELLB

=====
Composition/Information on Ingredients
=====

Ingred Name:TEXANOL (VAPOR PRESSURE 1.00 MM HG @ 68F) (LEL 0.6)
CAS:25265-77-4
RTECS #:UF6000000
Fraction by Wt: 1.4%
Other REC Limits:NONE SPECIFIED

Ingred Name:ETHYLENE GLYCOL (SARA III) (VAPOR PRESSURE 0.10 MM HG @

F) (LEL 3.2)
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 2.4%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:100 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:TITANIUM DIOXIDE (NUISANCE DUST)
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 16.9%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:10 MG/M3

Ingred Name:ALUMINUM OXIDE (SARA III) (NUISANCE DUST)
CAS:1344-28-1
RTECS #:BD1200000
Fraction by Wt: 1.8%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:10 MG/M3

Ingred Name:SILICA AMORPHOUS
CAS:112
945-52-5
RTECS #:VV7310000
Fraction by Wt: 2.4%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:6 MG/M3

Ingred Name:CALCIUM CARBONATE (NUISANCE DUST)
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: 13.2%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:10 MG/M3

Ingred Name:AMMONIA
CAS:1336-21-6
RTECS #:BQ9625000
Fraction by Wt: TRACE
Other REC Limits:NONE SPECIFIED
ACGIH TLV:25 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Health Hazard

s Acute and Chronic:INHALATION: VAPOR OR MIST MAY IRRITATE EYES, NOSE, THROAT & MUCOUS MEMBRANES PRODUCING DIZZINESS, HEADACHES, NAUSEA IN POORLY VENTILATED AREAS. SKIN: PROLONGED/REPEATED CONTACT WITH LATEX PAINT MAY CAUSE SKIN IRRITATION. EYE: DIRECT CONTACT WITH LATEX PAINT MAY RESULT IN EYE IRRITATION.

Effects of Overexposure:CHRONIC: INHALATION MAY HAVE AN EFFECT ON CENTRAL NERVOUS SYSTEM. MAY CAUSE DIZZINESS OR NARCOSIS.

=====
===== First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. CONSULT PHYSICIAN. SPLASH (EYES): FLUSH WITH WATER FOR 15 MIN. SPLASH (SKIN): WASH WITH SOAP AND WATER. REMOVE & WASH CLOTHING. INGESTION: IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK. DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Extinguishing Media:NON COMBUSTIBLE

Fire Fighting Procedures:LATEX COATINGS WILL NOT BURN. THEY MAY SPATTER

IF TEMP EXCEEDS BOILING POINT. DRY FILMS ARE CAPABLE OF BURNING.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT AND OPEN FLAME.

=====
===== Accidental Release Measures =====

Spill Release Procedures:DIKE AND CONTAIN SPILL WITH INERT MATERIAL & TRANSFER THE LIQUID TO CONTAINERS FOR RECOVERY AND DISPOSAL. KEEP SPILL OUT OF SEWERS AND OPEN BODIES OF WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING. DO NOT TAKE INTERNALLY. AVOID PROLONGED CONTACT OR INHALATION.

Other Precautions:WHEN TINTED, THIS BASE MAY CONSIST OF UP TO 2 FL OZ OF UNIVERSAL MACHINE COLORANTS WHICH CONTAIN ETHYLENE GLYCOL. ON AVERAGE THIS TINTED BASE WOULD CONTAIN AN ADDITIONAL AMOUNT OF 0.6% BY WEIGHT OF ETHYLENE GLYCOL (TLV/TWA = 100 PPM).

=====
===== Exposure Controls/Personal P

rotection =====

Respiratory Protection:WEAR APPROVED ORGANIC VAPOR RESPIRATOR UNLESS VENTILATION EQUIPMENT IS ADEQUATE TO KEEP AIRBORNE CONCENTRATIONS BELOW THE EXPOSURE STANDARDS.

Ventilation:GENERAL MECHANICAL VENT MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS BELOW TLV RANGES, USE LOCAL EXHAUST.

Protective Gloves:IMPERMEABLE SOLVENT RESISTANT GLOVES

Eye Protection:SFTY GOGGLES,CHEM SFTY GLASSES,FACE SHLD

Other Protective Equipment:IMPEREABLE APRONS & PROTECTIVE CLOTHING ARE

ADVISED WHEN WORKING WITH THIS PRODUCT. USE HEAD CAPS WHENEVER POSSIBLE.

Work Hygienic Practices:EYE WASHES AND SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER TAN N-BU/AC

Percent Volatiles by Volume:63.0

===== Stability and Reactivity Data =====

Stabil

ity Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HIGH TEMPERATURES OR HIGH HUMIDITIES

Conditions to Avoid Polymerization:HIGH TEMPERATURES OR HIGH HUMIDITIES

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR LANDFILL LIQUID AND CONTAMINATED DIKING MATERIAL, ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use

by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.