

INLAND TECHNOLOGY INC -- FP140 PARTSMMASTER 140 -- 6850-01-378-0610

=====
Product Identification
=====

Product ID:FP140 PARTSMMASTER 140

MSDS Date:10/08/1993

FSC:6850

NIIN:01-378-0610

MSDS Number: BSGKR

=== Responsible Party ===

Company Name:INLAND TECHNOLOGY INC

Address:2612 PACIFIC HWY NO C

City:TACOMA

State:WA

ZIP:98424

Country:US

Info Phone Num:800-552-3100

Emergency Phone Num:800-255-3924

CAG

E:0K209

=== Contractor Identification ===

Address:401 E 27TH STREET

Box:City:TACOMA

State:WA

ZIP:98421-1203

Country:US

Phone:800-552-3100/253-383-1177

CAGE:0K209

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROTREATED HEAVY NAPHTHA (C10-C11 HYDROCARBONS)

CAS:64742-48-9

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:

NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: NO HEALTH EFFECTS FORM

INHALATION NOTED. LOW ORAL AND DERMAL TOXICITY. CONTACT MAY CAUSE EYE IRRITATION. CHRONIC: PROLONGED OR REPEATED SKIN EXPOSURE CAN LEAD TO MILD IRRITATION, DEFATTING AND DERMATITIS.

Explanation of Carcinogenicity:NO INGREDIENTS OF A CONCENTRATION OF

0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:EYES: REDNESS, TEARING, DISCOMFORT. SKIN:

DEFATTING,

REDNESS, ITCHING, DISCOMFORT.

Medical Cond Aggravated by Exposure:SKIN CONTACT MAY AGGRAVATE EXISTING

DERMATITIS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS OPEN. IF IRRITATION PERSISTS, SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP AND WATER. INGESTED: DO NOT INDUCE VOMITING! GET IMMEDIATE MEDICAL ATTENTION. INHALED: REMOVE TO FRESH AIR AND ASSIST BREATHING IF NEEDED. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:105F,41C

Lower Limits:0.6%

Upper Limits:7%

Extinguishing Media:FOAM, DRY CHEMICAL, WATER SPRAY OR CARBON DIOXIDE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR FOR ENCLOSED OR CONFINED SPACES OR AS OTHERWISE NEEDED.

Unusual Fire/Explosion Hazard:NONE KNOWN.

=====
===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IMMEDIATELY. SHUT OFF AND ELIMINATE ALL SOURCES OF IGNITION. CONTAIN AND COLLECT SPILLED MATERIAL. ABSORB RESIDUE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:USE AND STORE AWAY FROM SOURCES OF IGNITION, STRONG OXIDIZING AGENTS AND STRONG MINERAL ACIDS. KEEP CONTAINER SEALED WHEN NOT IN USE.

Other Precautions:DO NOT EAT, DR

INK OR SMOKE IN VICINITY. MINIMIZE
BREATHING VAPOR OR MIST. AVOID PROLONGED OR REPEATED CONTACT WITH
SKIN. WASH CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE
OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED
AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IN ACCORDANCE WITH 29 CFR
1910.134.

Ventilation:USE ADEQUATE MECHANICAL DILUTION V
ENTILATION WHENEVER

PRODUCT IS USED IN A CONFINED SPACE, HEATED ABOVE ROOM TEMPERATURE

Protective Gloves:NITRILE OR BUTYL

Eye Protection:SAFETY GLASSES/GOGGLES/FACE SHIELD

Other Protective Equipment:NONE NORMALLY REQUIRED. HMIS: EYE WASH
STATION AVAILABLE.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

READ AND UNDERSTAND ALL CAUTIONS, LABELS, AND MSDS BEFORE USING
PRO

DUCT. MSDS ENTERED INITIALLY PRIOR TO PROCUREMENT TO ENABLE
SERVICES TO EVALUATE PRODUCT.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:310F,154C

Vapor Pres:4 (AIR=1)

Spec Gravity:0.75 (WATER=1)

Evaporation Rate & Reference: