

INLAND TECHNOLOGY INC -- FP140 PARTSMaster 140 -- 6850-01-378-0610

=====
Product Identification
=====

Product ID:FP140 PARTSMaster 140

MSDS Date:10/08/1993

FSC:6850

NIIN:01-378-0610

MSDS Number: BSGKR

=== Responsible Party ===

Company Name:INLAND TECHNOLOGY INC

Address:2612 PACIFIC HWY NO C

City:TACOMA

State:WA

ZIP:98424

Country:US

Info Phone Num:800-552-3100

Emergency Phone Num:800-255-3924

CAG

E:0K209

=== Contractor Identification ===

Address:401 E 27TH STREET

Box:City:TACOMA

State:WA

ZIP:98421-1203

Country:US

Phone:800-552-3100/253-383-1177

CAGE:0K209

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROTREATED HEAVY NAPHTHA (C10-C11 HYDROCARBONS)

CAS:64742-48-9

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:

NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: NO HEALTH EFFECTS FORM
INHALATION NOTED. LOW ORAL AND DERMAL TOXICITY. CONTACT MAY CAUSE
EYE IRRITATION. CHRONIC: PROLONGED OR REPEATED SKIN EXPOSURE CAN
LEAD TO MILD IRRITATION, DEFATTING AND DERMATITIS.

Explanation of Carcinogenicity:NO INGREDIENTS OF A CONCENTRATION OF
0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:EYES: REDNESS, TEARING, DISCOMFORT. SKIN:
DEFATTING,
REDNESS, ITCHING, DISCOMFORT.

Medical Cond Aggravated by Exposure:SKIN CONTACT MAY AGGRAVATE EXISTING
DERMATITIS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS
OPEN. IF IRRITATION PERSISTS, SEE DOCTOR. SKIN: REMOVE CONTAMINATED
CLOTHES. WASH WITH SOAP AND WATER. INGESTED: DO NOT INDUCE
VOMITING! GET IMMEDIATE MEDICAL ATTENTION. INHALED: REMOVE TO
FRESH AIR AND ASSIST BREATHING IF NEEDED. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:105F,41C

Lower Limits:0.6%

Upper Limits:7%

Extinguishing Media:FOAM, DRY CHEMICAL, WATER SPRAY OR CARBON DIOXIDE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE GEAR FOR ENCLOSED OR CONFINED SPACES OR AS
OTHERWISE NEEDED.

Unusual Fire/Explosion Hazard:NONE KNOWN.

=====
===== Accidental Release Measures =====

Spill Release Procedures:STOP LEAK IMMEDIATELY. SHUT OFF AND ELIMINATE
ALL SOURCES OF IGNITION. CONTAIN AND COLLECT SPILLED MATERIAL.
ABSORB RESIDUE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:USE AND STORE AWAY FROM SOURCES OF
IGNITION, STRONG OXIDIZING AGENTS AND STRONG MINERAL ACIDS. KEEP
CONTAINER SEALED WHEN NOT IN USE.

Other Precautions:DO NOT EAT, DR

INK OR SMOKE IN VICINITY. MINIMIZE BREATHING VAPOR OR MIST. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. WASH CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IN ACCORDANCE WITH 29 CFR 1910.134.

Ventilation:USE ADEQUATE MECHANICAL DILUTION VENTILATION WHENEVER

PRODUCT IS USED IN A CONFINED SPACE, HEATED ABOVE ROOM TEMPERATURE

Protective Gloves:NITRILE OR BUTYL

Eye Protection:SAFETY GLASSES/GOGGLES/FACE SHIELD

Other Protective Equipment:NONE NORMALLY REQUIRED. HMIS: EYE WASH STATION AVAILABLE.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

READ AND UNDERSTAND ALL CAUTIONS, LABELS, AND MSDS BEFORE USING PRODUCT.

MSDS ENTERED INITIALLY PRIOR TO PROCUREMENT TO ENABLE SERVICES TO EVALUATE PRODUCT.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:310F,154C

Vapor Pres:4 (AIR=1)

Spec Gravity:0.75 (WATER=1)

Evaporation Rate & Reference: