

INLAND TECHNOLOGY INC -- SKYSOL 200,FS 200 -- 6850-01-381-4427

===== Product Identification =====

Product ID:SKYSOL 200,FS 200

MSDS Date:10/13/1994

FSC:6850

NIIN:01-381-4427

MSDS Number: BSGMV

=== Responsible Party ===

Company Name:INLAND TECHNOLOGY INC

Address:401 EAST 27TH STREET

City:TACOMA

State:WA

ZIP:98421

Country:US

Info Phone Num:800-552-3100/206-383-1177/838-9889

Emergency Phone Num:800-

255-3924

CAGE:0K209

=== Contractor Identification ===

Address:401 E 27TH STREET

Box:City:TACOMA

State:WA

ZIP:98421-1203

Country:US

Phone:800-552-3100/253-383-1177

CAGE:0K209

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS/C12-C13 PARAFFINIC HYDROCARBONS

CAS:64475-85-0

RTECS #:PY8240000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:D-LIMONENE

CAS:5989-27-5

Other REC Limits:NONE RECOMMEND

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:TLV; 5 MG/M3 AS OIL MIST  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY TRACT. ACUTE- MISTS MAY CAUSE RESPIRATORY TRACT IRRITATION. EYE CONTACT MAY CAUSE IRRITATION. LOW ORDER ORAL AND DERMAL TOXICITY. CHRONIC- PROLONGED OR REPEATED SK IN EXPOSURE CAN LEAD TO MILD IRRITATION, DEFATTING AND DERMATITIS.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:EYES, SKIN, RESPIRATORY TRACT IRRITATION  
Medical Cond Aggravated by Exposure:SKIN CONTACT MAY AGGAVATE EXISTING DERMATITIS.

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET IMMEDIATE MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:144F,62C  
Lower Limits:0.6%  
Upper Limits:7%  
Extinguishing Media:FOAM, DRY CHEMICAL, WATER SPRAY OR CARBON DIOXIDE.  
Fire Fighting Procedures:WEAR AIR-SUPPLIED BREATHING EQUIPMENT AND FULL PROTECTIVE GEAR FOR ENCLOSED OR CONFINED SPACES OR AS OTHERWISE NEEDED.  
Unusual Fire/Explosion Hazard:NONE KNOWN.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. CONTAIN SPILL. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH/USE PUMP (EXPLOSION PROOF). GROUND ALL HANDLING EQUIPMENTS. PREVENT LIQUID FROM ENTERING SEWERS.  
Neutralizing

Agent:NOT RELEVANT

=====  
===== Handling and Storage =====

Handling and Storage Precautions:USE AND STORE AWAY FROM SOURCES OF IGNITION, STRONG OXIDIZING AGENTS AND STRONG ACIDS. KEEP CONTAINER SEALED WHEN NOT IN USE.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. KEEP OUT OF REACH OF CHILDREN.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:USE ADEQUATE MECHANICAL DILUTION VENTILATION WHENEVER PRODUCT IS USED IN A CONFINED SPACE, HEATED ABOVE ROOM TEMPERATURE

Protective Gloves:NITRILE, IF NEEDED

Eye Protection:SPLASH GOGGLES IF EYE CONTACT POSSIBLE

Other Protective Equipment:EYE WASH STATION, UNIFORM IF REQUIRED

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC:V4

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:340F,171C

Vapor Pres:4

Spec Gravity:0.78

Evaporation Rate & Reference: