View NSN Online: https://aerobasegroup.com/nsn/6850-00-209-7230

CASTROL INC.,BRAY PRODUCTS DIV. -- BRAYCO 483 -- 6850-00-209-7230

============ Product Identification ==============

Product ID:BRAYCO 483 MSDS Date:07/26/1991

FSC:6850

NIIN:00-209-7230

MSDS Number: BSHJD === Responsible Party ===

Company Name: CASTROL INC., BRAY PRODUCTS DIV.

Address:16715 VON KARMAN AVE., SUITE 230

City:IRVINE State:CA ZIP:92714 Country:US

Info Phone Num:714-660-9414 Emergency Phone Num:714-660-9 414/800-424-9300(CHEMTREC)

CAGE:EO288

=== Contractor Identification ===

Company Name: CASTROL INC., BRAY PRODUCTS DIV.

Address:16715 VON KARMAN AVE., SUITE 230

City:IRVINE State:CA ZIP:92714 Country:US

Phone:714-660-9414/ABROAD 202-4837616COLL

CAGE:EO288

Company Name: CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS

DIV

Address:1001 WEST 31ST STREET

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-1280 Country:US

Phone:800-621-2661/ FAX: 630-241-4140

CAGE:2R128

Company Name: EMULTEC INDUSTRIAL PR

ODUCTS INC Address:1150 HAYDEN DR SUITE 100 Box:City:CHARROLLTON State:TX ZIP:75006 Country:US Phone:972-417-1288 CAGE:0WA27 ======= Composition/Information on Ingredients ========= Ingred Name: NON-HAZARDOUS INGREDIENTS Fraction by Wt: 100% Other REC Limits: NONE RECOMMENDED ============= Hazards Identification ======================== LD50 LC50 Mixture: TLV FOR OIL MIST IS 5 MG/M3. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IAR C:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE & CHRONIC- EYE CONTACT MAY CAUSE MILD IRRITATION. PROLONGED/REPEATED SKIN CONTACT MAY CAUSE IRRITATION & DEFATTING. EXCESSIVE INHALATION OF VAPORS/MIST MAY CAUSE NASAL/RESPIRATORY IRRITATION & D IZZINESS. INGESTION CAN CAUSE GI IRRITATION, NAUSEA, VOMITING, DIARRHEA. TARGET ORGANS:EYES, SKIN, RESPIRATORY TRACT. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: EYE IRRITATION, REDNESS, TEARING, BLURRED VISION, S KIN IRRITATION, DEFATTING, DERMATITIS, RESPIRATORY/NASAL

IRRITATION, HEADACHE, DIZZINESS, NAUSEA, POSSIBLY UNCONSCIOUSNESS. ASPHYXIATION, GASTROINTES TINAL TRACT IRRITATION, VOMITING, **DIARRHEA**

Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL ATTENTION IF S

YMPTOMS PERSIST. SKIN:WIPE MATERIAL FROM SKIN. WASH SKIN WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED: REMOVE TO FRESH AIR & PROVIDE O XYGEN/CPR IF NEEDED. ORAL:DO NOT INDUCEVOMITING. ASPIRATION HAZARD. GET MEDICAL ATTENTION IMMEDIATELY. Flash Point Method:COC Flash Point:495F,257C Extinguishing Media: DRY CHEMICAL, CO2, FOAM. DON'T USE A DIRECT STREAM OF WATER. PRODU CT WILL FLOAT & REIGNITE. Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard: EMPTY CONTAINERS MAY RETAIN PRODUCT RESIDUE WHICH CAN IGNITE EXPLOSIVELY. ============ Accidental Release Measures ================ Spill Release Procedures: REMOVE IGNITION SOURCES. DO NOT ALLOW MATERIAL TO ENTER DRAINS, SEWERS OR WATERWAYS. ABSORB SPILL WITH NON-FLAMMABLE ABSORBENT AND PLACE INTO PROPER CONTAINERS FOR DISPOSAL. Neutralizing Agent: NOT RELEVANT ============ Handling and Storage =========================== Handling and Storage Precautions: STORE AT ROOM TEMPERATURES IN VENTILATED AREA AWAY FROM HEAT, FLAME & STRONG OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. Other Precautions: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. DO NOT WELD, HEAT OR DRILL CONTAINER. RESIDUE MAY IGNITE AVOID BREATHING VAPORS OR MISTS, KEEP OUT OF REACH OF CHILDREN. ===== Exposure Controls/Personal Protection ======== REQUIRED. HOWEVER, IF WORKING IN A CONFINED AREA OR MISTING IS OCCURING, USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.

Respiratory Protection: NO SPECIAL RESPIRATORY PROTECTION IS NORMALLY Ventilation: USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves: RUBBER, LATEX TO MINIMIZE SKI

N CONTACT

Eye Protection: SAFETY GLASSES, FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

PART NUBER INDICATOR A IS FOR BRAYCO 485 AND PNI B IS ASSIGNED FOR BRAYCO 483, THE SAME NSN.

HCC:N1 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:>500F,>260C Vapor Density:>1 Spec Gravity:0.86 Evaporation Rate & Ev