

FARWEST PAINT MFG CO -- EXTERIOR TRIM ENAMEL RED 11105 -- 8010-01-333-9814

=====
Product Identification
=====

Product ID:EXTERIOR TRIM ENAMEL RED 11105

MSDS Date:03/23/1992

FSC:8010

NIIN:01-333-9814

MSDS Number: BSHPQ

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:TEXANOL (ESTER ALCOHOL) (TEXANOL IS AN EASTMAN CHEMICAL PRODUCT)

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 4.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC: 62 GRAMS/L

ITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: PROLONGED INHALATION IN A
CONFINED AREA MAY LEAD TO MUCOUS MEMBRANE IRRITATION, DIZZINESS,
HEADACHE. SKIN: IRRITATION. EYE: IRRITATION. INGESTION: AMOUNTS
INGESTED INCIDENTAL TO CONSUMER AND INDUSTRIAL HAND
LING ARE NOT
LIKELY TO CAUSE INJURY, IF LARGER AMOUNTS INGESTED, COULD CAUSE
SERIOUS INJURY.
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH
SAFE HANDLING INSTRUCTIONS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS
DEVELOP, SEEK MEDICAL ATTENTION AT ONCE. SKIN: WASH OFF QUICKLY
WITH PLENTY OF WATER, THEN SOAP & WATER. REMOVE & WASH CONTAMINATED
CLOTHING BE FOR
RE REUSE. EYE: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF
WATER FOR AT LEAST 15 MINUTES, ESPECIALLY UNDER LIDS. OBTAIN
MEDICAL TREATMENT.

===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL, WATER, OR WATER FOG
Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINERS MAY
BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND
ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED
WITH ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY WITH ADEQUATE VENTILATION.
AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND
EYES. AVOID TEMPERATURES BELOW 40F.
Other Precautions:KEEP FROM FREEZING. STORE

CONTAINERS WITH LIDS

LIGHTLY CLOSED AND APPROPRIATELY LABELED. THIS PRODUCT CONTAINS NO MERCURY IN REPORTABLE QUANTITIES AS DEFINED BY OSHA AND EPA. KEEP OUT OF REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW LIMITS BY VENTILATION, WEAR PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS LISTED IN INGREDIENTS.

Ventilation: LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves: IMPERVIOUS GLOVES RECOMMENDED BY GLOVE MANUFACTURER

Eye Protection: SAFETY GLASSES WITH UNPERFORATED SIDELIDS, GOGGLES

Other Protective Equipment: EYE WASH, SAFETY SHOWERS

Work Hygienic Practices: KEEP WORK AREA CLEAN & FREE FROM SPILLS & LEAKS. WASH HANDS WITH SOAP & WATER BEFORE HANDLING FOOD, DRINK, OR SMOKING.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 212F, 100C

Vapor Pres: 23.8 @ 25C

Vapor Density: > AIR

pH: 7-8

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: INFINITE

Appearance and Odor: THIXOTROPIC LIQUID WITH SLIGHT ODOR; COLOR OF TINT

Percent Volatiles by Volume: 7.5

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
OXIDIZERS AND/OR HYDROFLUORIC ACID.

Stability Condition to Avoid
: ELEVATED TEMPERATURES, CONTACT WITH
OXIDIZING AGENTS.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE

Conditions to Avoid Polymerization: ELEVATED TEMPERATURES, CONTACT WITH
OXIDIZING AGENTS.

=====
===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information

ation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.