KERR-MCGEE REFINING CORPORATION -- KERMAC 142 FLASH NAPHTHS -- 6850-00-285-8011

Product ID:KERMAC 142 FLASH NAPHTHS MSDS Date:10/18/1993 FSC:6850 NIIN:00-285-8011 MSDS Number: BSHSN === Responsible Party === Company Name: KERR-MCGEE REFINING CORPORATION Box:2217 **City:HOUSTON** State:TX ZIP:77253 Country:US Info Phone Num:713-638-4700/800-424-9300 **Emergency Phone Nu** m:713-638-4700/800-424-9300 Preparer's Name: KEITH BUNSELMEYER CAGE:DO402 === Contractor Identification === Company Name: BARTLETT CHEMICALS Address:4955 RIVER ROAD Box:10710 City: JEFFERSON State:LA ZIP:70121 Country:US Phone:504-734-1971 CAGE:1V771 Company Name: KERR-MCGEE CHEMICAL CORP Address:123 ROBERT S KERR AVE Box:25861 City:OKLAHOMA CITY State:OK ZIP:73125 Country:US Phone:405-270-1313 CAGE:07083 Company Name: KERR-MCGEE REFININF CORP & SUBSIDIARIES Address:POB 2217 City:HOUSTON State:TX ZIP

:77253 Phone:713-638-4700/CHEMTREC 800-424-9300 CAGE:DO402 Company Name: KERR-MCGEE REFINING CORP Address:2211 NORFOLK SUITE 1100 Box:3367 City:HOUSTON State:TX ZIP:77253 Country:US Phone:713-638-4700/800-424-9300(CHEMTREC) CAGE:6G213 Company Name: THUNDERBIRD SALES CO Address:721 JET DR Box:30078 City:MIDWEST CITY State:OK ZIP:73140 Country:US CAGE:7A142

Ingred Name:NAPHTHA, MEDIUM ALIPHATIC CAS:64742-88-7 Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN-IRRITATION, DERMATITIS. EUE-IRRITATION. SWALLOWING-ASPIRATION HAZARD. Explanation of Carcinogenicity:NOT LISTED. Effects of Overexposure:INHALE-HEADACHE, NASAL & RESPIRATORY IRRITATION, NAUSEA, DROWSINESS, BREATHLESSNESS, FATIGUE, CENTRAL

NERVOUS SYSTEM DEPRESSION, CONVULSION & LOSS OF CONSCIOUSNESS. SWALLOWED-HEADACHE, NAUSEA, DROWSIN ESS, FATIGUE, PNEUMONIA, PULMONARY EDEMA, CENTRAL NERVOUS SYSTEM DEPRESSION, CONVULSIONS & LOSS OF CONSCIOUSNESS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:INHALATION-MOVE EXPOSED PERSON TO FRESH AIR. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. GET MEDICAL AT

TENTION.

SKIN-IMMEDIATELY REMOVE CLOTHING & WASH SKIN WITH SOAP & WATER. GET MEDICA L ATTENTION PROMPTLY. EYES-IMMEDIATELY FLUSH WITH WATER FOR ATLEAST 15 MIN. GET MEDICAL ATTENTION PROMPTLY. SWALLOW-CALL A PHYSICIAN IMMEDIATELY. ONLY INDUCE VOMITING IF INSTRUCTED BY A PHYSICIAN.

Flash Point Method:TCC Flash Point:142F,61C Autoignition Temp: Autoignition Temp Text: 450F Lower Limits:0.7 **Upper Limits:5** Exting uishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM. WATER STREAM MAY SPREAD FIRE, USE WATER ONLY TO COOL CONTAINERS EXPOSED TO FIRE. Fire Fighting Procedures: IF LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS. Unusual Fire/Explosion Hazard: CAN FORM COMBUSTIBLE MIXTURES WITH AIR WHEN HEATED. Spill Release Procedures: NOTIFY EMERGENCY RESPONSE PERSONNEL. EVACUATE AREA AND REMOVE IGNITION SOU RCES. BUILD DIKE TO CONTAIN FLOW. REMOVE FREE LIQUID, DO NOT FLUSH TO SEWER OR OPEN WATER. PICK UP WITH INERT ABSORBENT AND PL ACE IN CLOSED CONTAINER FOR DISPOSAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: DO NOT STORE WITH STRONG OXIDIZERS. STORE AS OSHA CLASS IIIA COMBUSTIBLE LIQUID. Other Precautions: CAUTION! COMBUSTIBLE LIQUID AND VAPOR. ======= Exposure Contro Is/Personal Protection ========= Respiratory Protection: UP TO 1000 PPM, HALF MASK ORGANIC VAPOR RESPIRATOR. UP TO 5000 PPM, FULL-FACE ORGANIC VAPOR RESPIRATOR OR FULL-FACE SUPPLIED AIR RESPIRATOR. GREATER THAN 5000 PPM, FIRE FIGHTING, SELF CONTAINED BREATH ING APPARATUS WITH POSITIVE PRESSURE. Ventilation: MAINTAIN LOCAL OR DILUTION VENTILATION TO KEEP AIR CONCENTRATIONS BELOW 100 PPM. Protective Gloves:NITRILE, NEOPRENE. Eye Protection: SAFETY GLASSES, CHEMICAL GOGGLES,

SHIELD Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDING. Supplemental Safety and Health AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

HCC:V4 Boiling Pt:B.P. Text:350-415F Vapor Pres:0.1 LBS Vapor Density:6 Spec Gravity:0.78 Viscosity:1.3CS @ 100F Evaporation Rate & amp; Reference:8 TIMES SLOWER, ETHER=1 Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR LIQUID , PETROLEUM NAPTHA ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY MANUFACTURER. Stability Condition to Avoid:KEEP AWAY FROM HEAT OR FLAME. Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND VARIOUS HYDROCARBONS.

Waste Disposal Methods:UTILIZE LICENSED WASTE DISPOSAL COM PANY.

CONSIDER RECYCLING OR INCINERATION. UTILIZE PERMITTED HAZARDOUS WASTE DISPOSAL SITE OR INDUSTRIAL WASTE DISPOSAL SITE AS APPROPIATE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this docu ment should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.