

DOW CORNING CORP -- SILICONE BRACKE FLUID, DOW CORNING (R) -- 9150-01-059-2586
===== Product Identification =====

Product ID:SILICONE BRACKE FLUID, DOW CORNING (R)

MSDS Date:08/10/1993

FSC:9150

NIIN:01-059-2586

MSDS Number: BSHVR

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-6000

Emergenc

y Phone Num:517-496-5900/(CHEMTREC)800-424-9300

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

===== Composition/Information on Ingredients =====

Ingred Name:POLYDIMETHYL SILOXANE

CAS:9016-00-6

RTECS #:TQ2690000

Fraction by Wt: 95%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIOCTYL SEBACATE; (DI(2-ETHYLHEXYL)SEBACATE).

CA

S:122-62-3
Fraction by Wt: 3%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TRIBUTYL PHOSPHATE
CAS:126-73-8
RTECS #:TC7700000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:0.2 PPM; 9394

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:EYE/SKIN:IRRITANT.
INHAL:IRRITATES RESPI PASSAGES, INJURY TO NERVOUS SYS. INGEST:SMALL AMTS SHOULD NOT INJURE; LG AMTS MAY INJURE SLIGHTLY.
CHRONIC:INHAL:NERVOUS SYS INJURY. INGEST:LG AMTS MAY INJURE.
Explanation of Carcinogenicity:PER MFG'S MSDS NONE KNOWN.
Effects of Overexposure:EYE:REDNESS, SWELLING, TEARING, DISCOMFORT.
SKIN:REDNESS, SWELLING, ITCHING, DISCOMFORT. INHAL:COUGHING, SHORTNESS OF BREATH, LIGHTNESS IN CHEST, RED EYES. INGEST:INJURY NOT SPECIFIED BY MFG.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:IMMED FLUSH W/WATER FOR 15MINS. SKIN:REMOVE FROM SKIN;WASH W/SOAP & WATER OR WATERLESS CLEANSER. IF IRRIT OR OTHER ILL EFFECTS DEVELOP OR PERSIST SEE DOCTOR. INHAL:REMOVE TO FRESH AIR. IF ILL EFFECTS PERSIST SEE DOCTOR. INGEST:GET MEDICAL ATTENTION. TREAT ACCORDING TO PERSON'S CONDITION & SPECIFICS OF EXPOSURE.

===== Fire Fighting Measures =====

F

Flash Point:>214F,>101C

Lower Limits:N/D

Upper Limits:N/D

Extinguishing Media:CARBON DIOXIDE, WATER, WATER FOG (OR SPRAY), DRY CHEMICAL, FOAM.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS. IF LG AMTS IS INVOLVE EVACUATE AREA.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:MOP UP, WIPE UP, OR SOAK UP W/ABSORBENT &

CONTAIN FOR SALVAGE/DISPOSAL. PROVIDE DIKE OR OTHER CONTAINMENT TO KEEP FROM SPREADING. CLEAN AREA W/APPROPRIATE SOLVENTS, WASHING W/MILD, CAUSTIC DETERGENTS OR SOLUTIONS OR HI PRESSURE STEAM.

===== Handling and Storage =====

Handling and Storage Precautions:PER MFG'S MSDS NO SPECIAL PRECAUTIONS. USE REASONABLE CARE. KEEP CONTAINERS CLOSED. USE REASONABLE CARE. AVOID EYE/SKIN CONTACT. AVOID BREATHING VAPOR

Other Precautions:THESE PRECAUTI

ONS ARE FOR ROOM TEMPERATURE HANDLING.

USE AT ELEVATED TEMPERATURE, OR AEROSOL/SPRAY APPLICATIONS, MAY REQUIRE ADDED PRECAUTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRATORY PROTECTION UNLESS ADEQUATE LOCAL EXHAUST VENTILATION IS PROVIDED OR AIR SAMPLING DATA SHOW EXPOSURES ARE W/IN RECOMMENDED EXPOSURE GUIDELINES. (INDUSTRIAL HYGIENE CAN ASSIST.) ORGANIC VAPOR TYPE NOISHA-APPROVED RESPIRATOR.

Ventilation:LOCAL

EXHAUST AND GENERAL VENTILATION ARE RECOMMENDED.

Protective Gloves:CHEMICAL GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:LAB COATS/APRONS, SAFETY SHOES.

Work Hygienic Practices:WASH HANDS AT MEALTIME & END OF SHIFT. LAUNDRY CONTAMINATED CLOTHING & SHOES PRIOR TO USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:N/D

Vapor Pres:N/D

Vapor Density:N/D

Spec Gravity:0.95

pH:N//A

Viscosity:20.

00CST

Evaporation Rate & Reference:NONE SPECIFIED BY MANUFA.

Solubility in Water:NONE

Appearance and Odor:PURPLE LIQUID WITH A SLIGHT ODOR.

Percent Volatiles by Volume:N/D

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIAL CAN CAUSE A REACTION.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:NITROGEN OXIDES,CARBON OXIDES & TRACES
OF INCOMPLETELY BURNED CARBON COMPOUNDS.METAL OXIDES,SILICO

N

DIOXIDE,FORMALDEHYDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH
FEDERAL/STATE/LOCAL REGULATIONS. (CALL DOW CORNING ENVIRONMENTAL
CONTROL 517-496-6315/5813 IF MORE INFORMATION IS DESIRED.)

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expres

sly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.