

FARWEST PAINT MFG CO -- EXTERIOR TRIM ENAMEL GREEN, 14672 -- 8010-01-333-9445

=====  
Product Identification  
=====

Product ID:EXTERIOR TRIM ENAMEL GREEN, 14672

MSDS Date:03/23/1992

FSC:8010

NIIN:01-333-9445

MSDS Number: BSHXK

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergen

cy Phone Num:206-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TEXANOL (ESTER ALCOHOL)

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 4.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC: 62 G/L

RTECS #:9999999VO

Other REC

Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: PROLONGED INHALATION IN  
CONFINED AREAS, MAY LEAD TO MUCUS MEMBRAN IRRITATION, DIZZINESS,  
HEADACHE. SKIN CONTACT: IRRITATION OF THE SKIN. EYE CONTACT:  
IRRITATION OF THE EYES. INGESTION: AMOUNTS INGESTED INCIDENTAL TO  
CONSUMER & INDUSTRIAL HANDLING ARE NOT LIKELY TO CAUSE INJURY,  
HOWEVER, INGESTION OF LARGER AMOUNTS COULD CAUSE SERIOUS INJURY.  
Effects of Overexposure:AMOUNTS COULD CAUSE SERIOUS INJURY.  
Medical Condition Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH  
SAFE HANDLING INSTRUCTIONS.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS  
DEVELOP, SEEK MEDICAL ATTENTION AT ONCE. SKIN CONTACT: WASH OFF  
QUICKLY WITH PLENTY OF WATER, THEN SOAP & WATER.  
REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE. EYE CONTACT: FLUSH IMMEDIATELY  
WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS, FOR AT LEAST 15  
MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT. INGESTION: GET MEDICAL  
ATTENTION.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL, WATER, WATER FOG  
Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED  
CONTAINERS  
Unusual Fire/Explosion Hazard:WILL NOT BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH &  
ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED  
WITH ABSORBENT MATERIALS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP  
FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED

ED AND

APPROPRIATELY LABELED.

Other Precautions:USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR OR SPRAY MIST. AVOID CONTACT WIT SKIN AND EYES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS.

Ventilation:LOCAL EXHAUST PREFERAB  
LE. GENERAL EXHAUST ACCEPTABLE IF  
EXPOSURE LEVEL BELOW APPLICABLE LIMITS.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:SAFETY GLASSES W/UNPERFORATD SIDESHIELDS

Other Protective Equipment:EYE WASH - SAFETY SHOWERS - GOGGLES - SAFETY GLASSES - IMPERVIOUS GLOVES.

Work Hygienic Practices:KEEP WORK AREA CLEAN & FREE FROM SPILLS & LEAKS. ALWAYS WASH HANDS BEFORE EATING, SMOKING, DRINKING.

Supplemental Safety and Health

REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

=====

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:23.8 @ 25C

Vapor Density:> AIR

pH:7-8

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR; COLOR OF TINT

Percent Volatiles by Volume:7.5

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS AND/OR HYDROFLUORIC ACID

Stability Condition to Avoid:ELEV

ATED TEMPERATURES, CONTACT WITH  
OXIDIZING AGENTS.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE  
Conditions to Avoid Polymerization:ELEVATED TEMPERATURES, CONTACT WITH  
OXIDIZING AGENTS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE & FEDERAL  
REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):

This information is

formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.