

ARMITE LABORATORIES -- LED-PLATE NO. 250/MIL-A-907 -- 8030-00-251-3980

=====
Product Identification
=====

Product ID:LED-PLATE NO. 250/MIL-A-907

MSDS Date:01/15/1993

FSC:8030

NIIN:00-251-3980

MSDS Number: BSRXH

=== Responsible Party ===

Company Name:ARMITE LABORATORIES

Address:1845 RANDOLPH ST

City:LOS ANGELES

State:CA

ZIP:90001

Country:US

Info Phone Num:213-587-7744

Emergency Phone Num:213-587-7

744

Preparer's Name:M L WILCOX

CAGE:84180

=== Contractor Identification ===

Company Name:ARMITE LABORATORIES

Address:1845 RANDOLPH ST

Box:City:LOS ANGELES

State:CA

ZIP:90001-1435

Country:US

Phone:213-587-7744

CAGE:84180

=====
Composition/Information on Ingredients
=====

Ingred Name:METALLIC LEAD POWDER (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 70%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.50 MG/M3

ACGIH TLV:0.15 MG/M3

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingre

d Name:VEHICLE: PARAFIN BASE/PETROLEUM OIL SAE
Other REC Limits:NONE SPECIFIED

Ingred Name:OTHER: PETROLEUM GREASE
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LEAD: CHRONIC OVEREXPOSURE TO HIGH
LEVELS OF AIRBORNE OR INGESTED LEAD MAY RESULT IN ANEMIA, INSOMNIA,
WEAKNESS, CONSTIPATION, NAUSEA, AND ABDOMINAL PAIN. PROLONGED
OVEREXPOSURE MAY R
ESULT IN KIDNEY A ND GASTROINTESTINAL DISORDERS.
NOT LIKELY WITH THIS MATERIAL.

=====
First Aid Measures
=====

First Aid:EYES: AS GREASE PRODUCT, WASH WELL. SKIN: REMOVE BY WIPING,
WASH WELL WITH SOAP AND WATER. INHALED: N/A. SWALLOWED: DO NOT
INDUCE VOMITING. CALL PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:404F,207C
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighti
ng Procedures:NONE AS A GREASE PRODUCT
Unusual Fire/Explosion Hazard:IN LARGE QUANTITY STORAGE, WITH MAJOR
FIRE - FUMES MAY BE PRESENT

=====
Accidental Release Measures
=====

Spill Release Procedures:WIPE AS GREASE. TAKE UP WITH CLAY, PUMICE,
ETC.

=====
Handling and Storage
=====

Handling and Storage Precautions:NORMAL - PREFER UNDER 125 F.

=====
Exposure Controls/Personal Protection
=====

Work Hygiene

c Practices:DO NOT EAT, DRINK OR SMOKE WHEN WORKING WITH THIS PRODUCT. WASH HANDS THOROUGHLY BEFORE EATING, SMOKING OR DRINKING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:T6

Boiling Pt:B.P. Text:300F,149C

Solubility in Water:INSOLUBLE

Appearance and Odor:DARK GRAY, NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:STRONG OXIDI

ZERS CAN CAUSE LEAD TO REACT

AND LIBERATE HYDROGEN GAS.

Hazardous Decomposition Products:AT TEMPERATURES ABOVE THE MELTING POINT, LEAD FUMES MAY BE EVOLVED.

===== Disposal Considerations =====

Waste Disposal Methods:ANY LARGE QUANTITY - RETURN FOR RE-PROCESSING TO DISTRIBUTOR OR SMELTER, OTHERWISE CONSULT LOCAL DISPSOAL PEOPLE. ALL DISPOSAL MUST COMPLY WITH STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.