

TRA-CON INC -- TRA-BOND 5126 RESIN -- 8040-00-776-9601

=====
Product Identification
=====

Product ID:TRA-BOND 5126 RESIN

MSDS Date:01/29/1993

FSC:8040

NIIN:00-776-9601

Kit Part:Y

MSDS Number: BSRZD

=== Responsible Party ===

Company Name:TRA-CON INC

Address:55 NORTH ST

City:MEDFORD

State:MA

ZIP:02155

Country:US

Info Phone Num:617-569-9700

Emergency Phone Num:617-569-9700

CAGE:22835

=== Contractor

Identification ===

Company Name:TRA-CON INC

Address:55 NORTH ST

Box:3933

City:MEDFORD

State:MA

ZIP:02155-4225

Country:US

Phone:617-391-5550

CAGE:22835

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN MIXTURE BASED ON 4,4' - ISOPROPYLIDENEDIPHENOL
EPICHLOROHYDRIN RESIN &/OR SIMILAR ISOMERS = CAS #25068-38-6

CAS:25068-38-6

RTECS #:KC2100000

Fraction by Wt: 70-90%

Other REC Limits:NONE SPECIFIED

Ingred Name:ALIPHATIC POLYOL EPICHLOROHYDRIN REACTION

PRODUCT AND/OR
SIMILAR ISOMERS SIMILAR TO CAS #17557-23-2
CAS:17557-23-2
RTECS #:TX3760000
Fraction by Wt: 10-30%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:INGESTION LD50 (RATS) > 3 GRAM/KG
Health Hazards Acute and Chronic:REPEATED CONTACT OR BREATHING OF
VAPORS MAY CAUSE IRRITATION; MATERIAL IS ALSO A STRONG SENSITIZER.
EYE AND SKIN CONTACT MAY CAUSE TRANSIENT IRRITATION.

===== First
Aid Measures =====

First Aid:EYES: FLUSH WITH WATER, GET MEDICAL ATTENTION. SKIN: WASH
WITH SOAP AND WATER; REMOVE CONTAMINATED CLOTHING. INHALATION:
REMOVE TO FRESH AIR. INGESTION: NO KNOWN ANTIDOTE, BUT GIVE MILK OR
WATER; DO NOT INDUCE VOMITING IF SWALLOWED, GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:>260F,>127C
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICALS
Fire Fighting Procedures:AVOID BREATHING SMOKE.
Unusual Fire/Explosion Hazard:TOXIC GASES MAY BE LIBERATED. HANDLE AS
COMBUSTIBLE. STORE IN A COOL PLACE.

===== Accidental Release Measures =====

Spill Release Procedures:PREVENT SKIN AND EYE CONTACT. SOAK UP IN
ABSORBENT MATERIAL, OR SCRAPE UP AND TRANSFER TO DISPOSAL
CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING
SOLVENT FLAMMABILITY CAUTIONS OR USE DE TERGENTS.

=====
Handling and Storage =====

Handling and Storage Precautions:FOR INDUSTRIAL USE ONLY. WARNING: MAY
CAUSE SENSITIZATION, IRRIT, OTHER ALLERGIC RESPONSES. AVOID EYE
&/OR SKIN CONTACT AND PROLONGED VAPOR INHALATION
Other Precautions:STORE IN A COOL PLACE IN CLOSED CONTAINERS. HANDLE
PER HAZARD POTENTIAL OR HARDENER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR SUPPLIED, OR ORGANIC CANISTER, MASK IN
CONFINED AREAS.

Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL):
RECOMMENDED.

Protective Gloves:RUBBER OR PLASTIC DISPOSABLE

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:AS REQUIRED TO PREVENT ALL BODY CONTACT; EYE
BATH AND/OR SAFETY SHOWER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>350F,>177C

Vapor Pres:1

Spec Gravity:1.18

Evaporation Rate & Reference:LOW

Solubility in Water:LOW

Ap

pearance and Odor:CLEAR, SLIGHT STRAW-COLORED LIQUID, MILD ODOR.

Percent Volatiles by Volume: