View NSN Online: https://aerobasegroup.com/nsn/8010-01-326-9704

Product ID:P/N 2190910 DEVRAN 219 CLEAR CONVERTER MSDS Date:05/06/1993 FSC:8010 NIIN:01-326-9704 Kit Part:Y MSDS Number: BSSFB === Responsible Party === Company Name: DEVOE COATINGS COMPANY Address:4000 DUPONT CIRCLE City:LOUISVILLE State:KY ZIP:40207 Country:US Info Phone Num:50 2-897-9861 Emergency Phone Num:800-424-9300 (CHEMTREC) CAGE:1HK86 === Contractor Identification === Company Name: DEVOE COATINGS CO Address:4000 DUPONT CIRCLE Box:7600 City:LOUISVILLE State:KY ZIP:40207-4802 Country:US Phone:502-897-9861 CAGE:1HK86

Ingred Name:METHYL N-AMYL KETONE (VAPOR PRESSURE 2.14 MM HG) CAS:110-43-0 RTECS #:MJ5075000 Fraction by Wt: 15% Other REC Limits:NONE SPECIFIED OSHA PEL:100 PPM ACGIH TLV:50 PPM

In

gred Name:N-BUTYL ALCOHOL (VAPOR PRESSURE 4.2 MM HG) (SARA III) (CERCLA 103A) CAS:71-36-3 RTECS #:EO1400000 Fraction by Wt: 10% Other REC Limits:NONE SPECIFIED **OSHA PEL:50 PPM CEILING** ACGIH TLV:50 PPM CEILING EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: POLYAMIDE RESIN (VAPOR PRESSURE 120F/NEAR FIRE/FLAME.STORE LRG QTY IN **BLDG(COMPLY** W/OSHA 1910.106).KEEP CNTNR CLSD.DON'T TRANSFR TO BOTTLE/UNLABELLED CNTNR.IF P ART OF KIT. OBEY HZD CAUTION OF BOTH PRTS ====== Exposu Respiratory Protection: DON'T BREATHE VAPOR, SPRAY, SAND DUST. SPRAY IN OUTDOOR/OPEN AREAS,& DURING/SAND DUST, NIOSH/MSHA MECHAN FILTER(RMV SOLID PARTICLES).RESTRICTED VENT,NIOSH/MSHA CHEM/MECHANICAL FILTER(RMV PARTICULATES & VA POR).CONFINED,AIR SUPPLY RSPRTR/HOODS. Ventilation: GENERAL DILUTION/LOCAL EXHAUST TO KEEP CONTAM CONCENTRATIONS BELOW TLV/PEL. PREVENT BLDUP IN LOWER LEVELS OF WORK AREA. Protective Gloves:SOLVENT IMPERMEABLE GLOVES Eye Protection: SOLVENT RESIST SFTY EYEWEAR W/SIDE SHLDS Other Protective Equipment: DO NOT GET ON SKIN. SOLVENT IMPERMEABLE CLOTHING & BOOTS TO PREVENT SKIN CONTACT ARE RECOMMENDED. Work Hygienic Practices: REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING OR SMOKING. Supplemental Safety and Health

Boiling Pt:B.P. Text:244 TO 340F Vapor Density:> AIR Evaporation Rate & amp; Reference:SLOWER T Stability Indicator/Materials to Avoid:YES AVOID CONTACT WITH STRONG OXIDIZING AGENTS. Hazardous Decomposition Products:MAY CAUSE TOXIC FUME WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND

FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional adv ice to verify and assume responsibility for the suitability of this information to their particular situation.