View NSN Online: https://aerobasegroup.com/nsn/5330-00-097-9773

RM ENGINEERED PRODUCTS INC -- 325 PACKING -- 5330-00-097-9773

Product ID:325 PACKING MSDS Date:08/01/1993 FSC:5330 NIIN:00-097-9773 **MSDS Number: BSSHD** === Responsible Party === Company Name: RM ENGINEERED PRODUCTS INC Address:4854 O HEAR AVE Box:5205 **City:NORTH CHARLESTON** State:SC ZIP:29406-4926 Country:US Info Phone Num:803-744-6261/FAX -0461 **Emergency Phone Nu** m:803-744-6261 CAGE:DO604 === Contractor Identification === Company Name: R M ENGINEERED PRODUCTS, INC. Address:4854 O'HEAR AVENUE Box:City:NORTH CHARLESTON State:SC ZIP:29405 Country:US Phone:843-744-6261 CAGE:10009 Company Name: RM ENGINEERED PRODUCTS Address: P.O. BOX 5205 Box:5205 City:NORTH CHARLESTON State:SC ZIP:29406 Phone:803-744-6261 CAGE:DO604 Company Name: RM ENGINEERED PRODUCTS INC Address:4854 O HEAR AVE Box:City:NORTH CHARLESTON State:SC ZIP:29406 Country:US Phone:803-744-6261 CAGE:0D

CP7

Company Name:UNITED STANDARD INDUSTRIES INC Address:2062 LEHIGH Box:City:GLENVIEW State:IL ZIP:60025-1619 Country:US Phone:312-724-0350 CAGE:28210

Ingred Name:ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 Fraction by Wt: 12-63% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9293

LD50 LC50 Mixture:PEL FOR ASBE STOS FIBERS 0.2 FIBER/CC Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:ACUTE & CHRONIC-A HEALTH HAZARD EXISTS IF FIBERS ARE RELEASED. BREATHING OF ASBESTOS FIBERS IN SIGNIFICANT AMOUNTS MAY PRODUCE IRREVERSIBLE LUNG DISEASE AND CANCER. FREE

FIBERS CAN CAUSE EYE & SKIN IR RITATION. INGESTION FREE ASBESTOS FIBERS MAY BE A FACTOR IN CANCERS OF THE GI TRACT & LARYNX & SMOKING RELA

TED.

Explanation of Carcinogenicity:CONTAINS A [1332-21-4] WHICH IS
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.
Effects of Overexposure:BREATHING OF ASBESTOS FIBERS IN SIGNIFICANT
AMOUNTS MAY PRODUCE IRREVERSIBLE LUNG DISEASE AND CANCER. FREE
FIBERS CAN CAUSE EYE AND SKIN IRRITATION. INGESTION MAY CAUSE GI

TRACT CANCER.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS OR EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MO

RE SUSCEPTIBLE TO THE EFFECTS OF THE SUBSTANCE.

First Aid:GET MEDICAL ATTENTION IF NEEDED. SKIN:WASH WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED:REMOVE TO FRESH AIR. PROVIDE OXYGEN/CPR IF NEEDED. ORAL:CALL A PHYSICIA N.

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMIC AL

FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures: WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:PRODUCES SMOKE, SOME FUMES AND POSSIBLY SOME FREE ASBESTOS FIBERS WHEN BURNED.

Spill Release Procedures: VACUUM FIBERS AND DUSTS, CAREFULLY, AVOIDING DUSTING. IF S

WEEPING IS USED, CONTROL DUST BY WETTING AND USE APPROPRIATE DUST MASK.PLACE IN AN APPROPRAITE CONTAINER FOR DISPOSAL. Neutralizing Agent:NONE

Handling and Storage Precautions:STORAGE- STORE IN CLEAN DRY PLACE AWAY FROM STRONG OXIDIZING AGENTS.

Other Precautions:DO NOT BREATHE DUST OR FIBERS. WASH THOROUGHLY AFTER HANDLING.

======= Exposure Controls/Personal Protection ==========

Respiratory Protec

tion:NONE REQUIRED WHERE ADEQUATE VENTILATION CONDITIONS EXIST. IF EXCESSIVE DUSTS OR FIBERS PRESENT, A NIOSH-APPROVED DUST RESPIRATOR IS RECOMMENDED. IF CONCENTRATION EXCEEDS CAPACITY OF RESPIRATOR, USE S ELF-CONTAINED BREATHING APPARATUS. Ventilation: MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves: RUBBER, LEATHER, COTTON Eye Protection: SAFETY GOGGLES WITH SIDE SHIELDS Other Protective Equipment: CLOTHING TO PROTECT FRO M DUST AND FUMES, AS NEEDED. Work Hygienic Practices: KEEP WORK AREA CLEAN OF ASBESTOS DUST. AVOID CREATING DUST.USE GOOD WORK HYGIENE. Supplemental Safety and Health NONE HCC:T6 Solubility in Water: INSOLUBLE Appearance and Odor: BRAIDED PACKING MATERIEL; COLOR NOT REPORTED; NO CHAR. ODOR: SLIPPERY TOUCH Stability Indicator/Materials to Avoid:YES NONE **KNOWN** Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products: MAY PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE AND SOME FREE ASBESTOS FIBERS WHEN BURNED. Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense . The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.