

WALNUT HILL ENTERPRISES INC -- VV-W-95C -- 9160-00-701-3681

=====  
Product Identification  
=====

Product ID:VV-W-95C

MSDS Date:03/01/1991

FSC:9160

NIIN:00-701-3681

MSDS Number: BSVQD

=== Responsible Party ===

Company Name:WALNUT HILL ENTERPRISES INC

Address:GREEN LANE & WILSON AVE

Box:599

City:BRISTOL

State:PA

ZIP:19007

Country:US

Info Phone Num:215-785-6511

Emergency Phone Num:215-785-6511

CAGE:0L

M34

=== Contractor Identification ===

Company Name:WALNUT HILL ENTERPRISES INC

Address:GREEN LANE AND WILSON AVE

Box:599

City:BRISTOL

State:PA

ZIP:19007

Country:US

Phone:215-785-6511

CAGE:0LM34

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PARAFFIN WAX; (CLAY TREATED PARAFFIN WAX)

CAS:64742-43-4

Fraction by Wt: 100%

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalat

ion:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MOLTEN WAX MAY CAUSE BURNS. MIST OR FUMES MAY CAUSE RESPIRATORY IRRITATION OR DISCOMFORT. HOT MATERIAL MAY CAUSE INJURY TO EYES AND SKIN. INHALATION OF FUMES FROM HOT MATERIAL CAN PRODUCE NAUSEA AND IRRITATE UPPER RESPIRATORY TRACT. NO HARM FROM INGESTION OF SMALL QUANTITIES.

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:EYE: COOL MATL SHOULD NOT CAUSE EYE IRRIT.IF HOT MATL SHOULD ENTER EYES, FLUSH IMMED W/FRESH WATER FOR AT LST 15 MINS WHILE HOLDING EYELIDS OPEN. SEE MD. SKIN: QUICKLY COOL IN WATER. SEE MD FOR EXTENS IVE BURNS. DO NOT TRY TO PEEL SOLIDIFIED MATL. VEGETABLE OIL/MINERAL OIL IS RECOM TO REMOVE MATL FROM SKIN. INHAL: REMOVE PERSON T  
O FRESH AIR. SEE MD IF DISCOMFORT OR IRRIT CONTINUES.  
INGEST: (SUPDAT)

=====  
===== Fire Fighting Measures =====

Flash Point:500F,260C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . DO NOT USE WATER TO EXTINGUISH FLAMES. TURN OFF HEAT SOURCE AND SMOTHER FLAMES.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:IF LIQUID, KEEP MATERIAL FROM DRAINS AND SEWERS, AND PERMIT IT TO SOLIDIFY.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT HEAT ABOVE FLASH POINT. DO NOT HEAT WITH OPEN FLAMES OR OPEN ELECTRICAL COILS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. IF VAPOR OR MIST IS GENERATED, USE NIOSH/MSHA APPROVED RESPIRATOR.

Ventilation:PROVIDE AS NEEDED. USE LOCAL EXHAUST IF REQUIRED.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPROVED CHEMICAL WORKERS (SUPDAT)

Other Protective Equipment:PROTECTIVE CLOTHING.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FIRST AID PROCEDURES: NOT TOXIC. SMALL QUANTITIES WILL PASS THROUGH THE SYSTEM. EYE PROT:GO

GGLES AND FULL LENGTH FACESHIELD .

===== Physical/Chemical Properties =====

Melt/Freeze Pt:M.P/F.P Text:>135F,>57C

Spec Gravity: