View NSN Online: https://aerobasegroup.com/nsn/9150-01-353-4799

VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC. -- ATF DEXRON -- 9150-01-353-4799

Product ID:ATF DEXRON MSDS Date:01/01/1988

FSC:9150

NIIN:01-353-4799

MSDS Number: BSWBZ === Responsible Party ===

Company Name: VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC.

Address: 200 E MAIN ST

Box:14000

City:LEXINGTON

State:KY ZIP:40512 Country:US

Info Phone Num:606-264-7000/71

78

Emergency Phone Num:800-ASHLAND/800-274-5263

Preparer's Name: NONE

CAGE:72527

=== Contractor Identification ===

Company Name: ASHLAND INDUSTRIAL PRODUCTS INC

Address:3499 BLAZER PKY

Box:14000

City:LEXINGTON

State:KY ZIP:40512 Country:US

Phone:859-357-7777

CAGE:9T904

Company Name: VALVOLINE OIL CO

Address:3499 BLAZER PKY

Box:14000

City:LEXINGTON

State:KY ZIP:40512 Country:US

Phone:606-357-7206 / 800-274-5263

CAGE:72527

======= Composition/Information on Ingredients ========

Ingred

Name: NON-HAZARDOUS INGREDIENTS Fraction by Wt: 100% Other REC Limits: NONE RECOMMENDED Ingred Name: PETROLEUM LUBE OIL, PER MSDS CAS # 64742-65-0 Fraction by Wt: 85-100% Other REC Limits: NONE RECOMMENDED OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST ========== Hazards Identification =========================== LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE AND CHRONIC- TOXICOLOGICAL TESTING INDICATES THAT SIMILAR PRODUCTS ARE NOT HAZARDOUS AS DEFINED BY OSHA (29 CFR 1910.1200). **Explanation of Carcinogenicity: NONE** Effects of Overexposure: MAY CAUSE SLIGHT EYE IRRITATION. First Aid:CALL A DOCTOR IF SYMPTOMS PERSIST. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WIPE EXCESS. WASH SKIN WITH SOAP & WATER. INHALED: REMOVE TO FR ESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. ORAL: IF CONSCIOUS, DRINK 2 GLASSES OF WATER & INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY, KEEP HEAD BELOW HIPS WHILE VOMITING. ============= Fire Fighting Measures ======================== Flash Point:218C

Flash Point:218C Vapor Density:>1 Spec Gravity:0.875

Evaporation Rate & Deference: