

SEYMOUR OF SYCAMORE,INC -- TOOLMAKERS BLUE LAYOUT INK;00-0016-0358 --
6850-01-015-0834

=====
===== Product Identification =====

Product ID:TOOLMAKERS BLUE LAYOUT INK;00-0016-0358

MSDS Date:03/25/1994

FSC:6850

NIIN:01-015-0834

MSDS Number: BSWZK

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE,INC

Address:917 CROSBY AVE

City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Info Phone Num:815-895-91

01

Emergency Phone Num:815-895-9101 800-255-3924(24-HRS)

CAGE:59581

=== Contractor Identification ===

Company Name:GOURMET INQUE LTD

Address:191 STANLEY ST

Box:City:ELK GROVE VILLAGE

State:IL

ZIP:60007-1555

Country:US

Phone:847-296-6192/FAX: 800-542-1042

CAGE:0TNN7

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

=====
===== Composition/Information on Ingredients =====

Ingred Nam

e:BLUE PIGMENT-PHTHALOCYANINE BLUE

CAS:147-14-8

Fraction by Wt: 0.5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 1.62%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9394

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)-DENATURED ACCORDING TO TESCOLO A
FORMULA

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 5.18%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1000 PPM

ACG

IH TLV:1000 PPM; 9394

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 2.41%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 0.6%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/125STEL;9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANO

L)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 0.24%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9394

Ingred Name:DIBUTYL PHTHALATE (SARA III)
CAS:84-74-2
RTECS #:TI0875000
Fraction by Wt: 0.56%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3; 9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)
CAS:117-81-7
RTECS #:TI0350000
Fraction by Wt: .12%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10STEL; 9394
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 1.63%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 1.52%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM/75 STEL; 9394
EPA

Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ACETATE
CAS:108-21-4
RTECS #:AI4930000
Fraction by Wt: 13.87%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:250 PPM
ACGIH TLV:250 PPM/310STEL;9394

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 37.45%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:750PPM/1000STEL;9294
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:
EL6475000
Fraction by Wt: 1.52%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 0.27%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S,200PPM
ACGIH TLV:S,200PPM/250STEL; 94
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 1.36%
Other REC Limits:NONE

RECOMMENDED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM/500STEL;9394

Ingred Name:NAPHTHA, LIGHT AROMATIC
CAS:64742-95-6
Fraction by Wt: 1.08%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM (NAPHTHA)
ACGIH TLV:400 PPM (NAPHTHA)

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 13.6%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9394

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 9.1%
Other REC Limits:NONE RECOMMENDED

=====
==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION,ESP. FROM
DIRECT SPRAY.SKIN:MAY CAUSE IRRITATION,DEFATTING,DRYNESS.INHAL:MAY
CAUSE RESPIRATORY IRRITATION.INGEST:MAY BE HARMFUL IF INGESTED.
Explanation of Carcinogenicity:DIOCTYL PHTHALATE IS KNOWN TO CAUSE
CANCER OR REPRODUCTIVE TOXICITY.
Effects of Overexposu
re:INHAL:HEADACHE,DIZZINESS,NAUSEA,POSSIBLE
UNCONSCIOUSNESS AND ASPHYXIATION.SKIN:IRRITATION,DERMATITIS.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING
RESPIRATORY AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
==== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND
WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH
AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGES

T:DO NOT

INDUCE VOMITING. GET PROMPT QUALIFIED MEDICAL ATTENTION.**IN ALL CASES,CALL PHYSICIAN IF SYMPTOMS PERSIST**

===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:-10F,-23C

Extinguishing Media:CARBON DIOXIDE,CHEMICAL,FOAM.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH FOG WATER SPRAY.WATER IS INEFFECTIVE IN FIGHTING FIRE.

Unusual Fire/Exp

losion Hazard:HEAT MAY BURST AEROSOL CONTAINERS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION.USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.WASH SPILL AREA TO REMOVE SLIPPINESS.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.KEEP AWAY FROM EXCESSIVE HEAT AND SUNLIGHT.

Other Precautions:USE THIS PRODUCT ONLY FOR ITS INTENDED USE.READ AND FOLLOW ALL LABEL INSTRUCTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A SELF-CONTAINED BREATHING APPARATUS.

Ventilation:USE ONLY WITH ADEQUATE VENTILATION.LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL

Protective Gloves:AS NEEDED.

Eye Protection:CHEMICAL GOGGLES FOR SPRAY

Other Protective Equipment:NONE

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS PRODUCT.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:1 ETHER=1

Solubility in Water:NOT REPORTED

Appearance and Odor:AEROSOL,12OZ.PHYSICAL PROPERTIES NOT REPORTED.

Percent Volatiles by Volume:91.5

===== Stability and Rea

ctivity Data =====

Stability Indicator/Materials to Avoid: YES

AMINES, ALKALINE MATERIALS, STRONG ACIDS.

Stability Condition to Avoid: DO NOT STORE ABOVE 120F. KEEP AWAY FROM SPARKS, PILOT LIGHTS AND OPEN FLAMES.

Hazardous Decomposition Products: OXIDES OF NITROGEN, HYDROGEN CYANIDE, CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DO NOT INCINERATE OR PUNCTURE CONTAINERS. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to thei

r
particular situation.