View NSN Online: https://aerobasegroup.com/nsn/9150-00-117-8791

Product ID:10510 NMMA TC WII OUTBOARD MOTOR OIL MSDS Date:11/01/1993 FSC:9150 NIIN:00-117-8791 MSDS Number: BSYJH === Responsible Party === **Company Name: GARD CORPORATION** Address:2727 ROE LANE **City:KANSAS CITY** State:KS ZIP:66103 Country:US Info Phone Num:913-236-5000 **Emergency Phone Num:** 913-236-5000 CAGE:3K676 === Contractor Identification === Company Name: UNIMARK OIL COMPANY (FORMERLY GARD OIL) Address:2727 ROE LANE **City:KANSAS CITY** State:KS ZIP:66103-1543 Country:US Phone:913-236-5000; FX 913-236-4419 CAGE:3K676

Ingred Name:NAPHTHA, MEDIUM ALIPHATIC CAS:64742-88-7 Minumum % Wt:20. Maxumum % Wt:30. Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPRIETARY ADDITIVES Minumum % Wt:0. Maxumum % Wt:6. Other REC Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION MAY CAUSE
RESPIRATORY TRACT IRRITATION AND CENTRAL NERVOUS SYSTEM DEPRESSION.
CONTACT MAY CAUSE SKIN AND EYE IRRITATION. MAY BE HARMFUL OR FATAL
IF SWALLOWED. CHRONIC: NONE SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:
THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:INHALED: ANESTHESIA, COUGHING, WHEEZING, SNEEZING, DIZZINESS, DROWSINESS, HEADACHE, NAUSEA, VOMITING. EYES: TEARING, STINGING, REDNESS, BLURRED VISION. SKIN: DEFATTING, REDNESS, SWELLING, ITCHING. ING ESTED: ABDOMINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN-WASH WITH SOAP AND WATER. INHALED-REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING DIFFICULT; ARTIFICIAL RESPIRATION IF STOPPED. GET MEDI CAL ATTENTION. INGESTED-CALL DOCTOR IMMEDIATELY! DO NOT INDUCE VOMITING! HAVE PERSDON LIE DOWN & KEEP WARM. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION.

Flash Point Method:TCC

Flash Point:=48.9C, 120.F

Extinguishing Media:USE NFPA CLASS B (CARBON DIOXIDE OR FOAM) EXTINGUISHERS FOR CLASS II FIRES.

- Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS AND FIREFIGHTERS WITH WATER SPRAY.
- Unusual Fire/Explosion Hazard: APPLYING TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

====== Acc

Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. DO NOT ALLOW TO ENTER WATERWAYS. CONTAIN SPILL. ABSORB UP WITH INERT MATERIAL (EG. CLAY,SAND); PLACE IN PROPER CONTAINER FOR DISPOSAL. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM

OXIDIZING MATERIALS. Other Precautions:DO NOT TRANSFER TO UNMARKED CONTAINERS.KEEP FIRE EXTINGUISHERS IN THE AREA.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES; USE NIOSH/MSHA APPROVED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation: USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST.

Protective Gloves: RUBBER OR PLASTIC

Eye Protection:CHEMICAL GOGGL

ES, IF NEEDED.

Other Protective Equipment: RUBBER OR PLASTIC APRON. HAVE EYE WASH AND SAFETY SHOWER AVAILABLE.

Work Hygienic Practices: WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health NONE

HCC:F4 Boiling Pt:>193.3C, 380.F Vapor Pres: