

APT SOLUTIONS INC -- MAGNETIC TAPE HEAD CLEANER XYLENE BLEND (SUPP DATA) --
5835-00-123-5175

=====
===== Product Identification =====

Product ID:MAGNETIC TAPE HEAD CLEANER XYLENE BLEND (SUPP DATA)

MSDS Date:11/19/1991

FSC:5835

NIIN:00-123-5175

MSDS Number: BSYJJ

=== Responsible Party ===

Company Name:APT SOLUTIONS INC

Address:309 S GRANT AVE

City:FT COLLINS

State:CO

ZIP:80521

Country:US

Info Phone Num:

303-221-4825

Emergency Phone Num:303-221-4825

CAGE:0UEB9

=== Contractor Identification ===

Company Name:APT SOLUTIONS INC

Address:309 S GRANT AVE

Box:City:FT COLLINS

State:CO

ZIP:80521

Country:US

Phone:303-221-4825

CAGE:0UEB9

=====
===== Composition/Information on Ingredients =====

Ingred Name:XYLENE. LD50:(ORAL,RAT)4300 MLGR/KG (MFR)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM;150 PPM STEL

ACGIH TLV:100 PPM;150 PPM STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:E

THANE, 1,1,1-TRICHLORO-; (METHYL CHLOROFORM)

CAS:71-55-6

RTECS #:KJ2975000

OSHA PEL:350 PPM;450 PPM STEL

ACGIH TLV:350 PPM;450 PPM STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:BENZENE, ETHYL-; (ETHYL BENZENE). LD50:(ORAL,RAT) 4300 GR/KG

CAS:100-41-4

RTECS #:DA0700000

OSHA PEL:100 PPM;125 PPM STEL

ACGIH TLV:100 PPM;125 PPM STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mi

xture:ING 1

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYES: CONTACT WILL BE PAINFUL AND IRRITATING. SKIN: PROLONGED CONTACT MAY CAUSE IRRITATION. INHAL: RESPIRATORY SYMPTOMS ASSOCIATED WITH PREEXISTING LUNG DISORDERS (E.G., ASTHMA-LIKE CONDITIONS) MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PRODUCES ANESTHETIC OR NARCOTIC EFFECT. CHLOROCARBON (EFTS OF OVEREXP)

Explan

ation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ: MATERIALS HAVE PRODUCED SENSITIZATION OF MYOCARDIUM TO EPINEPHRINE IN LAB ANIMALS AND COULD HAVE SIMILAR EFFECT IN HUMANS. ADRENOMIMETICS (E.G., EPINEPHRINE) MAY BE CONTRAINDICATED EXCEPT FOR LIFE-SUSTAINING USES IN HUMANS ACUTELY OR CHRONICALLY EXPOSED TO CHLOROCARBONS .

Medical Cond Aggravated by Exposure:RESPIRATORY SYMPTOMS ASSOCIATED WITH PREEXISTING LUNG DISORDERS (E.G., ASTHMA-LIKE CONDITIONS) MAY

BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN. SKIN: WASH WITH WATER. INHAL: REMOVE TO FRESH AIR. RE-ESTABLISH BREATHING IF NECESSARY AND CONTACT A PHYSICIAN. INGEST: DO NOT INDUCE VOMITING. CONTACT A PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:90.0F,32

.2C

Lower Limits:2%

Upper Limits:9%

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED PRESS DEMAND SCBA AND FULL PROTECTIVE EQUIPMENT . WATER SPRAY OR FOG MAY BE USED TO REDUCE RATE OF BURNING AND COOL CONTAINERS.

Unusual Fire/Explosion Hazard:VAPOR MAY TRAVEL A CONSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASH BACK. THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE HCL AND PHOSGENE .

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. WEAR PROTECTIVE CLOTHING. FOR MINOR SPILLS SOAK UP WITH SWEEPING COMPOUND OR SAND AND TRANSFER TO A DISPOSAL CONTAINER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT AND SOURCES OF IGNITION.

Other Precautions:DO NOT TAKE INTERNALLY OR INHALE VAPORS. AVOID EYE CONTACT.

NO SMOKING IN AREA OF USE. DO NOT USE IN GENERAL VICINITY OF ARC WELDING, OPEN FLAMES/HOT SURFACES. HEAT &/OR UV RADIATION MAY CAUSE FORMATION OF HCL &/OR PHOSGENE .

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED CANISTER MASK WITH BLACK ORGANIC VAPOR CANISTER.

Ventilation:MUST BE EXPLOSION PROOF. LOCAL EXHAUST: YES. MECHANICAL (GENERAL): IF NECESSARY.

Protective Gloves:NEOPRENE OR RUBBER GLOVES.

Eye Protection:

ANSI APPROVED CHEMICAL WORKERS GOGGLES (FP N)

Other Protective Equipment:FULL COVER CLOTHING.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

MFR TRADE NAME/PART #: 087-007, 542-900-902.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:260F,127C

Vapor Pres:10@20C

Vapor Density:HVR/AIR

Spec Gravity:0.942

Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance a

nd Odor: CLEAR LIQUID WITH CHARACTERISTIC AROMATIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZING AGENTS, WATER, ALUMINUM IN ANY FORM, ZINC POWDERS.

Stability Condition to Avoid: HIGH TEMPERATURES, SOURCES OF IGNITION.

Hazardous Decomposition Products: HYDROGEN CHLORIDE, CARBON MONOXIDE,
CARBON DIOXIDE, TRACE OF PHOSGENE AND CHLORINE.

===== Disposal Considerations =====

Waste Dispo

sal Methods: USE METHODS WHICH MEET ALL FEDERAL, STATE, AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume

responsibility for the suitability of this information to their
particular situation.