

EASTMAN KODAK CO -- 828 8581 KODAK HX TONER, BLACK -900 GRAMS -- 6850-01-387-6591
===== Product Identification =====

Product ID:828 8581 KODAK HX TONER, BLACK -900 GRAMS

MSDS Date:08/22/1992

FSC:6850

NIIN:01-387-6591

MSDS Number: BSZKJ

=== Responsible Party ===

Company Name:EASTMAN KODAK CO

Address:343 STATE ST

City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Info Phone Num:800-242-2424

Emergenc

y Phone Num:716-722-5151/716-724-4501

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:BUTYL ACRYLATE-P-DIVINYLBENZENE-STYRENE *93-4*

CAS:57516-68-4

Fraction by Wt: 90-95%

Ingred Name:COLUMBIA CARBON, CARBON BLACK, LAMPBLACK, BLACK PEARLS

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 5-10%

Other REC Limits:3.5 MG/CUM (NIOSH)

OSHA PEL:3.5 MG/CUM

ACGIH TLV:3.5 MG/CUM

Ingred Name:BENZYLDIMETHYLOCTADECYLAMMONIUM 3-NITRO-BENZENESULFONATE

93-4

CAS:124088-59-1

Fraction by Wt: < 2%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF THE
RESPI

RATORY TRACT & PNEUMOCONIOSIS (W/CHRONIC EXPOSURE). LOW HAZARD FOR ACUTE INHALATION/INGESTION. EYES: IRRITATION.

Explanation of Carcinogenicity:NONE

=====
First Aid Measures
=====

First Aid:INHALATION: MOVE TO FRESH AIR. EYES: WASH IMMEDIATELY W/WATER. SKIN: WASH W/SOAP & WATER. INGESTION: DRINK 1-2 GLASSES OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Extinguishing Media

:WATER SPRAY, CO2, DRY CHEMICAL

Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE DUST-AIR MIXTURES.

=====
Accidental Release Measures
=====

Spill Release Procedures:DON'T USE A VACUUM CLEANER TO CLEAN UP SPILLS OF POWDERED TONERS. THE VERY FINE PARTICIES CAN CAUSE A FIRE/EXPLOSION. SWEEP MATERIAL ONTO PAPAER & PLACE IN A FIBER CARTON.

=====
Handling and Storage
=====

Handling and Storage Precauti

ons:KEEP CONTAINER CLOSED.

Other Precautions:AVOID BREATHING DUST. USE W/ADEQUATE VENTILATION. KEEP FROM CONTACT W/OXIDIZING MATERIALS.

=====
Exposure Controls/Personal Protection
=====

Ventilation:RECOMMENDED

Protective Gloves:IMPERVIOUS

Eye Protection:RECOMMENDED

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Vapor Pres:NEGLIGIBLE

Vapor Density:NEGLIGIBLE

Evap

Evaporation Rate & Reference: NEGLIGIBLE
Solubility in Water: ISOLUBLE
Appearance and Odor: BLACK POWDER W/SLIGHT ODOR.
Percent Volatiles by Volume: NEGL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS
Hazardous Decomposition Products: CO₂, CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE/LANDFILL. CAN BE INCINERATED WHEN IN COMPLIANCE W/ LOCAL REGULATIONS. DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.