

DEFT INC CHEMICAL COATING DIV -- CAT, MIL-C-83286, 16473 P/C 03GY049CAT --
8010-00-181-8254

===== Product Identification =====

Product ID:CAT, MIL-C-83286, 16473 P/C 03GY049CAT

MSDS Date:06/06/1991

FSC:8010

NIIN:00-181-8254

Kit Part:Y

MSDS Number: BTCLB

=== Responsible Party ===

Company Name:DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Info Phone Num:714-474-0400

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:NORM GAUL

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC ISOCYANATE BIURET OF HMDI

CAS:4035-89-6

Fraction by Wt: 30%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:0.005 PPM TWA

Ingred Name:HEXAMETH

YLENE DIISOCYANATE [HDI] FREE MONOMER >0.5% AT TIME
OF MFR, AFTER 3-6 MO, MAY RISE TO MAX 1.6%.

CAS:822-06-0

RTECS #:MO1740000

Fraction by Wt: 0.5-1.6%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:N-BUTYL ACETATE (SARA III) (VAPOR PRESSURE 13 MM HG @ 68F)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM;STEL 200 PPM

ACGIH TLV:150 PPM;STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYL

ENE (SARA III) (VAPOR PRESSURE 21 MM HG @ 100F)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 4.35%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III) (VAPOR PRESSURE 7.1 MM HG @ 68F)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 0.89%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 125 PPM

ACGIH TLV:100 PPM;STEL 125 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL 3-ETHOXYPROPIONATE (VAPOR PRESSURE 0.7 MM HG @ 68F)

CAS:763-69-9

RTECS #:UF3325000

Fraction by Wt: 10%

Other REC Limits:50 PPM;STEL 100 PPM

Ingred Name:METHYL ETHYL KETONE (SARA III) (VAPOR PRESSURE 70 MM HG @
68F)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 45%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM;STEL 300 PPM

ACGIH TLV:200 PPM;STEL 300 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 625 G/L

A REFERENCE METHOD 24
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL: RESP TRACT IRRIT,NERV SYS
DEPRESS (HEADACHE,DIZZY,STAGGER,CONFUSION,UNCONSCIOUS,COMA). SKIN:
ISOCYANATE REACT W/PROTEIN CAUSING IRRIT (SWELL,RED,RASH). ABSORPT:
IRRIT,DRYING,DEFATTING (CRACKING
) . EYE: IRRIT (TEAR,RED,SWELL
W/STING).INGEST: IRRIT,CORROSIVE IN GI TRACT. VOMIT MAY CAUSE
ASPIRATION-CHEM PNEUMONITIS

Effects of Overexposure:ACUTE: VAPOR IRRITATING TO EYES, NOSE, THROAT.
INHALATION MAY CAUSE HEADACHES, DIFFICULT BREATHING &
UNCONSCIOUSNESS. CHRONIC: AS RESULT OF PREVIOUS REPEATED
OVEREXPOSURE OR SINGLE LARGE DOSE , SOME WILL DEVELOP ISOCYANATE
SENSITIZATION WHICH WILL CAUSE THEM TO REACT TO LATER ISOCYANATE
EXPOSURE WELL BELOW TLV.

Medical C

ond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY
DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS. ISOCYANATE
SENSITIZATION.

===== First Aid Measures =====

First Aid:INHAL: MOVE TO FRESH AIR. RESTORE BREATHING. ASTHMATIC TYPE
SYMPTOMS MAY DEVELOP. GET MEDICAL AID. SKIN: REMOVE CONTAMINATED
CLOTHES. WASH AFFECTED AREAS W/SOAP & WATER. WASH CONTAMINATED
CLOTHING BEF ORE REUSE. EYES: FLUSH W/LUKEWARM WATER(LOW PRESSURE)
15

MIN, OCCASIONALLY LIFTING EYELIDS. GET MED AID. INGESTION: DO
NOT INDUCE VOMITING. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON.
GET MED AID.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:23.0F,-5.0C

Lower Limits:1.00

Upper Limits:11.00

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG,
WATER SPRAY

Fire Fighting Procedures:USE FULL PROTECT CLOTH/FIREFIGHT EQUIP W/SCBA.
WATER MAY BE USED TO COOL CLSD C

NTNRS (PREVENT PRESS

BLDUP/AUTOIGNIT/EXPLOS). HDI/IRRIT VAPOR GENERATED BY FIRE.

Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD. KEEP FROM HEAT/IGNIT SOURCE. CLSD CNTNR MAY EXPLODE W/HEAT. APPLIC TO HOT SURFACE REQ SPECIAL PRECAUTION. OVEREXPOSURE TO DECOMP PROD-HLTH HZD.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN BLDGS IN COMPLY W/OSHA 1910.106. AVOID STORING NEAR HIGH TEMPERATURES/IGNITION SOURCES. STORE IN CLOSED CONTAINERS IN WELL VENTILATED AREA.

Other Precautions:KEEP CONTAINERS TIGHT & UPRIGHT (PREVENT LEAK). PREVENT PROLONGED VAPOR BREATHING. PROLONGED OVEREXPOSURE MAY CAUSE ALLERGIC REACTION. AVOID CONTACT WITH SKIN & EYES. DO NOT INGEST. DON'T HANDLE TILL MFR SFTY PRECAUTIONS READ/UNDERSTOOD.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A RESPIRATOR RECOMMENDED FOR ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING OR FRESH AIR SUPPLIED). OBEY OSHA REGS FOR RESPIRATOR USE. PROVIDE VENT TO KEEP EXPOSURE LEVELS BELOW PEL. USE VAPOR PARTICULATE R SPRTR (TC23C) WHEN BELOW 10X TLV/PEL.

Ventilation:EXHAUST VENT TO KEEP AIRBORNE CONCENTRATIONS BELOW TLV'S.

REMOVE ALL IGNITION SOURCES.

Protective Gloves:COTTON, NEOPRENE, RUBBER, POLYETHYLENE

Eye Protection:SPLASH GUARDS,SIDE/FACE SHIELDS,GOGGLES

Other Protective Equipment:THE USE OF LONG SLEEVE AND LONG LEG CLOTHING IS RECOMMENDED. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM. SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

===== Physical/Chemical Propertie

S =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 338F

Vapor Density:>AIR

Spec Gravity:0.91957

Viscosity:*

Evaporation Rate & Reference:3.36 X N-BUTYL ACETATE

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:75.3

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Con

dition to Avoid:CONTACT WITH MOISTURE, MATERIAL WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES.

Hazardous Decomposition Products:BY HIGH HEAT/TEMPERATURE: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN & HDI.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED WITH CARE, DUE TO PRODUCT RESIDUE & FLAMMABLE VAPOR. DON'T INCINERATE CLOSED CONTAINERS. EPA CODE: D001, F003, F005.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.