

TBA INDUSTRIAL PRODUCTS -- TBA 510 -- 5330-01-194-8989

=====
===== Product Identification =====

Product ID:TBA 510
MSDS Date:11/10/1987
FSC:5330
NIIN:01-194-8989
MSDS Number: BTGJJ
=== Responsible Party ===
Company Name:TBA INDUSTRIAL PRODUCTS
Box:40
City:ROCHDALE, LANCS
Country:EN
Info Phone Num:800-527-1935
Emergency Phone Num:800-527-1935
CAGE:01309
=== Contractor Identification ===
Company Name:R-W
AY GASKET AND SUPPLY CO
Address:1950 E SEDGLEY AVE
Box:City:PHILADELPHIA
State:PA
ZIP:19124-5622
Country:US
Phone:215-697-6350/215-743-1650
CAGE:5S153
Company Name:TBA INDUSTRIAL PRODUCTS
Box:40
City:ROCHDALE, LANCS
Country:EN
Phone:800-527-1935
CAGE:01309

=====
===== Composition/Information on Ingredients =====

Ingred Name:ASBESTOS, CHRYSOTILE (SARA III)
CAS:12001-29-5
RTECS #:CI6478500
Fraction by Wt: 72%
Other REC Limits:NONE RECOMME
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:2 FIBERS/C

C; A1;9394

Ingred Name:INERT FILLERS
Fraction by Wt: 3%
Other REC Limits:NONE RECOMME

Ingred Name:SYNTHETIC RUBBER
Fraction by Wt: 20%
Other REC Limits:NONE RECOMME

Ingred Name:CURING AGENTS
Fraction by Wt: 5%
Other REC Limits:NONE RECOMME

===== Hazards Identification =====

LD50 LC50 Mixture:TLV ASBESTOS=0.2 FIBERS/CC
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:HEALTH HAZARD-HAZARD WOULD ARISE ONLY
IF PRODUCT IS SUBJECTED TO MECHANICAL ACTION THAT WOULD RELEASE
FIBERS.ACUTE HAZARD:EYE AND SKIN IRRITATION. CHRONIC
HAZARD:INHALATION OF AIRBORNE FIBERS CAN CAUSE ASBESTOSIS,LUNG
CANCER AND MESOTHELIOMA.INGESTION CAN CAUSE CANCER OF GI TRACT AND
LARYNX.
Explanation of Carcinogenicity:ASBESTOS IS LISTED UNDER NTP,IARC AND
OSHA.
Effects of Overexposure:EYE/SKIN:IRRITATION. INHALATION:LABORED
BREATHING,RESTRICTED PULMONARY FUNCTION.
Medical Condition Aggravated by Exposure:INDIVIDUALS WITH A HISTORY OF SKIN
AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.
HIGHER RISK WITH SMOKERS.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.IF
IRRITATION PERSISTS,SEE DOCTOR. SKIN:WASH WITH SOAP AND WATER WHILE
REMOVING CONTAMINATED CLOTHING AND SHOES.IF IRRITATION PERSISTS,SEE
DOCTOR. INHALATION:REMOVE VICTIM

TO FRESH AIR.SEE DOCTOR.
INGESTION:NO SPECIFIC ACTION.SEE DOCTOR.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE WATER OR FOAM.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:FIRE CONDITIONS MAY CREATE TOXIC FUMES FROM THE RUBBER COMPONENT.

===== Accident
al Release Measures =====

Spill Release Procedures:USE WET COLLECTION METHOD.VACUUM UP WITH HEPA FILTERED VACUUM CLEANER. WEAR PROTECTIVE EQUIPMENT AND HALF FACE RESPIRATOR WITH HEPA FILTERS.
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLEAN,DRY PLACE,AWAY FROM STRONG OXIDIZING AGENTS. NORMAL WASH UP AFTER HANDLING IS RECOMMENDED.
Other Precautions:ASBESTOS IS BONDED BY AN ELASTOMETER COMPOUND, HOWEVER, DO NOT MISUSE BY IMPROPER CUTTING OR HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF FIBERS MAY BE RELEASED, USE NIOSH APPROVED HALF FACE RESPIRATOR WITH HEPA FILTER FOR ASBESTOS FIBERS.
Ventilation:NO SPECIAL REQUIREMENT UNDER NORMAL CONDITIONS. IF FIBERS MAY BE RELEASED, USE LOCAL EXHAUST VENTILATION.
Protective Gloves:NOT NORMALLY REQUIRED.
Eye Protection:
SAFETY GLASSES.
Other Protective Equipment:USE FULL BODY PROTECTION IF THE PEL IS EXCEEDED.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health
AS MANUFACTURED, LOCKED-IN ASBESTOS DOES NOT PRESENT A HAZARD. ONLY WHEN THE ITEM IS SUBJECTED TO ABRASIVE ACTIONS AND DUST IS GENERATED, THEN ASBESTOS FIBERS MAY BE RELEASED AND BECOME AIRBORNE.

===== Physical/Chemical Prop

erties =====

HCC:T6

Solubility in Water:INSOLUBLE

Appearance and Odor:SHEET;BLACK;SLIGHT RUBBERY ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION

Hazardous Decomposition Products:SMOKE,CARBON MONOXIDE,ASBESTOS
FIBERS,UNKNOWN PRODUCTS.

===== Disposal Considerations =====

==

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER.

ASBESTOS DUST SHOULD BE WETTED AND VACUUMED UP WITH HEPA FILTERED
VACUUM CLEANER,SEALED IN A PLASTIC BAG,AND TURNED IN TO DISPOSAL
COMPANY.DISPOSE OF IN ACCORDANCE WITH ALL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly o

r implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.