

HENTZEN COATINGS, INC -- OFF-WHITE HIGH SOLIDS PRIMER, PART A, ID 4488WEP-3 --  
8010-01-309-0328

===== Product Identification =====

Product ID:OFF-WHITE HIGH SOLIDS PRIMER, PART A, ID 4488WEP-3

MSDS Date:12/02/1993

FSC:8010

NIIN:01-309-0328

Kit Part:Y

MSDS Number: BTGLP

=== Responsible Party ===

Company Name:HENTZEN COATINGS, INC

Address:6937 W MILL ROAD

City:MILWAUKEE

State:WI

ZIP:53218

Country:U

S

Info Phone Num:414-353-4200

Emergency Phone Num:414-353-4200/800-424-9300 CHEMTREC

Preparer's Name:JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOAMYL KETONE

CAS:110-12-3

RTECS #:MP3850000

Fraction by Wt: 14.738%

Other REC Limits:NONE RECOMME

OSHA

PEL:50 PPM  
ACGIH TLV:50 PPM

Ingred Name:TITANIUM DIOXIDE PIGMENT  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 20-30%  
Other REC Limits:NONE RECOMME  
OSHA PEL:10 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:SILICA PIGMENT  
CAS:14808-60-7  
RTECS #:VV7330000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMME  
OSHA PEL:0.1 MG/M3  
ACGIH TLV:0.1 MG/M3

Ingred Name:EPOXY RESIN  
Fraction by Wt: 15-20%  
Other REC Limits:NONE RECOMME

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)  
CAS:108-10-1  
RTECS #:SA9275000  
Fr  
action by Wt: 7.016%  
Other REC Limits:NONE RECOMME  
OSHA PEL:50 PPM; STEL 75 PPM  
ACGIH TLV:50 PPM; STEL 75 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:EPOXY RESIN  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMME

Ingred Name:BUTYL ALCOHOL SOLVENT (SARA III)  
CAS:71-36-3  
RTECS #:EO1400000  
Fraction by Wt: 1.044%  
Other REC Limits:SKIN NOTATIO  
OSHA PEL:50 PPM (CEILING)  
ACGIH TLV:50 PPM (CEILING)  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC METAL (SARA III)  
CAS:7440-66-6

RTECS #:ZG8600000  
Fraction by Wt: 1.616%  
Other REC Limits:NUISANCE DUS  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:UNREGULATED CORROSION INHIBITIVE PIGMENT  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMME

Ingred Name:VOC: 3.033 LBS/GAL; 363.444 GRAMS/LITER  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMME

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES  
Health Hazards Acute and Chronic:INHAL: ANESTHETIC. RESP T  
RACT IRRIT,  
ACUTE NERVOUS SYSTEM DEPRESSION (HEADACHE, DIZZINESS, STAGGERING,  
CONFUSION, COMA). SKIN OR EYE: IRRIT. CHRONIC:REPEATED & PROLONGED  
OVEREXPOSURE TO SOLVENTS W/PER MANENT BRAIN & NERVOUS SYSTEM  
DAMAGE, LIVER, KIDNEY DAMAGE. MAY CAUSE LUNG INJURY IF RESPIRATORY  
PRECAUTION NOT USED.

Explanation of Carcinogenicity:BASED UPON ANIMAL DATA, IARC HAS LISTED  
SILICA AS PROBABLE HUMAN CARCINOGEN.

Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY  
AILME  
NTS; CHEMICAL SENSITIZATION.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP  
WARM & QUIET. NOTIFY PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH LARGE  
AMOUNTS OF RUNNING WATER AT LEAST 15 MINUTES. TAKE TO PHYSICIAN FOR  
MEDICAL TREATMENT. SKIN: WASH AFFECTED AREAS WITH SOAP & WATER.  
REMOVE CONTAMINATED CLOTHING. CONSULT PHYSICIAN. INGESTION: CALL  
PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:60.0F,15.6C  
Lower Limits:1.0  
Upper Limits:11.2  
Extinguishing Media:FOAM, DRY CHEMICAL, CO2  
Fire Fighting Procedures:WEAR FULL PROTECTIVE EQUIP INCLUDING SCBA.  
WATER MAY BE INEFFECTIVE,USE TO COOL (FOG NOZZLE PREFERRED) CLOSED  
CONTAINER (PREVENT PRESSR BLDUP,AUTOIGNIT,EXPLOSN)  
Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLSD. KEEP FROM  
HEAT/IGNIT SOURCE. CLOSED CONTAINER

MAY EXPLODE W/HEAT. DON'T APPLY  
TO HOT SURFACE. NEVER USE WELD/CUT TORCH ON/NEAR DRUM

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN & REMOVE WITH INERT ABSORBENT AND NONSPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO  
N'T STORE ABOVE 120F.STORE LRG QTY  
IN BLDGS IN COMPLY W/OSHA1910.106.KEEP AWAY FROM  
SPARKS/FLAME.EMPTIED CNTNR RETAIN HZD RESIDUE & EXPLOSIVE VAPOR.  
Other Precautions:DON'T INGEST.GROUND CNTNR WHEN POURING. AVOID LIQ  
FREE FALL >FEW INCHES. USE W/VENT & RSPRTRY EQUIP. AVOID PROLONGED  
VAPOR BREATHING/SPRAY MIST. AVOID PROLONGED/REPEATED SKIN CONTACT.  
FOLLOW PRECAUTIONS IN MSDS TILL CNTNR CLEANED/DESTROYED.

===== Exposure Controls/Personal Protection =====

R

Respiratory Protection:WHEN SPRAY IN OUTDOOR OR DURING SAND/GRINDING:  
NIOSH MECHAN FILTER RSPRTR (REMOVE SOLID PARTICLES). RESTRICTED  
AREA: NIOSH CHEM/MECHAN FILTER (SOLID & GAS). CONFINED AREA: NIOSH  
AIR SUPPLD RSPRTR/HOOD .USE NIOSH RSPRTR WHEN WELD,CUT,HAZING.  
Ventilation:GENRL DILUTN/LOCAL EXHAUST TO KEEP BELOW PEL IN  
MIXING,APPLICATION & CURING AREAS & REMOVE DECOMP FROM WELD & FLAME  
CUT.  
Protective Gloves:REQUIRIED FOR PROLONGED/REPEATED CONTACT  
Eye Protection:SAFETY EYEW  
EAR W/SPLASH GUARDS,SIDE SHLD  
Other Protective Equipment:PROTECTIVE SKIN CREAM IF CONTACT  
LIKELY.PREVENT PROLONGED SKIN CONTACT W/CONTAM CLOTHES.WASH CONTAM  
CLOTHES BEFORE REUSE  
Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING. SMOKE IN  
DESIGNATED AREA ONLY.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:232 TO 298F  
Decomp Temp:Decomp Text:400F,204C  
Vapor Pres:15.00 @68F  
Vapor Density:> AIR  
Spec Gr

avity:1.55

Viscosity:65-80 KU

Evaporation Rate & Reference:FASTER THAN BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:OPAQUE LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:44.96

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION AS IN WELDING. MAY CONTAIN CARBON MONOXIDE, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE IN AN APPROVED FACILITY. EPA HAZARDOUS WASTE NUMBER CODE: D001, IGNITABLE. DISPOSAL METHODS: INCINERATION.

=====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.