View NSN Online: https://aerobasegroup.com/nsn/8010-01-309-0329

HENTZEN COATINGS, INC -- MIL-P-53022B, TYPE II CATALYST, PART B -- 8010-01-309-0329

============ Product Identification ==============

Product ID:MIL-P-53022B, TYPE II CATALYST, PART B

MSDS Date:12/02/1993

FSC:8010

NIIN:01-309-0329

Kit Part:Y

MSDS Number: BTGLS === Responsible Party ===

Company Name: HENTZEN COATINGS, INC

Address:6937 W MILL ROAD

City:MILWAUKEE

State:WI ZIP:53218 Country:US

Info Phone Num:414-353

-4200

Emergency Phone Num:414-353-4200/800-424-9300 CHEMTREC

Preparer's Name: JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name: HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI ZIP:53218 Country:US

Phone:414-353-4200

CAGE:09225

======= Composition/Information on Ingredients ========

Ingred Name: 1-METHOXY-2-PROPANOL SOLVENT

CAS:107-98-2

RTECS #:UB7700000 Fraction by Wt: 45.016%

Other REC Limits: NONE RECOMME

OSHA PEL:100 PPM;STEL

150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

Ingred Name: EPOXY RESIN

Fraction by Wt: 30-40%

Other REC Limits: NONE RECOMME

Ingred Name: METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000 Fraction by Wt: 2.333%

Other REC Limits:NONE RECOMME OSHA PEL:50 PPM; STEL 75 PPM ACGIH TLV:50 PPM; STEL 75 PPM

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE SOLVENT (SARA III)

CAS:95-63-6

RTECS #:DC3325000 Fraction by Wt: 4.468%

Other REC Limits: NONE RECOMME

**OSHA PEL:25** 

PPM

**ACGIH TLV:25 PPM** 

Ingred Name: AROMATIC HYDROCARBON SOLVENT (MIXTURE OF C8'S TO C10'S)

CAS:64742-95-6

Fraction by Wt: 8.797%

Ingred Name: VOC: 4.991 LBS/GAL; 598.071 GRAMS/LITER

RTECS #:9999999VO

Other REC Limits: NONE RECOMME

========== Hazards Identification ================

Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. RESPIRATORY TRACT IRRITATION, ACUTE NERVOUS SYSTEM DEPRESSION (HEADACHE, DIZZINESS, STAGGERING, CONFUSION, COMA). SKIN OR EYE: IRRITAT ION.

CHRONIC OVEREXPOSURE: REPEATED OR PRO LONGED OVEREXPOSURE WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE, LIVER, KIDNEY DAMAGE.

Medical Cond Aggravated by Exposure: ASTHMA AND OTHER RESPIRATORY AILMENTS; CHEMICAL SENSITIZATION.

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. NOTIFY PHYSICIAN. EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF RUNNING WATER FOR AT LEAST 15 M

INUTES. TAKE TO A PHYSICIAN FOR MEDICAL TREATMENT. SKIN: WASH AFFECTEDAREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN. INGESTION: CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. Flash Point Method:TCC Flash Point:60.0F.15.6C Lower Limits:0.9 Upper Limits:36.5 Extinguishing Media: FOAM, DRY CHEMICAL, CO2 Fire Fighting Procedures: WEAR PROTECT EQUIP INCLUDING SCBA. WATER MAY INEFFECTIVE, USE WATER (FOG NOZZLES PREFERRED) COOL CLOSED CNTNR TO PREVENT PRESSURE BLDUP, AUTOIGNITN, EXPLOSION. Unusual Fire/Explosion Hazard: KEEP CONTAINER TIGHTLY CLOSED. KEEP FROM HEAT/IGNIT SOURCE. CLOSED CNTNR MAY EXPLODE W/HEAT. DON'T APPLY TO HOT SRFCS. NEVER USE WELD/CUT TORCH ON/NEAR DRUM. ======== Accidental Release Measures ============= Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN & REMOVE WITH INERT ABSORBENT AND NONSPARKING TOOLS. ============= Handling and Storage ========================== Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP AWAY FROM SPARKS & OPEN FLAME. DON'T INGEST. Other Precautions: GROUND CONTAINERS WHEN POURING. AVOID LIQUID FREE FALL > FEW INCHES. USE W/VENT & RESP EQUIP. AVOID PROLONGED VAPOR BREATHING. AVOID PROLONGED/REPEATED SKIN CONTACT. EMPTIED CNTNR

RETAIN HZD RESIDUE/EX PLOSIVE VAPOR. OBEY ALL HZD PRECAUTIONS.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: WHEN SPRAYED IN OUTDOOR OR DURING SAND/GRINDING: NIOSH MECHAN FILTER RESPRTR (RMV SOLID PARTICLES). RESTRICTED AREA: NIOSH CHEM/MECHAN FILTER. CONFINED AREA: NIOSH AIR SUPPLIED RSPRTR/HOOD. USE NIOSH RSPRTR WHEN CUTTING/WELDING/HAZING TORCH Ve

ntilation:GENRL DILUTN/LOCAL EXHAUST VENT TO KEEP BELOW PEL/TLV WHILE MIXING, APPLICATION, CURING, REMOVE DECOMP FROM WELD/FLAME CUT. Protective Gloves: REQ'D FOR PROLONGED OR REPEATED CONTACT Eye Protection: SAFETY EYEWEAR W/SPLASH GUARDS/SIDE SHLD Other Protective Equipment: USE PROTECTIVE SKIN CREAM WHERE CONTACT IS LIKELY. PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING. Work Hygienic Practices: WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING OR SMOKING. SMOK E IN DESIGNATED AREAS ONLY. Supplemental Safety and Health ========= Physical/Chemical Properties =========== Boiling Pt:B.P. Text:232 TO 418F Decomp Temp:Decomp Text:400F,204C Vapor Pres:15.00 @68F Vapor Density:> AIR Spec Gravity:0.97 Viscosity:20-40"ZAHNCUP Evaporation Rate & Deference: FASTER THAN BUTYL ACETATE Solubility in Water: NEGLIGIBLE Appearance and Odor: AMBER LIQUID, SOLVENT ODOR Percent Volatiles by Volume:66.41 ======== Stability and Reactivity Dat Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Hazardous Decomposition Products: MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION AS IN WELDING. MAY CONTAIN CARBON MONOXIDE & CARBON DIOXIDE. ======= Disposal Considerations ============ Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP AWAY FROM SPARKS AND OP EN FLAME. EPA HAZARDOUS

WASTE NUMBER/CODE: D001, IGNITABLE. DISPOSAL METHODS: INCINERATION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person

utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.