View NSN Online: https://aerobasegroup.com/nsn/6810-00-822-7637

Address:1888 NIRVANA AVE City:CHULA VISTA

State:CA

ZIP:92011-6118 Country:US

Info Phone Num:619-421-6601

Emergency Phone Num:619-421-6601

CAGE:1194X

=== Contractor Identification ===

Company Name: CROWN CHEMICAL CORP

Company Name: CROWN CHEMICAL CORP

Address:1888 NIRVANA AVE Box:City:CHULA VISTA

State:CA

ZIP:92011-6118 Country:US CAGE:1194X

======= Composition/Information on Ingredients ========

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM/500STEL;9394

========= Hazards Identification ==============

LD50 LC50 Mixture

:ORAL LD50 (RAT) = 5840 MG/KG

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE-LIQUID IS IRRITATING TO EYES.

SKIN-LIQUID IS MILDLY IRRITATING TO THE SKIN. INHALATION-VAPORS MAY BE IRRITATING TO THE NOSE, THROAT & RESPIRATORY TRACT. HIGH VAPOR CONCENTRATIONS MAY CAUSE CNS DEP RESSION. INGESTION-EARLY TO MODERATE CNSDEPRESSION.

Explanation of Carcinogenicity: THIS CHEMICAL IS NOT LISTED A S HAVING

ANY EVIDENCE OF BEING CARCINOGENIC.

Effects of Overexposure:EYE-MAY CAUSE PAIN, TEARING, AND INFLAMMATION. SKIN-SKIN IRRITATION & DERMATITIS. INGESTION-GIDDINESS, HEADACHE, NAUSEA AND DIZZINESS; IN EXTREME CASES UNCONSCIOUSNESS AND DEATH MAY OCCUR. ASPIRATION PNEUMONITIS MAY EVIDENCED BY COUGHING, LABORED BREATHING AND CYANOSIS, IN SEVERE CASES DEATH.

Medical Cond Aggravated by Exposure:PREEXISTING EYE, AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

======================================
--

First Aid:EYE-HOLD EYELIDS OPEN & FLUSH WITH PLENTY OF WATER FOR 15 MIN. GET MEDICAL ATTENTION. SKIN-REMOVE CLOTHIN/SHOES. FLUSH SKIN WITH WATER. THEN WASH WITH SOAP/WATER. IF IRRITATION OCCURS, CONTACT PHYSICI AN. INHALATION-REMOVE VICTIM TO FRESH AIR, IF BREATHING IS HARD, PROVIDE OXYGEN; IF NOT BREATHING GIVE CPR. GET MEDICAL ATTENTION. INGESTION-DO NOT INDCUE VOMITING. GET MEDICAL AT

TENTION.

Flash Point:=11.7C, 53.F

Lower Limits:2
Upper Limits:12

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. DO NOT USE DIRECT WATER STREAM. PRODUCT WILL FLOAT & REIGNITE.

Fire Fighting Procedures:WEAR FULL BUNKER GEAR, INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard: CONTAINERS EXPOSED TO

FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE.
========= Accidental Release Measures ==========
Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. SOAK UP WITH ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINER. SEAL TIGHTLY AND IDENTIFY FOR PROPER DIS POSAL. Neutralizing Agent:NONE
======================================
Handling and Storage Precautions:STOW CONTAINERS IN A SAFE NON-TRAFFIC AREA. KEEP CONTAINER TIGHTLY CLOSED & WELL IDENTIFIED. Other Precautions:DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE A NIOSH APPROVED RESPIRATOR O AVOID OVER EXPOSURE, WHE N ANTICIPATED EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS. USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR-PURYFYING RESPIRATOR FOR ORGANIC VAPORS. Ventilation:USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS. Protective Gloves:WEAR CHEMICAL RESISTANT GLOVES. Eye Protection:WEAR SAFETY GLASSES OR GOGGLES. Other Protective Equipment:WERA CHEMICAL RESIATNT CLOTHES AS REQUIRED. Work Hygienic Practices:AIR DRY CONTAMINATED CLOTHING IN A WELL VENT ILATED AREA. LAUNDER BEFORE REUSE. Supplemental Safety and Health AVOID PROLONGED OR REPEATED CONTACT WITH THE SKIN.
========= Physical/Chemical Properties ==========
HCC:F2 Boiling Pt:=82.2C, 180.F Melt/Freeze Pt:

INTENSE HEAT FROM