

LIQUID CARBONIC CORP -- LIQUID NITROGEN -- 9135-00-985-7080

=====  
Product Identification  
=====

Product ID:LIQUID NITROGEN

MSDS Date:07/01/1990

FSC:9135

NIIN:00-985-7080

MSDS Number: BTKSP

=== Responsible Party ===

Company Name:LIQUID CARBONIC CORP

Address:135 S LA SALLE STREET

City:CHICAGO

State:IL

ZIP:60603-4101

Country:US

Info Phone Num:312-855-2500

Emergency Phone Num:312-855-2500

CAGE:36517

=

== Contractor Identification ==

Company Name:LIQUID CARBONIC CORP

Address:135 S LA SALLE STREET

Box:City:CHICAGO

State:IL

ZIP:60603-4101

Country:US

Phone:312-855-2500

CAGE:36517

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:QW9700000

Fraction by Wt: 99.9%

ACGIH TLV:ASPHYXIAN; 9192

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogen

icity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NITROGEN IS NON-TOXIC & IS CLASSED AS A SIMPLE ASPHYXIANT - IT DISPLACES OXYGEN IN THE AIR. CONTACT WITH LIQUID WILL CAUSE FROSTBITE.

Explanation of Carcinogenicity:THIS PRODUCT IS NOT LISTED BY NTP, IARC, OR OSHA

Effects of Overexposure:INHALED:DIZZINESS, DROWSINESS, EVENTUAL UNCONSCIOUSNESS

Medical Cond Aggravated by Exposure:NO INFORMATION GIVEN ON MSDS BY MFR.

=====  
===== First Aid Measures =====  
=====

First Aid:INHALE:REMOVE TO FRESH AIR. RESTORE OR SUPPORT BREATHING IF NECESSARY. KEEP WARM & AT REST. USE CAUTION WHEN ENTERING CONTAMINATED AREAS TO VENTILATE TO ACCEPTABLE OXYGEN LEVELS. FROST BITE:FLUSH AFFECTED AREAS W/LUKE WARM WATER. \*\*DO NOT USE HOT WATER\*\* FOR SERIOUS CRYOGENIC FREEZING BURN,SEE PHYSICIAN IMMEDIATELY.

=====  
===== Fire Fighting Measures =====  
=====

Extinguishing Media:NON-FLAMMABLE INERT GAS AND LIQUID  
Un

usual Fire/Explosion Hazard:IF CONTAINERS ARE INVOLVED IN A FIRE, SAFELY RELOCATE OR COOL WITH WATER SPRAY.

=====  
===== Accidental Release Measures =====  
=====

Spill Release Procedures:FOLLOW SUPPLIER"S INSTRUCTIONS. LIQUID NITROGEN IS HANDLED IN VACUUM JACKETED VESSELS. IF THERE IS A MAL-FUNCTION, CONTACT THE CLOSEST SUPPLIER LOCATION IMMEDIATELY. USE IN A WELL VENTILATED AREA AND USE A "FIRST IN/FIRST OUT" INVENTORY SYSTEM.

Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR.

=====  
===== Handling and Storage =====  
=====

Handling and Storage Precautions:PROTECT CONTAINERS FROM PHYSICAL DAMAGE. STORE IN COOL, DRY WELL VENTILATED AREA AWAY FROM HEAT(ABOVE 130F) & DIRECT SUNLIGHT.

Other Precautions:REFER TO CGA SAFETY BULLETIN SB-2 & PHAMPHLETS P-1,P-9,P-12 & P-14. STORE CYLINDERS UPRIGHT AND FIRMLY SECURED. USE CHECKVALVE IN LINE TO PREVENT BACK FLOW. USE ONLY DOT OR ASME CODED CYLINDERS. DO NOT REF

ILL CYLINDERS, RETURN TO SUPPLIER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN IVENT OF A MAJOR LEAK, A SELF CONTAINED BREATHING APPARATUS MAY BE REQUIRED.

Ventilation:LOCAL EXHAUST OR MECHANICAL GENERAL VENTILATION TO PREVENT ACCUMULATION SO AS TO EXCLUDE AND ADEQUATE OXYGEN SUPPLY.

Protective Gloves:LOOSE FITTING,INSULATED

Eye Protection:SAFETY GOGGLES/GLASSES PLUS FACE SHIELD

Other Protective Equipment:SAFETY SHOES

Work Hygienic Prac

tices:MFR: ? HMIS:USE GOOD INDUSTRIAL HYGIENE

PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:G3

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:-320F,-196C

Vapor Pres:760 @BP

Vapor Density:0.97

Spec Gravity:0.81 @BP

Solubility in Water:VAPOR - VERY SLIGHT

Appearance and Odor:COLORLESS,ODORLESS GAS - LIQUID IS WATER WHITE

Percent Volatiles by Volume:1

00

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:MFR GAVE NO DISPOSAL INFORMATION. HMIS:NO DISPOSAL PROBLEM. GAS WILL DIFFUSE INTO ATMOSPHERE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by

elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.