View NSN Online: https://aerobasegroup.com/nsn/6850-01-209-3924

Product ID:P1117 FREON TA MSDS Date:01/05/1990 FSC:6850 NIIN:01-209-3924 MSDS Number: BTPLD === Responsible Party === Company Name: UNIVAR CORP VAN WATERS AND ROGERS INC Address:1600 NORTON BLDG 801 2ND AVE Box:34325 City:SEATTLE State:WA ZIP:98124-1325 Country:US Info Phone Num:303-388-5 651/206-889-3400 Emergency Phone Num:303-388-5651/206-889-3400 CAGE:GO055 === Contractor Identification === Company Name: UNIVAR CORP VAN WATERS/ROGERS INC Address:1600 NORTON BLDG 801 2ND AVE City:SEATTLE State:WA ZIP:98104-1564 Country:US Phone:206 447-5911 CAGE:GO055 Company Name: VAN WATERS AND ROGERS INC., UNIVAR CORP. Address:1600 NORTON BLDG. 801 2ND AVENUE Box:City:SEATTLE State:WA ZIP:98104-1564 Country:US Phone:206-447-5911/800-424-9300(CHEMTREC) CAGE:87664

======== Composition/In

formation on Ingredients =========

Ingred Name:FREON 113, 1,1,2,-TRICHLORO-1,2,2,-TRIFLUOROETHANE, TRICHLOROTRIFLUROETHANE CAS:76-13-1 RTECS #:KJ4000000 Fraction by Wt: 89% Other REC Limits:1000 PPM OSHA PEL:1000 PPM ACGIH TLV:1000 PPM Ozone Depleting Chemical:1 Ingred Name:ACETONE; DIMETHYL KETONE; 2-PROPANONE CAS:67-64-1 RTECS #:AL3150000 Exertise by Wh 449(

Fraction by Wt: 11% OSHA PEL:2400 MG/CUM ACGIH TLV:750 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

======= Hazards Identificatio

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. PROLONGED/REPEATED EXPOSURE BY INHALATION CAUSES CARDIAC IRREGULARITIES & DEATH. VAPORS ARE HEAVIER THAN AIR & CAN CAUSE SUFFOCATION BY REDUCING OXYGEN AVAILABLE FOR BREATHING. SKIN: IRRITATION AFTER PROLONGED CONTACT.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:LIGHT HEADEDNESS, G

IDDINESS, SHORTNESS OF

BREATH, NARCOSIS, UNCONSCIOUSNESS, SUFFOCATION, NAUSEA, VOMITING, IRRITATION.

Medical Cond Aggravated by Exposure:CARDIOVASCULAR DISEASE

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE CPR IF NECESSARY. EYES: FLUSH W/PLENTY OF WATER FOR 15 MINUTES. SKIN: WASH W/PLENTY OF SOAP & WATER. INGESTION: DON'T INDUCE VOMITING. IF CONSCIOUS, GIVE PLENTY O F WATER/MILK. DON'T GIVE ANYTHING BY M OUTH TO UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES. (SEE SUPPLEMENTAL DATA)

Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE Fire Fighting Procedures:WEAR SCBA & FULL PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL NEARBY CONTAINERS & STRUCTURES EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:WATER WILL EXTRACT A FLAMMABLE CO-SOLVENT WHICH WILL FORM A FLAMMABLE SUPERNATANT LAYER.

====

Spill Release Procedures:EXTINGUISH IGNITION SOURCES. SMALL: MOP/WIPE UP/DISPOSE OF IN DOT-APPROVED WASTE CONTAINER. LARGE: CONTAIN/DIKE W/SOIL/OTHER NON-COMBUSTIBLE ABSORBENT MATERIAL. PLACE ABSORBENT/RESIDUE IN DOT-APPROVED WASTE CONTAINER. KEEP OUT OF WATERWAYS.

Handling and Storage Precautions:STORE IN COOL, DRY WELL VENTILATED PLACE. STO

RE AWAY FROM IGNITION SOURCES. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. DON'T GET INTO EYES.

Other Precautions:DON'T USE PRESSURE TO EMPTY CONTAINERS. DON'T GET ON CLOTHING/SKIN. DON'T HEAT CLOSED CONTAINERS >125F. DON'T CUT/GRIND/WELD/DRILL/NEAR THIS CONTAINER. DON'T WEAR CONTACT LENSES.

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH APPROVED SCBA IN PRESSURE DEMAND MODE, SUPPLIED AIR RESPIRATOR

Ventilation:LOCAL MECH

ANICAL EXHAUST

Protective Gloves:RUBBER

Eye Protection: CHEMICAL GOGGLES/

Other Protective Equipment:LONG SLEEVED SHIRT, TROUSERS, SAFETY SHOES, RUBBER APRON, EYEWASH, SAFETY SHOWER

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NOTE TO PHYSICIAN: RISK OF ELICITING CARDIAC DYSRYTHMIAS/CATECHOLAMINE DRUGS/SUCH AS EPINEPHRINE/SHOULD BE CONSIDERED ONLY AS LAST RESORT IN LIFE THREATENING EMERGEN

## CIES. VAPORS ARE HEAVIER THAN AIR/W ILL COLLECT IN LOW PLACES. DON'T ENTER PLACES WHERE VAPORS ARE AT UNLESS WEARING PROTECTIVE EQUIPMENT.

Boiling Pt:B.P. Text:110.5F Melt/Freeze Pt:M.P/F.P Text:-150F Vapor Pres:380 Vapor Density:2.6 Spec Gravity:1.41 Evaporation Rate & amp; Reference:(BU AC =1): >1 Solubility in Water:INSOLUBLE Appearance and Odor:CLEAR, COLORLESS LIQUID W/FAINT SOLVENT ODOR

====== Stabil

Stability Indicator/Materials to Avoid:YES ALKALIS, OXIDIZING MATERIALS, WATER, MOIST AIR, ALKALINE EARTH METALS, POWERED ALUMINUM, ZINC. Stability Condition to Avoid:OPEN FLAMES, WELDING ARCS, HIGH TEMPERATURES, TEMP >125F & OTHER IGNITION SOURCES Hazardous Decomposition Products:CO, CO2, HYDROGEN CHLORIDE, CHLORINE, PHOSGENE, HYDROGEN FLOURIDE

Waste Disposal Methods:DIS

POSE OF CONTAMINATED PRODUCT & MATERIALS USED IN CLEANING UP SPILLS/LEAKS. EMPTY CONTAINERS CAN HAVE RESIDUES, GASES, MISTS & AREA SUBJECT TO PROPER WASTE DISPOSAL. DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accur ate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.