View NSN Online: https://aerobasegroup.com/nsn/1560-00-021-5922

Product ID:URANIUM METAL

MSDS Date:05/01/1994

FSC:1560

NIIN:00-021-5922

MSDS Number: BTQXS === Responsible Party ===

Company Name: CAMECO SPECIALTY METALS DEPT

Address:1 ELDORADO PL

City:PORT HOPE

State:ON Country:CA

Info Phone Num:905-885-4511

Emergency Phone Num:905-885-4511

Preparer's Name: JOHN

S. FRIEDMAN CAGE:2C003

=== Contractor Identification ===

Company Name: CAMECO SPECIALTY METALS DEPT

Address:1 ELDORADO PL Box:City:PORT HOPE

State:ON Country:CA CAGE:2C003

Company Name: LOCKHEED CORP LOCKHEED-GEORGIA CO DIV

Address:86 S COBB DR Box:City:MARIETTA

State:GA ZIP:30063 Country:US

Phone: 404-494-4411

CAGE:98897

======= Composition/Information on Ingredients ========

Ingred Name: URANIUM Fraction by Wt: 100%

Other REC Limits: NONE RECOMMENDED

====== Hazards I



LD50 LC50 Mixture:ORAL LD50 (RAT) IS NOT DETERMINED.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION-DUST INHALATION CAN RESULT IN RADIATION DOSE TO LUNGS. KIDNEY DAMAGE CAN OCCUR DUE TO CHEMICAL TOXICITY. SKIN CONTACT-LOW LEVEL RADIATION DOSE CAN RESULT FROM CONTINUED EXPOSURE. EYE CONTAC T-IRRITANT. INGESTION-INGESTION CAN RESULT IN RAD

IATION DOSE. KIDNEY DAMAGE CAN OCCUR DUE TO CHEMICAL TOXICITY.

Explanation of Carcinogenicity: NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure: NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:INHALATION-REMOVE FORM WORKPLACE TO PREVENT FURTHER EXPOSURE AND SHOWER. SKIN CONTACT-WASH THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. EYE CONTACT-FLUSH T

HOROUGHLY WITH WATER FOR AT LEAST 15

MINUTE S. GET MEDICAL AID. INGESTION-REMOVE FROM WORKPLACE TO PREVENT FURTHER EXPOSURE. GET MEDICAL AID.

========== Fire Fighting Measures ================

Autoignition Temp: Autoignition Temp Text: 800C

Extinguishing Media:CLASS D FIRE EXTINGUISHER, DRY SAND OR MAGNESIUMDIFLUORIDE SLAG.

Fire Fighting Procedures:FLAMMABLE; BURNS IN AIR AT 150-175C. IGNITES IN OXYGEN AT 170C. FINELY DIVIDED URANIUM METAL IS PYROPHIC. DO NOT

USE WATER TO ATTEMPT TO EXTINGUISH FIRE.

| | D 1 14 | | |
|----------------|-----------------|-------------------|--|
| Accidental | Ralasca Masc | sures =========== | |
| | LICICASE INICAS | MICO | |

Spill Release Procedures:SIGNIFICANT ONLY IF FINELY DIVIDED. CLEANUP TO MINIMIZE DUSTING. SURVEY FOR APLHA ACTIVITY.

============= Handling and Storage ==========================

Handling and Storage Precautions:STORE AWAY FROM ACIDS. USE LEATHER FACED GLOVES, WASH HANDS AFTER HANDLING BARE METAL. NORMAL INDUSTRIAL HANDLING AND HYGIENE.

Other Precautions: NONE

====

| ====== Exposure Controls/Personal Protection ======== |
|--|
| Respiratory Protection:MSA COMFO II CHEMICAL CARTRIDGE RESPIRATOR. Ventilation:ADEQUATE GENERAL AND LOCAL AIR EXHAUST SHOULD BE AVAILABLE. Protective Gloves:LEATHER FACED GLOVES. Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS. Other Protective Equipment:LONG SLEEVED COVERALLS, SAFETY BOOTS, HARD HAT. |
| Work Hygienic Practices:NORMAL INDUSTRIAL HYGIENE. Supplemental Safety and Health RADIOACTIVE MATERIAL, LOW SPECIFIC ACTIVITY (L SA), N.O.S. USE YELLOW RADIOACTIVE II OR III LABELS. |
| ========= Physical/Chemical Properties ========== |
| HCC:A1 Boiling Pt:B.P. Text:6904F,3818C Melt/Freeze Pt:M.P/F.P Text:2070F,1132C Spec Gravity:19.05 Solubility in Water:INSOLUBLE Appearance and Odor:SILVERY-WHITE METAL; SOLID. |
| ========== Stability and Reactivity Data ========== |
| Stability Indicator/Materials to Avoid:YES ACIDS; ATTACKED BY COLD WATER IN A FINELY DIVIDED STATE; METAL BECOMES COATED WITH A LAYER OF OXIDE IN AIR. Stability Condition to Avoid:AVOID CONTACT WITH OPEN IGNITION SOURCES. Hazardous Decomposition Products:URANO-URANIC OXIDE POWDER. |
| ======= Disposal Considerations =========== |
| Waste Disposal Methods:PLACE IN A SEALABLE CONTAINER (METAL, WOOD, ETC.) |
| Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no |
| |

manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.