View NSN Online: https://aerobasegroup.com/nsn/9150-00-267-7188

AEROSPACE LUBRICANTS INC. -- TRIBOLUBE-2 -- 9150-00-267-7188

Product ID:TRIBOLUBE-2 MSDS Date:10/20/1998

FSC:9150

NIIN:00-267-7188

MSDS Number: BTQYK === Responsible Party ===

Company Name: AEROSPACE LUBRICANTS INC.

Address:1505 DELASHMUT AVE

City:COLUMBUS

State:OH

ZIP:43212-2641 Country:US

Info Phone Num:614-291-3045

Emergency Phone Num:614-291-3045

CAGE:66164

=

== Contractor Identification ===

Company Name: AEROSPACE LUBRICANTS INC.

Address:1600 GEORGESVILLE RD

Box:City:COLUMBUS

State:OH ZIP:43228 Country:US

Phone:614-878-3600

CAGE:66164

Company Name: INLAND PACKAGING INC

Address: 209 PETERSON DR

Box:644

City: ELIZABETHTOWN

State:KY

ZIP:42701-9804 Country:US

Phone:502-737-6757

Contract Num:SP0450-01-M-C801

CAGE:66172

====== Composition/Information on Ingredients ========

Ingred Name: NO HAZARDOUS COMPONENTS WERE KNOWINGLY INCORPORATED INTO

THIS LUBRICANT. Other REC Limits: NONE RECOMMENDED ========= Hazards Identification =============== Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: NONE. CHRONIC: NONE. Explanation of Carcinogenicity: NOT CARCINOGENIC. Effects of Overexposure:PROLONGED AND REPEATED CONTACT WITH SKIN MAY CAUSE SKIN IRRITATION. DECOMPOSITION PRODUCTS AT HIGH TEMPERATURES **ABOVE 250C MAY** CAUSE "POLYMER FEVER." Medical Cond Aggravated by Exposure: NO KNOWN MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE. First Aid:INHALATION:REMOVE TO FRESH AIR IF NECESSARY SEEK MEDICAL ATTENTION. EYES-FLUSH WITH WATER, GET MEDICAL ATTENTION. SKIN-WIPE OFF AND WASH WITH SOAP AND WATER. INGESTION: NO KNOWN ADVERSE EFFECTS ARE KNOWN, CONSULT PHYSICIAN. ______ Autoignition Temp:>315.6C, 600.F Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY. Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS. DECOMPOSITION AT TEMPERATURES ABOVE 290C MAY CAUSE THE EXPLSION OF TOXIC GASOEUS FLUORI NE COMPOUNDS Unusual Fire/Explosion Hazard: TOXIC FLUORINE GASES ARE BY-PRODUCT OF COMBUSTION.. ======= Accidental Release M easures ========== Spill Release Procedures: SCOOP UP WITH PROPER TOOLS, WIPE UP WITH ABSORBENT CLOTH OR PAPER TOWEL, APPLY NON-SKID MATERIAL TO FLOOR. COLLECT WASTE MATERIAL FOR SALVAGE OR DISPOSAL ============= Handling and Storage ========================== Handling and Storage Precautions: USE REASONABLE CARE. DO NOT STORE ABOVE 250F OR NEAR FLAMMABLES. Other Precautions: DECOMPOSITION PRODUCTS FORMED AT HIGH TEMPERATURES ABOVE 250C MAY CAUSE POLYMER FEVER.

====== Exposure Controls/Personal Protection ======== Respiratory Protection: NOT REQUIRED UNLESS PRODUCT IS BEING USED AS A MIST. Ventilation: MECHANICAL (GENERAL): RECOMMENDED. Protective Gloves:PLASTIC DISPOSABLE. Eye Protection: SAFETY GLASSES RECOMMENDED. Other Protective Equipment: PLASTIC APRON, FABRIC LABORATORY COAT RECOMMENDED. Work Hygienic Practices: DO NOT CONTAMINATE SMOKING MATERIALS; WASH HANDS/OR CONTAMINATED AREA AFTER EXPOSURE. Supplemental Safety and Healt h **NONE** ======== Physical/Chemical Properties =========== HCC:V6 Boiling Pt:>260.C, 500.F Melt/Freeze Pt:>287.8C, 550.F Vapor Pres: