

MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY -- MOBILGUARD 450 (BLACK STAR) --
9150-01-053-0011

===== Product Identification =====

Product ID:MOBILGUARD 450 (BLACK STAR)

MSDS Date:11/30/1993

FSC:9150

NIIN:01-053-0011

MSDS Number: BTRKP

=== Responsible Party ===

Company Name:MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY

Address:PENNINGTON-ROCKY HILL RD

City:PENNINGTON

State:NJ

ZIP:08534

C

Country:US

Info Phone Num:800-662-4525

Emergency Phone Num:800-662-4525

CAGE:0AHK0

=== Contractor Identification ===

Company Name:MOBIL OIL CORP ENVIRONMENTAL AFFAIRS & TOXICOLOGY

Address:PENNINGTON-ROCKY HILL RD

Box:City:PENNINGTON

State:NJ

ZIP:08534

Country:US

CAGE:0AHK0

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

===== Composition/Information on Ingredients =====

Ingred Name:NON HAZARDOUS

INGREDIENTS

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:TLV: 5.00 MG/M3 SUGGESTED FOR OIL MIST
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.
Effects of Overexposure:NO SIGNIFICANT EFFECTS EXPECTED.
Medical Con
d Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WTHOROUGHLY WITH WATER. IF IRRITATION OCCURS,
CALL A PHYSICIAN. SKIN: WASH CONTACT AREAS WITH SOAP & WATER.
INHALATION: NOT EXPECTED TO BE A PROBLEM. HOWEVER, IF GREATER THAN
1/2 LITER ING ESTED, IMMEDIATELY GIVE 1-2 GLASSES OF WATER & CALL A
PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER FOR ASSISTANCE. DO NOT
INDUCE VOMITING OR
GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>450F,>232C
Autoignition Temp:Autoignition Temp Text:UNKNON
Lower Limits:0.6
Upper Limits:7.0
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER FOG.
WATER OR FOG MAY CAUSE FROTHING. USE WATER TO COOL FIRE EXPOSED
CONTAINER
Fire Fighting Procedures:WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY
FROM EXPOSURE. PREVENT RUNOF
F FROM FIRE CONTROL OR DILUTION FROM
ENTERING STREAMS, SEWERS, OR DRINKING WATER SUPPLY
Unusual Fire/Explosion Hazard:FOR FIRES IN ENCLOSED AREAS, FIRE
FIGHTERS MUST USE SELF-CONTAINED BREATHING APPARATUS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDENT TREATED SAWDUST,
DIATOMACEOUS EARTH, ETC. SHOVEL UP AND DISPOSE OF AT AN APPROPRIATE
WASTE DISPOSAL FACILITY IN ACCORDANCE WITH CURRENT APPLICABLE LAWS
AND

