

EXIDE CORP -- LEAD-ACID BATTERY -- 6140-01-203-4694

===== Product Identification =====

Product ID:LEAD-ACID BATTERY

MSDS Date:09/01/1993

FSC:6140

NIIN:01-203-4694

MSDS Number: BTRKY

=== Responsible Party ===

Company Name:EXIDE CORP

Address:645 PENN ST

City:READING

State:PA

ZIP:19612-4205

Country:US

Info Phone Num:215-378-0798

Emergency Phone Num:215-378-0798

CAGE:20038

=== Contractor Identificati

on ===

Company Name:CAMPBELL, J R EQUIPMENT CO

Address:3659 PARKWAY LN

Box:City:HILLIARD

State:OH

ZIP:43026-1236

Country:US

Phone:614-876-0132

CAGE:7T245

Company Name:CHICAGO INDUSTRIAL TRADING CO

Address:1901 LANDMEIER RD

Box:City:ELK GROVE VILLAGE

State:IL

ZIP:60007

Country:US

Phone:708-981-0090

CAGE:0K4U5

Company Name:EXIDE CORP

Address:645 PENN STREET

Box:14205

City:READING

State:PA

ZIP:19612-4205

Country:US

Phone:610-378-0500/0798

CAGE:20038

Company Name:EXIDE CORP.-GENERAL BATTERY CORP

Add

ress:645 PENN STREET
Box:City:READING
State:PA
ZIP:19601
Country:US
Phone:215-378-0527/800-424-9300(CHEMTREC)
CAGE:08163
Company Name:FIATALLIS N. AMERICA INC/CENTRAL PARTS OPERATION
Address:245 E NORTH AVE
Box:City:WHEATON
State:IL
ZIP:60187
Country:US
CAGE:2L857

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 53% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/
M3;DUST 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY (SARA III)
CAS:7440-36-0
RTECS #:CC4025000
Fraction by Wt: 0.2% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG SB/M3; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ARSENIC (SARA III)
CAS:7440-38-2
RTECS #:CG0525000
Fraction by Wt: 0.003% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3 (AS)
ACGIH TLV:0.01,A1 MG/M3; 9394
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CALCIUM, METAL
CA

S:7440-70-2
RTECS #:EV8040000
Fraction by Wt: 0.02% %
Other REC Limits:NONE RECOMMENDED

Ingred Name:TIN
CAS:7440-31-5
RTECS #:XP7320000
Fraction by Wt: 0.06% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9293

Ingred Name:POLYPROPYLENE RUBBER
CAS:9003-07-0
Fraction by Wt: 5-6% %
Other REC Limits:NONE RECOMMENDED

Ingred Name:SULFURIC ACID (SARA III)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 30-40% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1
MG/M3; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - FUSED
CAS:60676-86-0
RTECS #:VV7328000
Fraction by Wt: 3-5% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3 RDUST; Z-3
ACGIH TLV:0.1 MG/M3 RDUST;9394

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:HAZARDOUS EXPOSURE TO LEAD COMPOUNDS

CAN OCCUR ONLY WHEN PRODUCT IS HEATED, OXIDIZED OR OTHERWISE PROCESSED OR DAMAGED TO CREATE DUST, VAPOR OR FUME. INHALATION OF LEAD DUST MAY CAUSE RESPIRATORY TRAC T IRRITATION. INGESTION MAY CUASE GASTROINTESTINAL DISTURBANCES. MAY CAUSE EYE IRRITATION.

Explanation of Carcinogenicity:CONTAINS INORGANIC ARSENIC [7440-38-2] AND LEAD WHICH ARE LISTED BY NTP AND IARC AND REGULATED BY OSHA AS CARCINOGENS.

Effects of Overexposure:ACUTE: HEADACHE, FATIGUE, ABDOMINAL PAIN, LOSS OF APPETITE, MUSCULAR ACHES AND WEAKNESS, SLEEP DISTURBANCES AND IRRITABILITY. CHRONIC: ANEMIA, NEUROPATHY--PARTICULARLY OF THE MOTOR NERVES WITH WRIST D ROP, KIDNEY DAMAGE, REPRODUCTIVE CHANGESIN BOTH MALES AND FEMALES.

Medical Cond Aggravated by Exposure:LEAD AND ITS COMPOUNDS CAN AGGRAVATE SOME FORMS OF KIDNEY, LIVER AND NEUROLOGIC DISEASES.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE FROM EXPOSURE. GARGLE, WASH NOSE AND LIPS.

CONSULT PHYSICIAN. INGESTION: CONSULT PHYSICIAN IMMEDIATELY. SKIN: WASH IMMEDIATELY WITH SOAP AND WATER. EYES: FLUSH IMMEDIATELY WITH LARG E AMOUNTS OF WATER FOR 15 MINUTES. CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Lower Limits:4.1 % (H2)

Upper Limits:74.2% (H2)

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL

Fire Fighting Procedures:USE POSITIVE PRESSURE, SELF-CONTAINED BREATHING APPARATUS. WATER APPLIED TO ELECTR

OLYTE GENERATES HEAT &

CAUSES IT TO SPLATTER. WEAR CAID-RESISTANT CLOTHING.

Unusual Fire/Explosion Hazard:HIGHLY FLAMMABLE HYDROGEN GAS (H2) IS GENERATED DURING CHARGING AND OPERATION. TO AVOID RISK, KEEP IGNITION SOURCES AWAY FROM BATTERIES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW OF MATERIALM, CONTAIN/ABSORB SPILLS WITH DRY SAND, EARTH, VERMICULITE. DO NOT USE COMBUSTIBLE MATERIALS. IF POSSIBLE, CAREFULLY NEUT

RALIZE ELECTROLYTE WITH SODA

ASH, SODIUM BICARBONATE, LIME , ETC. WEAR ACID-RESISTANT CLOTHING,
BOOTS, GLOVES

Neutralizing Agent:SODA ASH, SODIUM BICARBONATE, LIME.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE BATTERIES IN COOL, DRY, WELL-
VENTILATED AREAS WITH IMPERVIOUS SURFACES AND ADEQUATE CONTAINMENT
IN THE EVENT OF SPILLS.

Other Precautions:BATTERIES SHOULD BE STORED UNDER ROOF FOR PROTECTION
AGAINST ADVER

SE WEATHER CONDITIONS. SEPARATE FROM INCOMPATIBLE
MATERIALS. STORE AND HANDLE ONLY IN AREAS WITH ADEQUATE WATER
SUPPLY AND SPILL CONTR OL. AVOID DAMAGE TO CONTAINERS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED UNDER NORMAL CONDITIONS. WHEN
CONCENTRATIONS OF SULFURIC ACID MIST ARE KNOWN TO EXCEED PEL, USE
NIOSH OR MSHA-APPROVED RESPIRATORY PROTECTION.

Ventilation:STORE AND HANDLE IN WELL-VENTILATED AREA. IF MECHANICAL

VENTILATION IS USED, COMPONENTS MUST BE ACID RESISTANT.

Protective Gloves:RUBBER OR PLASTIC ACID-RESISTANT

Eye Protection:CHEMICAL GOGGLES/FACE SHIELD

Other Protective Equipment:ACID RESISTANT APRON. UNDER SEVERE EXPOSURE
OR EMERGENCY, WEAR ACID-RESISTANT CLOTHING AND BOOTS.

Work Hygienic Practices:HANDLE BATTERIES CAUTIOUSLY TO AVOID SPILLS.

MAKE CERTAIN VENT CAPS ARE ON SECURELY. AVOID CONTACT WITH INTERNAL
PARTS.

Supplemental Safety and Health

IN AREAS WHERE SULFURIC ACID IS

HANDLED IN CONCENTRATIONS GREATER THAN

1%, EMERGENCY EYEWASH STATIONS AND SHOWERS SHOULD BE PROVIDED, WITH
UNLIMITED WATER SUPPLY.

=====
===== Physical/Chemical Properties =====

HCC:Z4

Boiling Pt:B.P. Text:203-240F

Vapor Pres:17 TO 11

Vapor Density:>1

Spec Gravity:1.23 TO 1.350

Evaporation Rate & Reference:LESS THAN 1

Solubility in Water:100%

Appearance and Odor:MANUFACTURED ARTICLE; NO APPARENT ODOR. ELECTROLYTE
IS CLEAR LIQUID.

=====
===== Stabil

ity and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS, BASES, HALIDES, HALOGENATES, POTASSIUM NITRATE,
PERMANGANATE, PEROXIDES, REDUCING AGENTS, NASCENT HYROGEN

Stability Condition to Avoid: PROLONGED OVERCHARGE, SOURCES OF IGNITION.

Hazardous Decomposition Products: TOXIC METAL FUME/VAPOR/DUST; CONTACT
WITH STRONG ACID IN PRESENCE OF NASCENT HYDROGEN MAY GENERATE
ARSINE GAS.

===== Disposal Considerations =====

===

Waste Disposal Methods: SEND SPENT BATTERIES TO SECONDARY LEAD SMELTER
FOR RECYCLING. PLACE NEUTRALIZED SLURRY INTO SEALED CONTAINERS AND
DISPOSE OF AS HAZARDOUS WASTE AS APPLICABLE. WASTE SHOULD BE
MANAGED IN ACCORDANCE WITH APPROVED LOCAL, STATE AND FEDERAL
REQUIREMENTS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatso
ever,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.