

ROYAL LUBRICANTS COMPANY INC. -- ROYCO 634 -- 9150-01-053-6688

===== Product Identification =====

Product ID:ROYCO 634
MSDS Date:04/27/1994
FSC:9150
NIIN:01-053-6688
MSDS Number: BTRWR
=== Responsible Party ===
Company Name:ROYAL LUBRICANTS COMPANY INC.
Address:6CAMPUS DRIVE
City:PARSIPPANY (FORMALLY IN EAST HANOVER)
State:NJ
ZIP:07054
Country:US
Info Phone Num:201-887-7410
Emergency Phone Num:20
1-887-7410
CAGE:07950
=== Contractor Identification ===
Company Name:ROYAL LUBRICANTS COMPANY INC.
Address:215 MERRY LN
Box:518
City:EAST HANOVER
State:NJ
ZIP:07936
Country:US
Phone:973-887-7411/7410
CAGE:07950

===== Composition/Information on Ingredients =====

Ingred Name:POLYALHAOLEFIN (PER MSDS CAS # 68037-01-4).
Fraction by Wt: 20-30%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ESTER (MSDS CAS # 108419-34-7).
Fraction by Wt: 15-25%
Other REC Limits:NONE RECOMMENDED

In

Ingredient Name: PETROLEUM HYDROCARBON (PER MSDS CAS #64742-53-6).

Fraction by Wt: 25-45%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 5 MG/M3 (OIL MIST)

ACGIH TLV: 5 MG/M3 (OIL MIST)

Ingredient Name: MIXTURE OF STODDARD SOLVENT (PER MSDS CAS #8053-41-3).

Fraction by Wt: 5-10%

Other REC Limits: NONE RECOMMENDED

Ingredient Name: MINOR ADDITIVES

Fraction by Wt: 200F, >93C

Extinguishing Media: USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

Fire Fighting Procedures: DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL

BUNKER GEAR, INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURE.

===== Accidental Release Measures =====

Spill Release Procedures: DIKE AND CONTAIN. SOAK UP WITH AN ABSORBENT MATERIAL. DISPOSE OF PROPERLY.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURE.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL,

DRY PLACE WITH ADEQUATE

VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

Other Precautions: WASH WITH SOAP & WATER BEFORE EATING, DRINKING OR USING TOILET FACILITIES. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE A NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.

Ventilation: NOT APPLICABLE PER MANUFACTURE'S MSDS.

Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: SAFE

TY GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURE.

Work Hygienic Practices:NONE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.8702

Viscosity:9.50CST @104F

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR AMBER LIQUID WITH FRUITY SMELL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS.

Stability Condi

on to Avoid:AVOID HEAT, FLAME AND CONTACT WITH STRONG
OXIDIZING AGENTS.

Hazardous Decomposition Products:COMPLEX MIXTURE OF AIRBORNE SOLID,
LIQUID, PARTICULATES AND GASES WILL EVELVE WHEN PYROLYSIS OR
COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN
COMPLIANCE WITH LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is form

ulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.