

CHEMEX PAINT AND COATINGS,INC. -- CHEM-PRO 9111 -- 8010-00-286-9072

===== Product Identification =====

Product ID:CHEM-PRO 9111

MSDS Date:01/01/1987

FSC:8010

NIIN:00-286-9072

MSDS Number: BTSFT

=== Responsible Party ===

Company Name:CHEMEX PAINT AND COATINGS,INC.

Address:2822 N 35TH ST.

City:TAMPA

State:FL

ZIP:33605

Country:US

Info Phone Num:ILLEGIBLE ON MSDS

Emergency Phone Num:ILLEGIBLE ON MSDS

CAGE:OA701

=== Contractor Identification ===

Company Name:CHEMEX PAINT & COATINGS, INC.

CAGE:0A701

Company Name:CHEMEX PAINT AND COATING

Address:2822 35TH STREET

City:TAMPA

State:FL

ZIP:33605

Country:US

Phone:(813) 248-6104

CAGE:OA701

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETROLEUM SOLVENT

CAS:8008-20-6

RTECS #:OA5500000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM PETR. DIST.

ACGIH TLV:400 PPM RUBBER SOLV.

Ingred Name:AROMATIC HYDRO

CARBONS

CAS:70995-17-8

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY
CAUSE IRRITATION.INGEST:MAY CAUSE GI TRACT IRRITATION.INHAL:MAY
CAUSE RESPIRATORY IRRITATION.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED
AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:SKIN:IRRITATION.INHAL/INGEST:NAUSEA,DIZZINESS.
Medical Cond Aggravated by Exposure:UNLIKELY TO AGGRIVATE EXISTING
MEDICAL CONDITIONS.

=====
===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND
WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH
AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT
INDUCE VOMITING. GET PROM
PT QUALIFIED MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:20.0F,-6.7C
Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER
FOG.
Unusual Fire/Explosion Hazard:VAPORS CAN FORM EXPLOSIVE MIXTURES WITH
AIR.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION.USE PROPER
RESPIRATORY AND PROTECTIVE EQUIPMENT.SHUT OFF LEAK IF
SAFE.DIKE.SOAK UP WITH A NON-COMBUSTIBLE INERT
ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.WASH
SPILL AREA TO REMOVE SLIPPINESS.
Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED
PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP

AWAY FROM SOURCES
OF IGNITION.

Other Precautions:AVOID SKIN AND EYE CONTACT.DO NOT INHALE
VAPORS/MISTS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN
ENCLOSED SPACES USE A NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC
VAPORS.

Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL)
VENTILATION TO MAINTAIN TLV/PEL.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GOGGLES.

Othe

r Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A
LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS
PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health

NONE

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt.=120.C, 248.F

Vapor Pres:2

Vapor Density: