View NSN Online: https://aerobasegroup.com/nsn/8030-00-252-8300

VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC. -- TECTYL 275 -- 8030-00-252-8300

Product ID:TECTYL 275 MSDS Date:02/10/1993

FSC:8030

NIIN:00-252-8300

MSDS Number: BTSNF === Responsible Party ===

Company Name: VALVOLINE OIL CO SUBSIDIARY OF ASHLAND OIL INC.

Address: 200 E MAIN ST

Box:14000

City:LEXINGTON

State:KY ZIP:40512 Country:US

Info Phone Num:606-264-7000/76

16;FAX 601-429-0537

Emergency Phone Num:800-274-5263

CAGE:72527

=== Contractor Identification === Company Name:RALRUBE INC.

Address:36977 FOX GLEN

Box:City:FARMINGTON HILLS

State:MI ZIP:48331 Country:US

Phone:248-661-0260, FAX 248-661-3941

CAGE:6X798

Company Name: VALVOLINE OIL CO

Address:3499 BLAZER PKY

Box:14000

City:LEXINGTON

State:KY ZIP:40512 Country:US

Phone:606-357-7206 / 800-274-5263

CAGE:72527

======= Composition/Information on Ingredients ========

Ingred Name: NAPHTHA, MED

IUM ALIPHATIC CAS:64742-88-7

Fraction by Wt: 25-40%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM ACGIH TLV:100 PPM

Ingred Name: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT

NAPHTHENIC/PETROLATUM

CAS:64742-53-6 RTECS #:PY8036000 Fraction by Wt: 25-40%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000 Fraction by Wt: 10-15%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:S, 50 PPM

AC

GIH TLV:S, 25 PPM; 9394

========== Hazards Identification ===============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY

CAUSE IRRITATION AND DEFATTING.2-BUTOXYETHANOL MAY BE DERMALLY

ABSORBED IN HARMFUL AMOUNTS.INGEST:MAY CAUSE GI TRACT

IRRITATION.MAY CAUSE LUNG DAMAGE IF VOMITED AFTE R

INGESTING.INHAL:MAY CAUSE RESPIRATORYIRRITAT

ION, CNS

EFFECTS.CHRONIC:MAY DAMAGE LIVER, CNS, KINDEY, BLOOD FORMING ORGANS.

Explanation of Carcinogenicity: THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP, IARC OR OSHA.

Effects of Overexposure:SKIN:DERMATITIS.EYES:REDNESS,TEARING,BLURRED VISION.INGEST:NAUSEA,VOMITING,DIARRHEA.INHAL:DIZZINESS,WEAKNESS,FAT IGUE,NAUSEA,HEADACHE,POSSIBLE UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN AND RESPIRATORY AILMENTS MAY BE

======================================
First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING. GET PROMPT QUALIFIED MEDICAL ATTENTION.
=========== Fire Fighting Measures =============
Flash Point Method:TCC Flash Point:>148F,>64C Lower Limits:1.
Extinguishing Media:REGULAR FOAM,CARBON DIOXIDE,DRY CHEMICAL.WATER OR FOAM CAN CAUSE FROTHING IF SPRAYED INTO BURNING LIQUID. Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.
Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR, CAN TRAVEL DISTANCES ALONG THE GROUND, AND FLASHBACK AT THE SOURCE.
======== Accidental Release Measures ==========
Spill Release Proced ures:ELIMINATE SOURCES OF IGNITION.USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.SHUT OFF LEAK IF SAFE.DIKE.SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSA L.PREVENT RUNOFF TO SEWER. Neutralizing Agent:NONE
============ Handling and Storage =============
Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID SOURCES OF IGNITION. USE WITH A DEQUATE VENTILATION.
Other Precautions:GROUND CONTAINERS WHEN TRANSFERRING LIQUIDS.FOLLOW LABEL DIRECTIONS.AVOID BREATHING VAPORS.AVOID SKIN AND EYE CONTACT.EMPTY CONTAINERS MAY BE DANGEROUS;DISPOSE OF PROPERLY.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A SELF-CONTAINED BREATHING APPARATUS. Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILAT

AT INCREASED RISK FROM EXPOSURE.

ION TO MAINTAIN TLV/PEL.

Protective Gloves: NEOPRENE, NITRILE.

Eye Protection: CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health

NONE

======== Physical/Chemical Properties ==========

HCC:V4
Boiling Pt:B.P. Text:
315F,157C
Vapor Pres:2
Vapor Density:>1
Spec Gravity:0.852-0.876
Viscosity: