

FISKE BROTHERS REFINING CO -- LUBRIPLATE,PRODUCT
NO:630-A;630-2;630-AA;630-AAA;630-AA-W. -- 9150-00-663-1770

===== Product Identification =====

Product ID:LUBRIPLATE,PRODUCT NO:630-A;630-2;630-AA;630-AAA;630-AA-W.

MSDS Date:01/01/1994

FSC:9150

NIIN:00-663-1770

MSDS Number: BTTSS

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:8038

City:TOLEDO

State:O

H

ZIP:43605-3843

Country:US

Info Phone Num:419-691-2491 / FAX 419-693-3806

Emergency Phone Num:800-255-3924CHEM-TEL

Preparer's Name:JAMES R. KONTAK

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-355-8041

Contract Num:SP0450-99-MB291

CAG

=====
Composition/Information on Ingredients
=====

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE PRESENT IN THIS PRODUCT.

RTECS #:9999999ZZ

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:5MG/M3 FOR OIL MIST IN AIR.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONG/REP

EAT SKIN CONTACT MAY CAUSE

IRRIT.MATL CONTACTING EYE MAY CAUSE IRRIT.HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON.AS PRECAUTION EXPOUSRE TO LIQ/VAP/MIST/FUME SHOULD BE MINIMIZED.THIS MATL HAS LOW ORDER OF ACUTE ORAL TOXICITY BUTMINUTE AMTS ASPIRATED INTO LUNGS DURING INGEST MAY CAUSE MILD-SEVERE PULM INJUR

Explanation of Carcinogenicity:PER MSDS CARCINOGENICITY:
NTP/IARC/OSHA:NO.

Effects of Overexposure:EYE/SKIN IRRIT. MILD TO SEVERE PULMONARY INJURY FROM ASPIRATION INTO LUNGS FROM INGEST.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MFG.

=====
First Aid Measures
=====

First Aid:EYE:FLUSH W/CLEAR WATER FOR 15MINS OR TIL IRRIT SUBSIDES.IF PERSISTS SEE DR.SKIN:REMOVE CONTAMIN CLOTH.WASH W/SOAP & WARM WATER.IF INJECTED BY HI PRESS UNDER SKIN REGARDLESS OF APPEARANCE/SIZE CALL DR IMMED.DELAY MAY CAUSE LOSS OF AFFECTEDPART OF BODY.INHAL:VAPOR PRESS VERY LOW;INHAL @ RM TEMP NOT A PROBLEM.IF OV

ERCOME BY VAPOR FROM HOT MATL IMMED REMOVE.CALL DR.INGEST:CALL DR.DO NOT INDUCE VOMIT

=====
Fire Fighting Measures
=====

Flash Point Method:COC

Flash Point:≈204.4C, 400.F

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY (FOG).

Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STOR

E OR MIX W/STRONG OXIDANTS.

EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD AS THEY MAY EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER W/SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS AND WATER COURSES.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING & LAUNDER BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:LOCAL EXHAUST USED TO CAPTURE FUMES & VAPORS.

Protective G

loves:OIL-RESISTANT GLOVES IF NEEDED.

Eye Protection:GOGGLES IF CHANCE OF EYE CONTACT.

Other Protective Equipment:USE OIL-RESISTANT APRON IF NEEDED.

Work Hygienic Practices:SEE OTHER PRECAUTIONS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.94-0.95

Evaporation Rate & Reference: