

SHACHIHATA INDUSTRIAL CO LTD -- XSTAMPER INK X-200 BLACK -- 7510-01-207-3961

=====  
Product Identification  
=====

Product ID:XSTAMPER INK X-200 BLACK

MSDS Date:12/05/1987

FSC:7510

NIIN:01-207-3961

MSDS Number: BTVSC

=== Responsible Party ===

Company Name:SHACHIHATA INDUSTRIAL CO LTD

Address:65 UWABATA CHO NISHI KU

City:NAGOYA

Country:JA

Info Phone Num:213-530-4445

Emergency Phone Num:213-530-4445

P

reparer's Name:ISAO HATTORI

CAGE:S4748

=== Contractor Identification ===

Company Name:SHACHIHATA INDUSTRIAL CO LTD

Address:65 UWABATA CHO NISHI KU

Box:City:NAGOYA

Country:JA

Phone:213-530-4445

CAGE:S4748

=====  
Composition/Information on Ingredients  
=====

Ingred Name:GLYCERYL STEARATE

CAS:123-94-4

Fraction by Wt: 42-48%

Ingred Name:2-(2-BUTOXYETHYOXY)-ETHANOL, DIETHYLENE GLYCOL MONOBUTYL  
ETHER (BUTYL CARBITOL)

CAS:112-34-5

RTECS #:KJ9100000

Fraction by Wt: 10-12%

Ingred

Name:1,2-PROPANEDIOL (PROPYLENE GLYCOL)

CAS:57-55-6

RTECS #:TY2000000

Fraction by Wt: 11-13%

Ingred Name:ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL  
CARBINOL

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 8-10%

Other REC Limits:400 PPM

OSHA PEL:400 PPM

ACGIH TLV:400 PPM

Ingred Name:9-OCTADECENOIC ACID (OLEIC ACID) (EMERSOL 210)

CAS:112-80-1

RTECS #:RG2275000

Fraction by Wt: 5-8%

Ingred Name:NIGROSINE BASE, SOLVENT BLACK 7 \*94-2\*

CAS:8005-02-5

Fraction by Wt: 8-12%

Ingred Name:C.

I. SOLVENT VIOLET 8

CAS:52080-58-7

Fraction by Wt: 8-12%

Ingred Name:FORMALDEHYDE, POLYMER WITH 1-PHENYLETHANONE, HYDROGENATED

CAS:68441-83-8

Fraction by Wt: 1-9%

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: MAY CAUSE SLIGHT IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:MAY CAUSE SLIGHT IRRITATION.

Med

ical Cond Aggravated by Exposure:NONE

=====  
First Aid Measures  
=====

First Aid:SKIN: REMOVE W/CLOTH/TOWEL & WASH EXPOSED AREA W/SOAP. EYES:  
FLUSH W/PLENTY OF WATER FOR 10 MINS. OBTAIN MEDICAL ATTENTION IN  
ALL CASES.

=====  
Fire Fighting Measures  
=====

Flash Point Method:CC  
Flash Point:99.68F  
Lower Limits:2  
Upper Limits:12  
Extinguishing Media:FOAM, DRY CHEMICAL  
Fire Fighting Procedures:NOT REQUIRED  
Unusual Fire/Exp  
losion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SCRAPE UP W/CARDBOARD/RAG & WASH THE AREA  
W/DETERGENT.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL PLACE & KEEP AWAY FROM  
SUNLIGHT & HEAT, FLAME.  
Other Precautions:KEEP AWAY FROM CHILDREN.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NOT REQUIRED  
Ventilat  
ion:NOT REQUIRED  
Protective Gloves:PLASTIC FILM/RUBBER  
Eye Protection:NOT REQUIRED  
Other Protective Equipment:NOT REQUIRED  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

Melt/Freeze Pt:M.P/F.P Text:5-77F  
Spec Gravity:1.04  
Solubility in Water:SLIGHT  
Appearance and Odor:PERFUME

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
NONE  
Stability Condition to Avoid:SUNLIGHT, HEAT & FLAM

E.  
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:CAN BE BURNED IAW/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.