View NSN Online: https://aerobasegroup.com/nsn/8040-00-726-3567

## DELTA PLASTICS CO -- ADHESIVE, PART 2 -- 8040-00-726-3567

============= Product Identification ==============

Product ID:ADHESIVE, PART 2

MSDS Date:07/08/1993

FSC:8040

NIIN:00-726-3567

Kit Part:Y

MSDS Number: BTVZL === Responsible Party ===

Company Name: DELTA PLASTICS CO Address: 280 SOUTH MAIN STREET

Box:489 City:PIXLEY State:CA ZIP:93256 Country:US

Info Phone Num:209-757-2010

Emergency Phone Num:209-757-2010

Pre

parer's Name: ERIC SKIFF

CAGE:DO191

=== Contractor Identification === Company Name: DELTA DPC, INC

Address:983 E. LEVIN AVE.

Box:City:TULARE

State:CA ZIP:93274 Country:US

Phone: 209-686-1644

CAGE:0ND20

Company Name: DELTA PLASTICS CO. Address: 280 MAIN ST. PO BOX 489

Box:489 City:PIXLEY State:CA ZIP:93256

Phone:209-757-2010

CAGE:DO191

====== Composition/Information on Ingredients ========

Ingred Name: POLYAMINE EPOXY HARDENER

Fraction by Wt: 100%

Other REC Limits: NONE RECOMMENDED

Ingr

Other REC Limits:NONE RECOMMENDED
======================================
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:IRRITATION, SENSITIZATION, DERMATITIS Effects of Overexposure:IRRITATION, SENSITIZATION, DERMATITIS Medical Cond Aggravated by Exposure:ALLERGY, ECZEMA OR SKIN CONDITIONS
======================================
First Aid:EY ES: IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN. SKIN: PROMPTLY WASH WITH MILD SOAP AND WATER. INGESTION: IF CONSCIOUS, GIVE LARGE QUANTITIES OF WATER. GET MEDICAL AT TENTION. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING IS DIFFICULT. OTHER: PROMPTLY REMOVE WET CONTAMINATED NON-IMPERVOIUS CLOTHING. WASH BEFORE REUSE.
======================================
Flash Point:205F,96C Extinguishing Media:CARB ON DIOXIDE, FOAM, DRY CHEMICAL, WATER SPRAY Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:AVOID HEAT, OPEN FLAMES, AND ELECTRIC SPARKS.
========= Accidental Release Measures ==========
Spill Release Procedures:SOAK UP IN ABSORBENT MATERIAL AND FLUSH THE AREA WITH PLENTY OF WATER.
============== Handling and Storage ==============
Handling and Storage Precautions: CAUTION: THIS SYSTEM CONTAINS AN EPOXY
RESIN WITH AN AMINE HARDNER. IN CASE OF CONTACT, WASH IMMEDIATELY WITH SOAP AND WATER.  Other Precautions:FOR EYES,FLUSH W/PLENTY OF WATER 15 MIN & CONSULT PHYSICIAN. AVOID SKIN OR EYE CONTACT. AVOID INHALATION OF VAPOR. USE GOOD VENT, PARTICULARLY IF HEATED/SPRAYED. THESE MATERIAL MAY CAUSE SKIN OR SENSI TIZATION OR OTHER ALLERGIC RESPONSES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:AIR MASK IF IN CONFINED AREA Ventilation:L

ed Name:VOC: 0 LB/GAL; 0 GRAMS/LITER

RTECS #:9999999VO

OCAL EXHAUST VENTILATION RECOMMENDED Protective Gloves: IMPERVIOUS RUBBER GLOVES Eye Protection: ONLY OSHA APPROVED EYE PROTECTION EQUIP Other Protective Equipment: SAFETY SHOWER AND EYE BATH. USE COVERALLS OR APRON, GLOVES, ETC TO PROTECT AGAINST SKIN & CLOTHING CONTAMINATION. Work Hygienic Practices: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health ======== Physical/Chemical Properties ============= Boiling Pt:B.P. Text:410F,210C Vap or Pres:0.05 Vapor Density:>1 Spec Gravity: 0.96 (WATER=1) pH:11.5 Viscosity:1000-2000 CP Evaporation Rate & Deference: NIL Solubility in Water:NIL Appearance and Odor: AMBER LIQUID, HAS A SLIGHT AMINE ODOR Percent Volatiles by Volume:NIL ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES STRONG ACIDS, BASES, AND MERCAPTANS IN BULK. AVOID STRONG OXIDIZING AGENTS. Stability Condition to Avoid: AVOID STRONG ACIDS, BASES AND MERCAPTA NS IN BULK. AVOID ELEVATED TEMPERATURES. Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES, AMMONIA ======= Disposal Considerations ============ Waste Disposal Methods: INCINERATE IN FURNACE OR BURY IN LANDFILL IN ACCORDANCE WITH FEDERAL, STATE, OR LOCAL REGULATION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United Sta

tes of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.