

BONDED PRODUCTS, INC -- EPOXY GROUT, PART A

=====
MSDS Safety Information
=====

FSC: 8040
NIIN: 00-726-3567
MSDS Date: 04/19/1994
MSDS Num: BTVZM
Product ID: EPOXY GROUT, PART A
MFN: 01
Kit Part: Y
Responsible Party
Cage: DO082
Name: BONDED PRODUCTS, INC
Address: 439 S BOLMAR ST
Box: 39
City: WEST
CHESTER PA 19382-4933
Info Phone Number: 610-696-9220
Emergency Phone Number: 610-696-9220
Preparer's Name: A NICHOLAS ROSA
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: DO082
Assigned Ind: Y
Name: BONDED PRODUCTS, INC
Address: 439 SOUTH BOLMAR STREET
Box: 39
City: WEST CHESTER PA 19381-0039

=====
Contractor Summary
=====

Cage: 19092
Name: ABBEY COLOR INC DBA ABBEY PRODUCTS AND BONDED
Address: 400 E TIOGA ST
City: PHILADELPHIA PA 19134-1127
Phone: 215-739-9960
Cage: DO082
Name: BONDED PRODUCTS, INC
Address: 439 SOUTH BOLMAR STREET
Box: 39
City: WEST CHESTER PA 19381-0039
Phone: 610-696-9220 OR 215-739-9960

=====
Item Description Information
=====

=====
Item Manager: GSA
Item Name: ADHESIVE
Unit of Issue: KT
UI Container Qty: 1
=====

Ingredients
=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Effects of Exposure: SKIN: POSSIB

LE IRRITATION AND SENSITIZATION ON PROLONGED

AND REPEATED CONTACT. EYES: IRRITATION OF EYES ON PROLONGED AND REPEATED
EXPOSURE. INHALATION: NAUSEA AND HEADACHE. INGESTION: ABDOMINAL DISCOM FORT.

Signs And Symptions Of Overexposure: SKIN IRRITATION, NAUSEA, AND HEADACHE.

VAPORS MAY IRRITATE RESPIRATORY PASSAGES.

Medical Cond Aggravated By Exposure: ANY PREVIOUS EYE, SKIN, RESPIRATORY OR
ALLERGIC CONDITIONS CAN BE AGGRAVATED BY EXPOSURE

First Aid: SKIN: WIPE OR FLUSH OFF SKIN, WASH IMMEDIA

TELY WITH SOAP AND WATER

AND DRY COMPLETELY. CONTACT PHYSICIAN IF IRRITATION PERSISTS. EYES: FLUSH
WITH WATER FOR 15 MINUTES. GET PHYSICIANS HELP. INHALATION: REMOVE PERSON TO
FRESH AIR. ADMINISTEROXYGEN, IF NECESSARY. INGESTION: CONTACT A PHYSICIAN.

=====
Handling and Disposal
=====

Spill Release Procedures: STOP FLOW.CONTAIN SPILL.SOAK UP W/ABSORBNT
MAT'L,SCRAPE UP & PUT INTO METAL

CNTNR.REMOVE IGNITN SOURCE.VENT.PROTECT

SKIN,EYES & RESPRTRY PASSAGE DURING CLEAN UP.PROTECT SHOES W/RUBBERS.USE
RUBBER OR V INYL FLOVES & SOLVNT & SOLVNT PROTECTING RESPRTRS.

Neutralizing Agent: THE PART B OF THIS PRODUCT WITH THE PART A

Waste Disposal Methods: RECLAIM IF POSSIBLE. FOR DISPOSAL, REACT THIS PART A
WITH THE PART B AND DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL
REGULATIONS.

Handling And Storage Precautions: HANDLE IN WELL VENTILATED AREA. USE PROTECT

CLOTHING. AVOID SKIN, EYES, & CLOTHING CONTACT. AVOID BREATHING VAPOR.
WASH W/SOAP & WATER AFTER HANDLING.

Other Precautions: STORE PRODUCT IN COOL DRY AREA IN TIGHTLY SEALED CONTAINER.
USE BARRIER CREAM IF NEEDED, WASH EXPOSED SKIN AREAS BEFORE EATING.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: CC

Flash Point Text: >245F,>118C

Extinguishing Media: F

OAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures: HANDLE AS A COMBUSTIBLE MATERIAL. CONTAINERS EXPOSED
TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY. FIREFIGHTERS SHOULD WEAR CBA.
KEEP UPWIND FROM FIRE.

Unusual Fire/Explosion Hazard: HEATED CONTAINERS CAN DEVELOP PRESSURE AND
EXPLODE. THE PRODUCT SHOULD BE HANDLED AS A COMBUSTIBLE MATERIALS.

=====
Control Measures
=====

Respirator

Protection: ORGANIC CHEMICAL CARTRIDGE RESPIRATOR. NIOSH/MSHA
APPROVED.

Ventilation: LOCAL EXHAUST SYSTEM AND GOOD GENERAL VENTILATION. USE ADEQUATE
VENTILATION IN ENCLOSED AREAS.

Protective Gloves: IMPERVIOUS GLOVES, RUBBER OR VINYL

Eye Protection: SFTY GOGGLES OR FACE SHIELD. ANSI APPRVD

Other Protective Equipment: RUBBER PROTECTIVE GARMENTS TO PREVENT SKIN OR
CLOTHING CONTACT. EYE WASHES.

Work Hygienic Practices: GOOD PERSONL HOUSEKEEP & PERSONL CLEANLINESS. WASH
CONTAM CLOTH BEFORE
REUSE. DISCARD HEAVILY CONTAM CLOTHING & LEATHER.

=====
Physical/Chemical Properties
=====

Spec Gravity: 1.1 (WATER=1)

Solubility in Water: SLIGHT

Appearance and Odor: LIGHT STRAW COLORED LIQUID WITH A CHARACTERISTIC ODOR

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To

Avoid: TEMPERATURES OVER 110 F.
Materials To Avoid: STRONG OXIDIZING AGENTS
Hazardous Decomposition Products: OXIDES OF CARBON AND SMOKE
Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

R

Responsible Party Code: DO082
Trans ID NO: 83412
Product ID: EPOXY GROUT, PART A
MSDS Prepared Date: 04/19/1994
Review Date: 06/16/1994
MFN: 1
Multiple KIT Number: 0
Kit Part IND: Y
Review IND: Y
Unit Of Issue: KT
Container QTY: 1
Additional Data: * UNIT OF ISSUE CONTAINER QUANTITY: 2.5 GALLON TOTAL MIXED
MATERIAL IN A FIVE GALLON CONTAINER

=====
Detail DOT Information
=====

DOT PSN Code: ZZZ
DO

T Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
Detail IMO Information
=====

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS
MODE OF TRANSPORTATION

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====
HAZCOM Label
=====

Product ID: EPOXY GROUT, PART A

Cage: DO082

Assigned IND: Y

Company Name: BONDED PRODUCTS, INC

Street: 439 SOUTH BOLMAR STREET

PO Box: 39

City: WEST CHESTER PA

Zipcode: 19381-0039

Health Emergency Phone: 610-696-9220

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: SKIN: POSSIBLE IRRITATION AND SENSITIZATION ON
PROLONGED AND REPEATED CONTACT. EYES: IRRITATION OF EYES ON PROLONGED AND
REPEATED EXPOSURE. INHALATION: NAUSEA AND HEADACHE. INGESTION: ABDOMINAL
DISCOMFORT.

SKIN IRRITATION, NAUSEA, AND HEADACHE. VAP

ORS MAY IRRITATE
RESPIRATORY PASSAGES.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.