View NSN Online: https://aerobasegroup.com/nsn/8030-01-041-1606

## QCM COMPANY -- A-1104 PRIMER FOR PLASTISOL COATINGS -- 8030-01-041-1606

Product ID:A-1104 PRIMER FOR PLASTISOL COATINGS

MSDS Date:05/20/1994

FSC:8030

NIIN:01-041-1606

Kit Part:Y

MSDS Number: BTWDF === Responsible Party ===

Company Name: QCM COMPANY

Address:930 SOUTH CENTRAL AVENUE

City:KENT State:WA ZIP:98032 Country:US

Info Phone Num: 206-859-0933

**Emergency Phone** 

Num:206-859-0933/800-424-9300 CHEMTREC

Preparer's Name: ROY WHEELDON

CAGE:8L872

=== Contractor Identification ===

Company Name:Q C M CO Address:930 CENTRAL AVE S

Box:City:KENT

State:WA

ZIP:98032-6105 Country:US

Phone:253-859-0933, FAX 253-859-0935

CAGE:8L872

======= Composition/Information on Ingredients ========

Ingred Name: METHYL ETHYL KETONE (SARA III) (SEC 304: FINAL RQ 5000 LBS)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 61.8%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200

PPM ACGIH TLV:200 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ETHANOL (SEC 304: FINAL RQ 100 LBS)

CAS:64-17-5

RTECS #:KQ6300000 Fraction by Wt: 20%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1000 PPM ACGIH TLV:1000 PPM

Ingred Name: VOC PER LITER: 5.78 LBS/GAL (692 GRAMS/LITER); VOC PER LITER MINUS EXEMPT SOLVENTS & WATER: 5.78 LBS/GAL

RTECS #:9999999VO

Other REC Limits: NONE RECOMMENDED

Routes of Entry: Inh

alation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: SKIN, EYE, RESPIRATORY AND

GASTROINTESTINAL IRRITATION, POSSIBLY SEVERE. EXCESSIVE INHALATION

MAY PRODUCE CENTRAL NERVOUS SYSTEM DEPRESSION.

First Aid:EYE CONTACT: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION. SKIN CONTACT: REMOVE CONTAMINAT

ED CLOTHING. WASH THOROUGHLY WITH SOAP AND WATER. INHALATION: SEEK IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE

VOMITING.

========== Fire Fighting Measures ===============

Flash Point Method:TCC Flash Point:16.0F,-8.9C

Lower Limits: 1.8 Upper Limits: 19.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL

Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE. COOL CONTAINERS IN VICINITY WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:KEEP

| ALL CONTAINERS. VAPORS MAY TRAVEL TO SOURCE OF IGNITION AND CAUSE FLASHBACK. FIRE CAUSES ACID SMOKE AND/OR FUMES.   |
|---|
| ======== Accidental Release Measures ==========   |
| Spill Release Procedures:REMOVE ALL IGNITION SOURCES. SMALL SPILLS:<br>TAKE UP WITH ABSORBENT MATERIAL. LARGE SPILLS: DAM AND RECOVER.  |
| =========== Handling and Storage =============  |
| Handling and Storage Precautions: AVOID HIGH TEMPERATURE AREA AND   |
| IGNITION SOURCES. ALL HANDLING EQUIPMENT SHOULD BE GROUNDED AND EXPLOSION PROOF. AVOID ALL PERSONAL CONTACT. Other Precautions:WASH THOROUGHLY AFTER HANDLING.  |
| ====== Exposure Controls/Personal Protection ========   |
| Respiratory Protection:USE APPROVED SELF-CONTAINED BREATHING APPARATUS IF NECESSARY.  Ventilation:LOCAL EXHAUST: NECESSARY. MECHANICAL (GENERAL): NECESSARY. Protective Gloves:RUBBER OR NEOPRENE Eye Protection:CHEMICAL SPALSH GOGGLES  Other Protective Equipment:SA FETY SHOWER. EYE WASH STATION. Supplemental Safety and Health   |
| ======== Physical/Chemical Properties ==========  |
| Boiling Pt:B.P. Text:165F,74C Vapor Pres:85 @ 20C Vapor Density:2.4 Spec Gravity:0.86 (WATER=1) Evaporation Rate & Description |
| ========= Stability and Reactivity Data =========   |
| Stability Indicator/Materials to Avo  |

ALL IGNITION SOURCES AWAY. GROUND

id:YES STRONG OXIDIZING AGENTS

Stability Condition to Avoid:STRONG ACIDS OR OXIDIZERS, HIGH TEMPERATURES

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, MISCELLANEOUS HYDROCARBON

Conditions to Avoid Polymerization:STRONG OXIDIZERS, ALL IGNITION SOURCES.

======= Disposal Considerations ===========

Waste Disposal Methods: ACCORDING TO STATE, FEDERAL, AND LOCAL REGULATIONS. HAZARDOUS WASTE CODE: F005, D001, U159, FLAMMABLE.

## Disclaimer (pr

ovided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.