

SOUTH COAST TERMINALS, INC -- HYDRAULIC FLUID,AUTOMATIC TRANSMISSION,DEXRON III --
9150-01-114-9968

===== Product Identification =====

Product ID:HYDRAULIC FLUID,AUTOMATIC TRANSMISSION,DEXRON III

MSDS Date:09/08/1994

FSC:9150

NIIN:01-114-9968

MSDS Number: BTWFJ

=== Responsible Party ===

Company Name:SOUTH COAST TERMINALS, INC

Address:7401 WALLISVILLE ROAD

Box:15535

City:HOUSTON

State:TX

ZIP:77020

Country:US

Info Phone Num:713-672-2401 EXT 232

Emergency Phone Num:713-672-2401/800-424-9300(CHEMTREC)

CAGE:1L506

=== Contractor Identification ===

Company Name:SOUTH COAST TERMINALS, INC

Address:7401 WALLISVILLE ROAD

Box:15535

City:HOUSTON

State:TX

ZIP:77020

Country:US

Phone:713-672-2401/800-424-9300(CHEMTREC)

CAGE:1L506

===== Composition/Information on Ingredients =====

Ingred Name:LUBRICATING OIL BASE STOCK

CAS:64791-97-5

Fraction by Wt: 80 - 90%

Other REC Limits:NONE REC

RECOMMENDED
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST

Ingredient Name:TRADE SECRET COMPONENT
Fraction by Wt: 10 - 20%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY &
GI TRACTS. ACUTE- MAY CAUSE EYE IRRITATION,
BURNING.
PROLONGED/REPEATED SKIN CONTACT MAY CAUSE IRRITATION. INHALATION OF
MIST MAY CAUSE IRRITATION. INGESTION MAY CAUSE GASTROINTESTINAL
TRACT IRRITATION. CHRONIC- MAY CAUSE DERMATITIS, BURNING, REDNESS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, BURNING, REDNESS, TEARING, NAUSEA
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:MOVE TO FRESH
AIR. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN.
SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. SEEK
MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:392F,200C
Extinguishing Media:WATER FOG/SPRAY, CARBON DIOXIDE, FOAM/DRY CHEMICAL.
DIRECTLY SPRAYING WATER/FOAM ONTO BURNING OIL MAY CAUSE FROTHING.
Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA
WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:PICK UP SPILL WITH INERT MATERIAL SUCH AS
SAND, CLAY, EARTH. SHOVEL INTO CONTAINERS FOR DISPOSAL. PREVENT
RUN-OFF TO ENTER WATERWAYS, SEWERS. SPILLS MAY NEED TO BE REPORTED
TO THE NATIONAL

RESPONSE CENTER (800-424-8802).

Neutralizing Agent:NOT RELEVANT

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL, DRY, VENTILATED PLACE,
AWAY FROM STRONG OXIDIZING AGENTS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:AVOID CONTACT WITH EYES AND SKIN. WASH THOROUGHLY
AFTER HANDLING. LAUNDRY CLOTHING BEFORE REUSE. AVOID INHALING
MISTS. DO NOT TAKE INTERNALLY.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY REQUIRED. IF WORKING IN CONFINED
AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES
EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS (PEL), WEAR
NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR.

Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL
BELOW APPLICABLE STANDARD(S).

Protective Gloves:NITRILES FOR PROLONGED/REPEATED CONTACT

Eye Protection:SAFETY GOGGLES IF SPLASHING ANTICIPATED

Other Protective

Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DISCARD CONTAMINATED LEATHER GLOVES AND
SHOES.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:>428F,>220C

Vapor Pres:1

Spec Gravity:0.87 - 0.88

Solubility in Water:NEGLIGIBLE

Appearance

and Odor:DARK AMBER LIQUID - MILD ADDITIVE ODOR

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:EXTREME HEAT

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
OXIDES OF SULFUR, PHOSPHORUS AND NITROGEN

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF IN AN APPROPRIATE DISPOSAL FACILITY
IN COMPLIANCE

E WITH LOCAL, STATE AND FEDERAL REGULATIONS.
INCINERATION IS RECOMMENDED. TREAT AS AN OIL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify
and
assume responsibility for the suitability of this information to their
particular situation.