

GARDCO DIVERSIFIED, INC. -- TT-L-20A GRAY, 36231 -- 8010-00-515-1568

=====  
Product Identification  
=====

Product ID:TT-L-20A GRAY, 36231

MSDS Date:01/25/1994

FSC:8010

NIIN:00-515-1568

MSDS Number: BTZZQ

=== Responsible Party ===

Company Name:GARDCO DIVERSIFIED, INC.

Address:228-B PATTERSON AVENUE

City:HAMPTON

State:VA

ZIP:23669

Country:US

Info Phone Num:804-722-9155

Emergency Phone Num:804-722-9155

5

Preparer's Name:BJG

CAGE:DO292

=== Contractor Identification ===

Company Name:GARDCO DIVERSIFIED, INC

Address:228-B PATTERSON AVENUE

City:HAMPTON

State:VA

ZIP:23669

Phone:804-722-9155

CAGE:DO292

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III) (VAPOR PRESSURE 4.2 MM HG @ 68F)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 16%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingre

d Name:METHYL ETHYL KETONE (SARA III) (VAPOR PRESSURE 70 MM HG @ 68F)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 12%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (VAPOR PRESSURE 33 MM HG @ 68F)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 9%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM

Ingred Name:XYLENE (SARA III) (VAPOR PRESSURE 4.2 MM HG @ 68F)

CAS:1330-20-7

RTECS

#:ZE2100000

Fraction by Wt: 3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ACETATE

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 7%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:LAMP BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 1%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3

Ingred Name:DIATOMAC

EOUS SILICA  
CAS:68855-54-9  
Fraction by Wt: 15%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:VOC: 469 GRAMS/LITER (3.90 LBS/GAL)  
RTECS #:9999999VO  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL:NASAL & RESPIRATORY IRRIT,  
DIZZINESS, FATIGUE, NAUSEA, HE  
ADACHE, UNCONSCIOUSNESS,  
ASPHYXIATION. SKIN:PROLONGED/REPEATED CONTACT:IRRIT.  
ABSORPTION:POTENTIAL HAZARD. EYE:SEVERE IRRIT, REDNESS, TEA RING,  
BLURRED VISION. INGEST:GI IRRIT, NAUSEA, VOMITING, DIARRHEA,  
ASPIRATION INTO LUNG:CHEM PNEUMONITIS-CAN BE FATAL.  
Effects of Overexposure:ACUTE: IRRITATION OF SKIN, EYES, MUCOUS  
MEMBRANES, DRYING, DEFATTING OF SKIN. AVOID INGESTION AND BREATHING  
OF VAPORS. CHRONIC: EYE, LIVER, KIDNEY, AND CENTRAL NERVOUS SYSTEM  
DAMAGE MAY OCCUR

Medical Cond Aggravated by Exposure:MAY PROVOKE ASTHMATIC RESPONSE IN  
PERSON WITH ASTHMA WHO ARE SENSITIVE TO AIRWAY IRRITANT.

=====  
===== First Aid Measures =====

First Aid:IF SPILLED ON SKIN OR IN EYE, WASH WITH COPIOUS QUANTITIES OF  
WATER, CONTACT PHYSICIAN IF SPILLED IN EYE. IF INGESTED, DO NOT  
INDUCE VOMITING, KEEP PERSON WARM, QUIET AND CONTACT PHYSICIAN.  
BREATHING: REMOVE PERSON TO FRESH AIR GIVE OXYGENIF BREATHING  
DIFFICULT; GIVE AR  
TIFICAL RESPIRATION IF BREATHING STOPS. KEEP  
PERSON WARM AND GET MEDICAL HELP.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:>24F,>-4C  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS W/FULL  
FACE PIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE  
MODE WHEN FIGHTING FIRES.  
Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR MAY TRAVEL ALONG  
GROUND O

R MOVED BY VENT & IGNITED BY HEAT, PILOT LIGHTS, FLAMES, & IGNITION SOURCES AT LOCATIONS DISTANT FROM SOURCE.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE UP AND CONTAIN SPILL WITH INERT MATERIAL, MOP UP AND PLACE MATERIAL INTO CONTAINERS. PREVENT RUN-OFF TO SEWER, STREAMS. NOTIFY AUTHORITIES.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE/USE IN HIGH TEMP AREAS OR

NEAR HEAT, SPARK, FLAME. KEEP CLOSURE TIGHT & CONTAINER UPRIGHT TO PREVENT LEAK. STORE IN VENTED AREA.

Other Precautions:AVOID CONTACT WITH OR BREATHING OF VAPORS RELEASED DURING CURING PROCESS. DO NOT TAKE INTERNALLY. AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING OF VAPORS OR SPRAY MIST. ALL HAZARD PRECAUTIONS GIVE N IN MSDS MUST BE OBSERVED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ABOVE TLV,NIOSH/MSHA AIR SUPPL  
D RESPIRATION

ADVISED IN ABSENCE OF ENVIRONMENTAL CONTROL. OSHA REGS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATOR UNDER SPECIFIED CONDITIONS (SEE SFTY EQUIP SUPPLIER).IMPLE MENT ENGINEERING/ADMINISTRATIVE CONTROL.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL &/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:WEAR RESISTANT GLOVES (NITRILE RUBBER)

Eye Protection:CHEM SPLASH GOGGLES.CHECK OTHER PERMITD.

Other Protective Equipment:TO PREVENT REPEAT  
ED OR PROLONGED SKIN

CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 314F

Vapor Density:> AIR

Spec Gravity:1.12 (WATER=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NOT SOLUBLE

Appearance and Odor:GRAY VISCOUS LIQUIDS WITH LACQUER SOLVENT ODOR

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: NEVER USE WELDING OR CUTTING TORCH ON/NEAR DRUMS (EVEN EMPTY) BECAUSE PRODUCT (EVEN RESIDUE) CAN IGNITE EXPLOSIVELY.

===== Disposal Considerations =====

Waste Disposal Methods: SMALL: ALLOW VOLATILE PART TO EVAPORATE IN HOOD. ALLOW TIME FOR VAPOR TO CLEAR HOOD DUCT. DISPOSE OF REMAINING MAT'L

IN ACCORD W/REGS. LRG: DESTROY BY LIQ INCINERATION. CONTAM ABSORBENT MAY BE DEPOSITED IN LANDFILL IN ACCORD W/LOCAL, STATE, & FED REGS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should

seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.