

DEL PAINT MFG -- ENAMEL, WHITE 17886 -- 8010-00-901-8035

===== Product Identification =====

Product ID:ENAMEL, WHITE 17886

MSDS Date:08/30/1993

FSC:8010

NIIN:00-901-8035

MSDS Number: BVBGP

=== Responsible Party ===

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Info Phone Num:405-672-1431

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name

:ONEY FLEMING

CAGE:39934

=== Contractor Identification ===

Company Name:DEL PAINT MFG

Address:3105 EAST RENO

Box:City:OKLAHOMA CITY

State:OK

ZIP:73117

Country:US

Phone:405-672-1431

CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATES

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 27.66%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:XYLENE (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt:

0.24%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NON-HAZARDOUS INGREDIENTS
Fraction by Wt: 72.10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC: 3.25 LB/GAL; 390 G/L
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE CONTACT: IRRITATION, REDNESS,
TEARING, AND BLURRED VISION. SKIN CONTACT: PROLONG OR REPEATED
EXPOSURE CAN CAUSE MODERATE IRRITATION, DEFATTING, AND DERMATITIS.
INHALATION: NASAL AND RESPIRATORY IRRITATION, DIZZINESS, NAUSEA,
& HEADACHE. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION,
NAUSEA, VOMITING, DIARRHEA.
Effects of Overexposure:IF TLV'S ARE EXCEEDED SKIN CONTACT PRODUCES
REDNESS. EYE CONTACT PRODUCES REDNESS AND PAIN. INHALATION GIVES
LABORED BREATHING, DULLNESS, DROWSINESS, INGESTION CAN CAUSE
ABDOMINAL PAIN AND NAUSEA.
Medical Condition Aggravated by Exposure:DISEASES OF THE RESPIRATORY SYSTEM.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH CLEAN, WARM WATER FOR AT LEAST 15
MINUTES, OCCASIONALLY LIFTING EYELIDS. SEEK MEDICAL ATTENTION. SKIN
CONTACT: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED SKIN AREAS
WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH
AIR, ADMINISTER
OXYGEN IF NECESSARY, SEEK MEDICAL ATTENTION. INGESTION: KEEP PERSON
WARM, QUIET AND GET MEDICAL ATTENTION. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:115F,46C
Autoignition Temp:Autoignition Temp Text:540F
Lower Limits:1
Upper Limits:6
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM. WATER MAY
SPREAD FIRE, USE WATER SPRAY ONLY TO COOL CONTAINERS EXPOSED TO
FIRE.
Fire F

ighting Procedures:SCBA RECOMMENDED FOR FIRE FIGHTERS. WATER
SPRAY MAY BE USED FOR COOLING CONTAINERS TO PREVENT PRESSURE BLDUP
& AUTOIGNITION OR EXPLOSION WITH EXTREME HEAT.

Unusual Fire/Explosion Hazard:VAPOR HEAVIER THAN AIR. MAY TRAVEL ALONG
GROUND OR MOVED BY VENT & IGNITED BY PILOT LIGHT, OTHER FLAMES,
SPARKS, HEATERS, SMOKING, & OTHER REMOTE IGNIT SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE THE AREA. COV
ER SPILL WITH INERT
ABSORBENT MATERIAL AND SHOVEL WITH NON-SPARKING TOOLS INTO
CONTAINER. REMOVE CONTAINER TO A SAFE AREA AND SEAL.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN DRY AREA. KEEP AWAY
FROM FOOD PRODUCTS. KEEP AWAY FROM SPARKS, FIRE AND REMOTE IGNITION
SOURCES.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM
CHILDREN. ALL EQUIPMENT SHOULD BE GROUNDED
TO REDUCE STATIC
ELECTRICITY HAZARD. USE NON-SPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV OF THE PRODUCT OR ANY COMPONENT IS
EXCEEDED, USE A RESPIRATOR WITH APPROPRIATE CARTRIDGES (NIOSH
APPROVED). ENGINEERING OR MANAGEMENT CONTROLS SHOULD BE IMPLEMENTED
TO REDUCE EXPOSURE.

Ventilation:LOCAL EXHAUST MUST BE SUFFICIENT TO KEEP AIRBORNE VAPOR
CONCENTRATIONS BELOW THE TLV LIMIT.

Protective Gloves:CHEMICAL RES
ISTANT GLOVES

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:SOURCE OF CLEAN WATER SHOULD BE AVAILABLE IN
WORK AREA FOR FLUSHING EYES & SKIN. WEAR IMPERVIOUS CLOTHING AS
NEEDED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300F,149C

Decomp Temp:Decomp Text:752F,400C

Vapor Pres:2.58

Vapor Density:> AIR

Spec Gravity:1.23 (WATER=1)

Viscosity:77-86 KU

Evaporation Rate & Reference:SLO

WER THAN ETHER

Solubility in Water:NO

Appearance and Odor:WHITE LIQUID WITH MILD ODOR

Percent Volatiles by Volume:45.97

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT STORE NEAR HEATED SURFACES, OPEN
FLAMES OR IGNITION SOURCES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON
DIOXIDE.

===== Disposal Consi
derations =====

Waste Disposal Methods:WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE
WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATORY CONTROLS.
HAZARDOUS WASTE CHARACTERISTIC: IGNITABILITY. EPA HAZARDOUS WASTE
CODE: NONE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warra
nts this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.