

DYNATRON/BONDO CORPORATION -- 6294 DENT FILLER, COMPONENT B -- 8030-00-926-2133
===== Product Identification =====

Product ID:6294 DENT FILLER, COMPONENT B
MSDS Date:04/12/1994
FSC:8030
NIIN:00-926-2133
Kit Part:Y
MSDS Number: BVBGZ
=== Responsible Party ===
Company Name:DYNATRON/BONDO CORPORATION
Address:3700 ATLANTA, INDUSTRIAL PARKWAY, NW
City:ATLANTA
State:GA
ZIP:30331
Country:US
Info Phone Number:404-699-0073;696-2730/ 800-241-3386
Emergency Phone Num:800-424-8300 CHEMTREC
Preparer's Name:M WHEELock
CAGE:16522
=== Contractor Identification ===
Company Name:BONDO/MAR-HYDE CORP
Address:3700 ATLANTA INDUSTRIAL PKWY NW
Box:City:ATLANTA
State:GA
ZIP:30331
Country:US
Phone:404-696-2730
CAGE:16522

===== Composition/Information on Ingredients =====

Ingred Name:DIBENZOYL PEROXIDE (SARA III)
CAS:94-36-0
RTECS #:DM8575000
Fraction by Wt: 50%
Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3--10 HR SHIFT
ACGIH TLV:5 MG/M3--10 HR SHIFT

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYE IRRITATION, MINOR SKIN IRRITATION. CHRONIC: NONE KNOWN.
Effects of Overexposure:EYES: MAY CAUSE EYE IRRITATION. SKIN: PROLONGED SKIN CONTACT MAY CAUSE SKIN IRRITATION AND REDNESS. INHALATION: MAY CAUSE IRRITATION OF THE NOSE, THROAT, AND LUNG. INGESTION: MAY CAUSE TOXIC EFFECTS.
Medical Cond Aggravated by Exposure:NO INFORMATION FOUND

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES & CONTACT A PHYSICIAN. SKIN: WASH IMMEDIATELY WITH SOAP & WATER. CONSULT A PHYSICIAN IF DISCOMFORT DEVELOPS. INHALATION: REMOVE TO FRESH AIR. CONSULT A PHYSICIAN IF DISCOMFORT PERSISTS. INGESTION: ADMINISTER LARGE QUANTITIES OF WATER IF PERSON IS CONSCIOUS. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. IMMEDIATELY CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:>200F,>93C
Extinguishing Media:WATER FOG OR SPRAY, CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:EVACUATE AREA AND APPLY WATER FROM A SAFE DISTANCE.
Unusual Fire/Explosion Hazard:PEROXIDES AND DECOMPOSITION PRODUCTS ARE FLAMMABLE AND CAN IGNITE WITH EXPLOSIVE FORCE IF CONFINED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:AVOID CONTACT WITH SKIN. MATERIAL LEFT UNCOVERED COULD INCREASE FIRE HAZARD DUE TO EVAPORATION OF WATER & LEACHING OF PLASTICIZER AWAY FROM BENZOYL PEROXIDE. DIKE TO PREVENT RUNOFF FROM ENTERING DRAIN S, SEWERS, STREAMS, ETC. TRANSFER INTO CONTAINER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM ALL SOURCES OF HEAT AND IGNITIO

N SUCH AS RADIATORS, STEAM PIPES AND DIRECT SUNLIGHT. DO NOT STORE NEAR COMBUSTIBLES.

Other Precautions:DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING. DO NOT BREATHE VAPORS. KEEP CONTAINERS CLOSED. KEEP FROM FREEZING. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED IF TLVS ARE EXCEEDED

Ventilation:MECHANICAL

Protective Gloves:NEOPRENE OR POLYVINYL ALCOHOL

Eye Protection:CHEMICAL

SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:EYE WASH STATION SHOULD BE AVAILABLE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Decomp Temp:Decomp Text:200F,93C

Spec Gravity:1.2+/- 0.15@77F

Viscosity:250,000 CPS

Solubility in Water: